

Part Number	Model Name / Description	Type	Flow		Length (A)		OUTPUT (B)		FEED O.D. (C)		Average NaCl rejection	Minimum NaCl rejection	Average MgSO4I rejection	Minimum MgSO4 rejection	Shipping Weight		Membrane Active Area		Max. Pressure		Max. Temperature	
			gpd	m³ / day	inch	cm	inch	cm	inch	cm	%	%	%	%	lbs	kg	ft²	m²	psi	KPa	°F	°C
80766	BW30-2540	Brackish Water	850	3.2	40	101.6	3.9	9.91	0.75	1.9	99.50				0.0		28	2.6	600	4136.87	113	45.0
	BW30-2540	Brackish Water	650	2.4	40	101.6	2.4	6.10	0.75	1.9	99.00				0.0			0.0	600	4136.87	113	45.0
	BW30-330	Brackish Water	7500	28.3	40	101.6	7.9	20.07	0.75	1.9	99.00				0.0			0.0	600	4136.87	113	45.0
80773	BW30-365	Brackish Water	9500	35.8	40	101.6	7.9	20.07	1.125	2.9	99.50				0.0		365	33.9	600	4136.87	113	45.0
369692	BW30-365-IG	Brackish Water	9500	35.8	40	101.6	7.9	20.07	1.125	2.9	99.00				0.0		365	33.9	600	4136.87	113	45.0
98650	BW30-400	Brackish Water	10500	39.6	40	101.6	7.9	20.07	1.125	2.9	99.50				0.0		400	37.1	600	4136.87	113	45.0
248151	BW30-400-34i	Brackish Water	10500	39.6	40	101.6	7.9	20.07	1.125	2.9	99.50	99.00			0.0		400	37.1	600	4136.87	113	45.0
369695	BW30-400-IG	Brackish Water	10500	39.6	40	101.6	7.9	20.07	1.125	2.9	99.00				0.0		400	37.1	600	4136.87	113	45.0
	BW30-4040	Brackish Water	2200	8.3	40	101.6	3.9	9.91	0.75	1.9	99.00				0.0			0.0	600	4136.87	113	45.0
80783	BW30-4040	Brackish Water	2400	9.0	40	101.6	3.9	9.91	0.75	1.9	99.50				0.0		78	7.2	600	4136.87	113	45.0
249107	BW30-440i	Brackish Water	11500	43.3	40	101.6	7.9	20.07	1.125	2.9	99.00				0.0		440	40.8	600	4136.87	113	45.0
174961	BW30FR-365	Low Fouling	9500	35.8	40	101.6	7.9	20.07	1.125	2.9	99.00				0.0		365	33.9	600	4136.87	113	45.0
202681	BW30FR-400	Brackish Water	10500	39.6	40	101.6	7.9	20.07	1.125	2.9	99.00				0.0		400	37.1	600	4136.87	113	45.0
273805	BW30FR-400-34i	Brackish Water	10500	39.6	40	101.6	7.9	20.07	1.125	2.9	99.50	99.00			0.0		400	37.1	600	4136.87	113	45.0
	BW30HP-4040	Brackish Water	2800	10.6	40	101.6	3.9	9.91	0.75	1.9	99.00				0.0			0.0	600	4136.87	113	45.0
	BW30HR-440i	Brackish Water	12650	47.7	40	101.6	7.9	20.07	1.125	2.9	99.70	99.40			0.0		440	40.8	600	4136.87	113	45.0
	BW30LE-4040	Brackish Water		0.0		0.0		0.00		0.0					0.0			0.0	0.00			0.0
	BW30LE-440	Brackish Water	11500	43.3	40	101.6	7.9	20.07	1.5	3.8	99.00				0.0			0.0	600	4136.87	113	45.0
	BW30LE-440	Brackish Water	11500	43.3	40	101.6	7.9	20.07	1.125	2.9	99.00				0.0		440	40.8	600	4136.87	113	45.0
347733	HRLE-440i	Brackish Water	12650	47.7	40	101.6	7.9	20.07	1.125	2.9	99.50	99.30			0.0		440	40.8	600	4136.87	113	45.0
170701	HSRO-390-FF	Semi-Conductor	9000	33.9	40	101.6	7.9	20.07	1.125	2.9	99.50				0.0		390	36.2	600	4136.87	113	45.0
98592	HSRO-4040-FF	Semi-Conductor	1900	7.2	40	101.6	3.9	9.91	0.75	1.9	99.50				0.0		90	8.3	600	4136.87	113	45.0
343771	LC-HR-4040	Brackish Water	2900	10.9	40	101.6	3.9	9.91	0.75	1.9	99.70	99.50			0.0		94	8.7	600	4136.87	113	45.0
356603	LC-LE-4040	Brackish Water	2500	9.4	40	101.6	3.9	9.91	0.75	1.9	99.20	99.10			0.0		94	8.7	600	4136.87	113	45.0
249109	LE-400	Brackish Water	11500	43.3	40	101.6	7.9	20.07	1.125	2.9	99.30	99.00			0.0		400	37.1	600	4136.87	113	45.0
246670	LE-400i	Brackish Water	12650	47.7	40	101.6	7.9	20.07	1.125	2.9	99.30	99.00			0.0		440	40.8	600	4136.87	113	45.0
275173	LE-4040	Brackish Water	2500	9.4	40	101.6	3.9	9.91	0.75	1.9	99.00				0.0		78	7.2	600	4136.87	113	45.0
246670	LE-440i	Brackish Water	12650	47.7	40	101.6	7.9	20.07	1.125	2.9	99.30	99.00			0.0		440	40.8	600	4136.87	113	45.0
231653	LP-2540	Brackish Water	1000	3.8	40	101.6	2.4	6.10	0.75	1.9	99.20				0.0		28	2.6	600	4136.87	113	45.0
212819	LP-4040	Brackish Water	2900	10.9	40	101.6	3.9	9.91	0.75	1.9	99.20				0.0		78	7.2	600	4136.87	113	45.0
	NF200-400	Nano-Filtration		0.0	40	101.6		0.0		0.0					0.0			0.0	600	4136.87	113	45.0
15138	NF-2540	Nano-Filtration	920	3.5	40	101.6	2.4	6.1	0.75	1.9					0.0		28	2.6	600	4136.87	113	45.0
149986	NF270-2540	Nano-Filtration	850	3.2	40	101.6	2.4	6.1	0.75	1.9	97.0				0.0		28	2.6	600	4136.87	113	45.0
148822	NF270-400	Nano-Filtration	14700	55.4	40	101.6	7.9	20.1	1.5	3.8					0.0		400	37.1	600	4136.87	113	45.0
149987	NF270-4040	Nano-Filtration	2500	9.4	40	101.6	3.9	9.9	0.75	1.9	97.0				0.0		82	7.6	600	4136.87	113	45.0
15144	NF400	Nano-Filtration	13700	51.6	40	101.6	7.9	20.1	1.125	2.9					0.0		400	37.1	600	4136.87	113	45.0
15143	NF-4040	Nano-Filtration	3050	11.5	40	101.6	3.9	9.9	0.75	1.9					0.0		82	7.6	600	4136.87	113	45.0
	NF-90	Nano-Filtration		0.0	40	101.6		0.0		0.0					0.0			0.0	0.00	113	45.0	
149982	NF90-2540	Nano-Filtration	680	2.6	40	101.6	2.4	6.1	0.75	1.9	97.0				0.0		28	2.6	600	4136.87	113	45.0
179985	NF90-400	Nano-Filtration	7500	28.3	40	101.6	7.9	20.1	1.5	3.8	95.0	85.0			0.0		400	37.1	600	4136.87	113	45.0
149983	NF90-4040	Nano-Filtration	2000	7.5	40	101.6	3.9	9.9	0.75	1.9	97.0				0.0		82	7.6	600	4136.87	113	45.0
	RO-3840-30FF	Sanitary		0.0	40	101.6		0.0		0.0					0.0			0.0	600	4136.87	113	45.0
116314	RO-390-FF	Sanitary	10800	40.7	40	101.6	7.9	20.07	1.125	2.9	99.50				0.0		390	36.2	600	4136.87	113	45.0
116314	RO-390-FF	Sanitary	10800	40.7	40	101.6	7.9	20.1	1.125	2.9	99.5				0.0		390	36.2	600	4136.87	113	45.0
84286	RO-4040-FF	Sanitary	2400	9.0	40	101.6	3.9	9.91	0.75	1.9	99.50				0.0		85	7.9	600	4136.87	113	45.0
84286	RO-4040-FF	Sanitary	2400	9.0	40	101.6	3.9	9.9	0.75	1.9	99.5				0.0		85	7.9	600	4136.87	113	45.0
272569	SG30-400-34i	Semi-Conductor	10200	38.4	40	101.6	7.9	20.07	1.125	2.9					0.0			0.0	600	4136.87	113	45.0
265606	SG30LE-400	Semi-Conductor	9500	35.8	40	101.6	7.9	20.07	1.125	2.9	99.50	99.20			0.0		400	37.1	600	4136.87	113	45.0
	SG30LE-430	Semi-Conductor		0.0		0.0		0.00		0.0					0.0			0.0	600	4136.87	113	45.0
272573	SG30LE-440i	Semi-Conductor	10000	37.7	40	101.6	7.9	20.07	1.125	2.9					0.0			0.0	600	4136.87	113	45.0
80733	SW30-2514	Sea-Water	150	0.6	14	35.6	2.4	6.10	0.75	1.9	99.40				2.0	0.9			1000	6894.78	113	45.0
80734	SW30-2521	Sea-Water	300	1.1	21	53.3	2.4	6.10	0.75	1.9	99.40				2.6	1.2		0.0	1000	6894.78	113	45.0
80737	SW30-2540	Sea-Water	700	2.6	40	101.6	2.4	6.10	0.75	1.9	99.40				4.9	2.2		0.0	1000	6894.78	113	45.0
113853	SW30-380	Sea-Water	9000	33.9	40	101.6	7.9	20.1	0.75	1.9	99.40				0.0		380	35.2	1000	6894.78	113	45.0
80740	SW30-4021	Sea-Water	600	2.3	21	53.3	3.9	9.9	0.75	1.9	99.40				6.0	2.7		0.0	1000	6894.78	113	45.0
80741	SW30-4040	Sea-Water	1950	7.3		0.0		0.0		0.0	99.40				0.0		80	7.4	1000	6894.78	113	45.0
	SW30-6040	Sea-Water	2100	7.9	40	101.6	5.97	15.2	1.5	3.8		99.0			0.0			0.0		0.00	113	45.0
	SW30-8040	Sea-Water	6000	22.6	40	101.6	7.9	20.1	1.125	2.9	99.10	98.60			0.0		300	27.8	1000	6894.78	113	45.0
	SW30HR-2514	Sea-Water	65	0.2	14	35.6	2.4	6.10	0.75	1.9	99.40				2.2	1.0		0.0	1000	6894.78	113	45.0
	SW30HR-2521	Sea-Water	130	0.5	21	53.3	2.4	6.10	0.75	1.9	99.40				2.6	1.2		0.0	1000	6894.78	113	45.0
	SW30HR-2540	Sea-Water	320	1.2	40	101.6	2.4	6.1	0.75	1.9	99.40				4.9	2.2		0.0	1000	6894.78	113	45.0
231995	SW30HR-320	Sea-Water	6000	22.6	40	101.6	7.9	20.1	1.125	2.9	99.75	99.60			0.0</							

Part Number	Model Name / Description	Type	Flow		Length (A)		OUTPUT (B)		FEED O.D. (C)		Average NaCl rejection	Minimum NaCl rejection	Average MgSO4I rejection	Minimum MgSO4 rejection	Shipping Weight		Membrane Active Area		Max. Pressure		Max. Temperature	
			gpd	m³ / day	inch	cm	inch	cm	inch	cm	%	%	%	%	lbs	kg	ft²	m²	psi	KPa	°F	°C
246512	SW30HRLE-400i	Sea-Water	7500	28.3	40	101.6	7.9	20.1	1.125	2.9	99.80	99.65			0.0		400	37.1	1200	8273.74	113	45.0
255048	SW30HR-LE-4040	Sea-Water	1600	6.0	40	101.6	3.9	9.9	0.75	1.9	99.75	91.00			0.0			0.0	1200	8273.74	113	45.0
	SW30HRLE-440i	Sea-Water	8200	30.9	40	101.6	7.9	20.1	1.125	2.9	99.80	99.65			0.0		440	40.8	1200	8273.74	113	45.0
259124	SW30ULE-400i	Sea-Water	11000	41.4	40	101.6	7.9	20.1	1.125	2.9	99.70	99.55			0.0		400	37.1	1200	8273.74	113	45.0
	SW30ULE-440i	Sea-Water	12000	45.2	40	101.6	7.9	20.1	1.125	2.9	99.70	99.55			0.0		440	40.8	1200	8273.74	113	45.0
293991	SW30XHR-400i	Sea-Water	6000	22.6	40	101.6	7.9	20.1	1.125	2.9	99.75	99.60			0.0		400	37.1	1200	8273.74	113	45.0
	SW30XHR-440i	Sea-Water	6600	24.9	40	101.6	7.9	20.1	1.125	2.9	99.82	99.70			0.0		440	40.8	1200	8273.74	113	45.0
219219	SW30XLE-400i	Sea-Water	9000	33.9	40	101.6	7.9	20.1	1.125	2.9	99.70	99.60			0.0		400	37.1	1200	8273.74	113	45.0
	SW30XLE-440i	Sea-Water	9900	37.3	40	101.6	7.9	20.1	1.125	2.9	99.70	99.60			0.0		440	40.8	1200	8273.74	113	45.0
	TW30-1514-10	Sea-Water	10	0.0		0.0		0.00		0.0					0.0			0.0		0.00		0.0
170102	TW30-1812-100	Drinking Water	100	0.4	11.74	29.8	1.75	4.45	0.68	1.7	90.00				0.0			0.0	300	2068.43	113	45.0
	TW30-1812-16	Drinking Water	16	0.1	11.74	29.8	1.75	4.45	0.68	1.7	98.00				0.0			0.0	300	2068.43	113	45.0
93430	TW30-1812-24	Drinking Water	24	0.1	11.74	29.8	1.75	4.45	0.68	1.7	98.00				0.0			0.0	300	2068.43	113	45.0
80719	TW30-1812-36	Drinking Water	36	0.1	11.74	29.8	1.75	4.45	0.68	1.7	98.00				0.0			0.0	300	2068.43	113	45.0
80722	TW30-1812-50	Drinking Water	50	0.2	11.74	29.8	1.75	4.45	0.68	1.7	98.00				0.0			0.0	300	2068.43	113	45.0
114731	TW30-1812-75	Drinking Water	75	0.3	11.74	29.8	1.75	4.45	0.68	1.7	98.00				0.0			0.0	300	2068.43	113	45.0
	TW30-2013	Tap Water	100	0.4	11.74	29.8	1.75	4.45	0.68	1.7	96.00				0.0			0.0	300	2068.43	113	45.0
80635	TW30-2026	Tap Water	220	0.8	26	66.0	1.8	4.57	0.68	1.7	99.50				0.0		7	0.6	600	4136.87	113	45.0
80639	TW30-2514	Tap Water	200	0.8	14	35.6	2.4	6.10	0.75	1.9	99.50				0.0		7	0.6	600	4136.87	113	45.0
80641	TW30-2521	Tap Water	325	1.2	21	53.3	2.4	6.10	0.75	1.9	99.50				0.0		13	1.2	600	4136.87	113	45.0
	TW30-2527	Tap Water	475	1.8	27	68.6	2.4	6.10	0.75	1.9	99.00				0.0			0.0	300	2068.43	113	45.0
80643	TW30-2540	Tap Water	850	3.2	40	101.6	2.4	6.10	0.75	1.9	99.50				0.0		28	2.6	600	4136.87	113	45.0
80605	TW30-4014	Tap Water	525	2.0	14	35.6	3.9	9.91	0.75	1.9	99.50				0.0		20	1.9	600	4136.87	113	45.0
80608	TW30-4021	Tap Water	900	3.4	21	53.3	3.9	9.91	0.75	1.9	99.50				0.0		36	3.3	600	4136.87	113	45.0
80610	TW30-4040	Tap Water	2400	9.0	40	101.6	3.9	9.91	0.75	1.9	99.50				0.0		78	7.2	600	4136.87	113	45.0
	TW30HP-2527	Tap Water	600	2.3	27	68.6	2.4	6.10	0.75	1.9	99.00				0.0			0.0	300	2068.43	113	45.0
	TW30HP-2540	Tap Water	650	2.4	40	101.6	2.4	6.10	0.75	1.9	99.00				0.0			0.0	300	2068.43	113	45.0
	TW30HP-4040	Tap Water	2800	10.6	40	101.6	3.9	9.91	0.75	1.9	99.00	98.00			0.0			0.0	300	2068.43	113	45.0
	TW30HP-4611	Tap Water	1200	4.5	11.32	28.8	4.61	11.71	0.75	1.9	99.00				0.0			0.0	600	4136.87	113	45.0
	TW30HP-4619	Tap Water	1450	5.5	19.2	48.8	4.61	11.71	0.75	1.9	99.00				0.0			0.0	600	4136.87	113	45.0
	TW30HP-4641	Tap Water	5200	19.6	41.31	104.9	4.61	11.71	0.75	1.9	99.00				0.0			0.0	600	4136.87	113	45.0
	TW30LE-4040	Tap Water	2340	8.8	40	101.6	3.9	9.91	0.75	1.9	99.20				0.0		87	8.1	600	4136.87	113	45.0
154530	XLE-2521	Low Energy	365	1.4	21	53.3	2.4	6.10	0.75	1.9	99.00				0.0		13	1.2	600	4136.87	113	45.0
154540	XLE-4021	Low Energy	1025	3.9	21	53.3	3.9	9.91	0.75	1.9	99.00				0.0		36	3.3	600	4136.87	113	45.0
154546	XLE-4040	Low Energy	2600	9.8	40	101.6	3.9	9.91	0.75	1.9	99.00				0.0		87	8.1	600	4136.87	113	45.0
101060	XLE-440	Brackish Water	12700	47.9	40	101.6	7.9	20.07	1.125	2.9	99.00				0.0		440	40.8	600	4136.87	113	45.0
347731	XLFRLE-400-34i	Brackish Water	11500	43.3	40	101.6	7.9	20.07	1.125	2.9	99.40	99.20			0.0		400	37.1	600	4136.87	113	45.0