



Pall-Fit Series Filter Elements

Upgrade JB Filter Elements to Pall Dynalloy® Filter Elements

Features

- Retrofit for JB¹ filter elements used in offshore applications
- Dynalloy sinter-bonded filter media
- Minimum collapse differential pressure – 268.9 bard (3900 psid) per ISO 2941
- All machined flow surfaces have 63 RMS finish
- Electropolished hardware
- Available in 10 and 40 micron (µm) grades, 98% efficiency
- All 316/316L SS construction
- Outside to inside flow
- Built to ISO 9001 standards

Performance Specifications

Filter Grades (98% efficiency):
10, 40 µm

Minimum Core Collapse Pressure:
268.9 bard (3900 psid) @ 121.1°C (250°F)

Maximum Operating Differential Pressure:²
P/N 132295-01 (63.5 mm/2.50" length):
127.6 bard (1850 psid) @ 121.1°C (250°F)

P/N 132294-01 (149.6 mm/5.89" length):
172.4 bard (2500 psid) @ 121.1°C (250°F)

Product Specifications

Materials of Construction:
Media: 316 Stainless Steel
Hardware: 316/316L Stainless Steel

Dimensions (nominal):
P/N 132295-01:
Outside diameter: 30.73 mm (1.21")
Length: 63.5 mm (2.50")

P/N 132294-01:
Outside diameter: 61.21 mm (2.41")
Length: 149.6 mm (5.89")

¹ JB Services International

² Maximum operating differential pressure recommended for outside to inside flow only.





Pall Fit Series 63.5 mm/2.50" and 149.6 mm/5.89" elements shown

Liquid Removal Ratings (µm)

Cartridge Designation	Nominal Efficiency
13229X-01-1405	98% @ ≥ 10 µm
13229X-01-H57T	98% @ ≥ 40 µm

Filter Element Differential Pressure vs. Flow



* 10 µm differential pressure based upon calculated value.

Part Numbers/Ordering Information

P/N 132295-01 (63.5 mm/2.50" length element)
132295-01- (e.g., 132295-01-1405)

P/N 132294-01 (149.6 mm/5.89" length element)
132294-01- (e.g., 132294-01-H57T)

Code 	Filter Media Grade Options
1405	10 µm
H57T	40 µm

LENNTECH

info@lennotech.com

www.lennotech.com

Tel. +31-15-261.09.00

Fax. +31-15-261.62.89

Pall Corporation has offices and plants throughout the world in locations including: Argentina, Australia, Austria, Belgium, Brazil, Canada, China, France, Germany, India, Indonesia, Ireland, Italy, Japan, Korea, Malaysia, Mexico, the Netherlands, New Zealand, Norway, Poland, Puerto Rico, Russia, Singapore, South Africa, Spain, Sweden, Switzerland, Taiwan, Thailand, United Kingdom, United States, and Venezuela. Distributors are located in all major industrial areas of the world.

© Copyright 2007, Pall Corporation. Pall, PALL, and Dynalloy are trademarks of Pall Corporation.

® Indicates a Pall trademark registered in the USA. *Filtration. Separation. Solution.*sm is a service mark of Pall Corporation.