



- **Integrated float switch:** makes the pump suitable for limited spaces.
- **Manual and automatic working**
- **Minimum draining level 2mm (man)**
- **Integrated check valve**

Model: **COMPAC 150**
 Part number: **N1080030**
 Barcode: **8010583317176**

Submersible pump for clear water. Motor shaft in stainless steel, single phase NORYL hydraulic system. COMPAC pumps are equipped with 10 m power cable with plug and can be used in manual or automatic version with float switch.


LENNTECH
WATER TREATMENT SOLUTIONS

info@lenntech.com Tel. +31-152-610-900
 www.lenntech.com Fax. +31-152-616-289

APPLICATIONS

Drainage of standing water and domestic waste water
 Flooded rooms emptying and drying
 Water drawing from wells, basins or cisterns

ABSORBED POWER	300 W	MAX TEMP. OF PUMPED FLUID	40°C
VOLTAGE	230 V	MAX.SIZE OF IMPURITIES	5 mm
FLOW RATE	8500 l/h	START/STOP	140 mm / 30 mm
MAX. HEAD	7 m	WEIGHT	4.7 kg
PUMP BODY	Polypropylene	PACKAGING DIMENSIONS	23 x 19.5 x 29 cm
PUMP OUTLET DIAMETER	41,90 mm (1 1/4 M)	PCS PER PALLET	60
MIN. DRAINING LEVEL	2 mm / 30 mm (man/aut)	ACCESSORIES	Adjustable connector/ check valve
MAX DEPTH OF IMMERSION	7 m		