

Part Number	Model Name / Description	Type	Flow		Length (A)		OUTPUT (B)		FEED O.D. (C)		Average NaCl rejection	Minimum NaCl rejection	Average MgSO4I rejection	Minimum MgSO4 rejection	Shipping Weight		Membrane Active Area		Max. Pressure		Max. Temperature	
			gpd	m³ / day	inch	cm	inch	cm	inch	cm	%	%	%	%	lbs	kg	ft²	m²	psi	KPa	°F	°C
	TM710D	Brackish water	2150	8.1	40	101.6	0.75	1.91	4	10.2	99.8						87	8.1	600	4136.87	113	45.0
	TM720DA400	Brackish water	8900	33.5	40	101.6	1.125	2.86	7.9	20.1	99.8						400	37.1	600	4136.87	113	45.0
	TM720D-400	Brackish water	8900	33.5	40	101.6	1.125	2.86	7.9	20.1	99.8						400	37.1	600	4136.87	113	45.0
	TM720D-440	Brackish water	9800	36.9	40	101.6	1.125	2.86	7.9	20.1	99.8						440	40.8	600	4136.87	113	45.0
	TM710	Brackish water	2400	9.0	40	101.6	0.75	1.91	4	10.2	99.7						87	8.1	600	4136.87	113	45.0
	TM720-370	Brackish water	9500	35.8	40	101.6	1.125	2.86	7.9	20.1	99.7						370	34.3	600	4136.87	113	45.0
	TM720-400	Brackish water	10200	38.4	40	101.6	1.125	2.86	7.9	20.1	99.7						400	37.1	600	4136.87	113	45.0
	TM720-430	Brackish water	11000	41.4	40	101.6	1.125	2.86	7.9	20.1	99.7						430	39.9	600	4136.87	113	45.0
	TM720-440	Brackish water	11000	41.4	40	101.6	1.125	2.86	7.9	20.1	99.7						440	40.8	600	4136.87	113	45.0
	TM720C-400	Brackish water	8200	30.9	40	101.6	1.125	2.86	7.9	20.1		98.2					400	37.1	600	4136.87	113	45.0
	TM720C-430	Brackish water	8800	33.2	40	101.6	1.125	2.86	7.9	20.1		98.2					430	39.9	600	4136.87	113	45.0
	TM720C-440	Brackish water	9000	33.9	40	101.6	1.125	2.86	7.9	20.1		98.2					440	40.8	600	4136.87	113	45.0
	TM720D-400	Brackish water	11000	41.4	40	101.6	1.125	2.86	7.9	20.1							400	37.1	600	4136.87	113	45.0
	TM720D-440	Brackish water	12100	45.6	40	101.6	1.125	2.86	7.9	20.1			99.7				440	40.8	600	4136.87	113	45.0
	TM720L-400	Brackish water	8500	32.0	40	101.6	1.125	2.86	7.9	20.1			99.0				400	37.1	600	4136.87	113	45.0
	TM720L-430	Brackish water	9200	34.7	40	101.6	1.125	2.86	7.9	20.1			99.0				430	39.9	600	4136.87	113	45.0
	TM720L-440	Brackish water	9400	35.4	40	101.6	1.125	2.86	7.9	20.1			99.0				440	40.8	600	4136.87	113	45.0
	TML20D-370	Brackish water	9700	36.6	40	101.6	1.125	2.86	7.9	20.1			99.7				370	34.3	600	4136.87	113	45.0
	TML20D-400	Brackish water	10500	39.6	40	101.6	1.125	2.86	7.9	20.1			99.7				400	37.1	600	4136.87	113	45.0
	TML20DA400	Brackish water	10500	39.6	40	101.6	1.125	2.86	7.9	20.1			99.7				400	37.1	600	4136.87	113	45.0
	TML20D-440	Brackish water	11500	43.3	40	101.6	1.125	2.86	7.9	20.1			99.7				440	40.8	600	4136.87	113	45.0
	SU-720	Brackish water	6900	26.0	40	101.6	1.125	2.86	7.9	20.1	99.4	99.0					300	27.8	290	1999.49	113	45.0
	SU-720F	Brackish water	8500	32.0	40	101.6	1.125	2.86	7.9	20.1	99.4	99.0					380	35.2	290	1999.49	113	45.0
	SU-720L	Brackish water	5800	21.9	40	101.6	1.125	2.86	7.9	20.1	99.0	98.0					300	27.8	220	1516.85	113	45.0
	SU-720LF	Brackish water	7100	26.8	40	101.6	1.125	2.86	7.9	20.1	99.4	99.0					380	35.2	290	1999.49	113	45.0
	SU-720R	Brackish water	5000	18.8	40	101.6	1.125	2.86	7.9	20.1	99.7	99.4							300	2068.43	113	45.0
	SU-710	Brackish water	1700	6.4	40	101.6	0.83	2.11	4	10.2			99.4				75	7.0	600	4136.87	113	45.0
	SU-710L	Brackish water	1500	5.7	40	101.6	0.83	2.11	4	10.2	99.0	98.0					75	7.0	600	4136.87	113	45.0
	SU-710R	Brackish water	1300	4.9	40	101.6	0.83	2.11	4	10.2	99.7	99.4					75	7.0	600	4136.87	113	45.0
	TMG10	Brackish water	2400	9.0	40	101.6	0.75	1.91	4	10.2	99.5	99.0					87	8.1	365	2516.59	113	45.0
	TMG20-370	Brackish water	9500	35.8	40	101.6	1.50	3.81	7.9	20.1	99.5	99.0					370	34.3	365	2516.59	113	45.0
	TMG20-400	Brackish water	10200	38.4	40	101.6	1.5	3.81	7.9	20.1	99.5	99.0					400	37.1	365	2516.59	113	45.0
	TMG20-430	Brackish water	11000	41.4	40	101.6	1.5	3.81	7.9	20.1	99.5	99.0					430	39.9	365	2516.59	113	45.0
	TMG20-440	Brackish water	11300	42.6	40	101.6	1.125	2.86	7.9	20.1	99.5	99.0					440	40.8	365	2516.59	113	45.0
	TMH10A	Brackish water	2400	9.0	40	101.6	0.75	1.91	4	10.2	99.3	99.0					87	8.1	365	2516.59	113	45.0
	TMH20A-370	Brackish water	10200	38.4	40	101.6	1.125	2.86	7.9	20.1	99.3	99.0					370	34.3	365	2516.59	113	45.0
	TMH20A-400	Brackish water	11000	41.4	40	101.6	1.125	2.86	7.9	20.1	99.3	99.0					400	37.1	365	2516.59	113	45.0
	TMH20A-430	Brackish water	11800	44.5	40	101.6	1.125	2.86	7.9	20.1	99.3	99.0					430	39.9	365	2516.59	113	45.0
	TMH20A-440	Brackish water	12100	45.6	40	101.6	1.125	2.86	7.9	20.1	99.3	99.0					440	40.8	365	2516.59	113	45.0
	TML10	Low Fouling	1850	7.0	40	101.6	0.75	1.91	4	10.2	99.7	99.0					73	6.8	600	4136.87	113	45.0
	TML10F	Low Fouling	2200	8.3	40	101.6	0.75	1.91	4	10.2	99.7	99.0					87	8.1	600	4136.87	113	45.0
	TML20-370	Low Fouling	9500	35.8	40	101.6	1.125	2.86	7.9	20.1	99.7	99.0					370	34.3	600	4136.87	113	45.0
	TML20-400	Low Fouling	10200	38.4	40	101.6	1.125	2.86	7.9	20.1	99.7	99.0					400	37.1	600	4136.87	113	45.0
	TML20-430	Low Fouling	11000	41.4	40	101.6	1.125	2.86	7.9	20.1	99.7	99.0					430	39.9	600	4136.87	113	45.0
	TML20N-400	Low Fouling	10200	38.4	40	101.6	1.125	2.86	7.9	20.1	99.7	99.0					400	37.1	600	4136.87	113	45.0
	TM820-370	Sea water	5800	21.9	40	101.6	1.125	2.86	7.9	20.1	99.7	99.5					370	34.3	1000	6894.78	45	17.9
	TM820-400	Sea water	6500	24.5	40	101.6	1.125	2.86	7.9	20.1	99.75	99.5					400	37.1	1000	6894.78	113	45.0
	TM820A-370	Sea water	5600	21.1	40	101.6	1.125	2.86	7.9	20.1	99.75	99.5					370	34.3	1200	8273.74	113	45.0
	TM820A-400	Sea water	6000	22.6	40	101.6	1.125	2.86	7.9	20.1	99.75	99.5					400	37.1	1200	8273.74	113	45.0
	TM820C-370	Sea water	6000	22.6	40	101.6	1.125	2.86	7.9	20.1	99.75	99.5					370	34.3	1200	8273.74	113	45.0
	TM820C-400	Sea water	6500	24.5	40	101.6	1.125	2.86	7.9	20.1	99.75	99.5					400	37.1	1200	8273.74	113	45.0
	TM820E-400	Sea water	7500	28.3	40	101.6	1.125	2.86	7.9	20.1	99.75	99.5					400	37.1	1200	8273.74	113	45.0
	TM820F-370	Sea water	8300	31.3	40	101.6	1.125	2.86	7.9	20.1	99.7	99.5					370	34.3	1000	6894.78	113	45.0
	TM820F-400	Sea water	9000	33.9	40	101.6	1.125	2.86	7.9	20.1	99.7	99.5					400	37.1	1000	6894.78	113	45.0
	TM820H-370	Sea water	5600	21.1	40	101.6	1.125	2.86	7.9	20.1	99.75	99.5					370	34.3	1200	8273.74	113	45.0
	TM820H-400	Sea water	6000	22.6	40	101.6	1.125	2.86	7.9	20.1	99.75	99.5					400	37.1	1200	8273.74	113	45.0
	TM820K-400	Sea water	5800	21.9	40	101.6	1.125	2.86	7.9	20.1	99.86	99.5					400	37.1	1200	8273.74	113	45.0
	TM820L-400	Sea water	12200	46.0	40	101.6	1.125	2.86	7.9	20.1	99.8	99.5					400	37.1	1200	8273.74	113	45.0
	TM820L-440	Sea water	13500	50.9	40	101.6	1.125	2.86	7.9	20.1	99.8	99.5					440	40.8	1200	8273.74	113	45.0
	TM820R-400	Sea water	8500	32.0	40	101.6	1.125	2.86	7.9	20.1	99.8	99.5					400	37.1	1200	8273.74	113	45.0
	TM820R-440	Sea water	9400	35.4	40	101.6	1.125	2.86	7.9	20.1	99.8	99.5					440	40.8	1200	8273.74	113	45.0
	TM820S-400	Sea water	9000	33.9	40	101.6	1.125	2.86	7.9	20.1	99.8	99.5					400	37.1	1200	8273.74	113	45.0
	TM820S-440	Sea water	9900	37.3	40	101.6	1.125	2.86	7.9	20.1	99.8	99.5					440	40.8	1200	8273.74	113	45.0
	TM820V-400	Sea water	9000	33.9	40	101.6	1.125	2.86	7.9	20.1	99.8	99.5					400	37.1	1200	8273.74	113	45.0

Part Number	Model Name / Description	Type	Flow		Length (A)		OUTPUT (B)		FEED O.D. (C)		Average NaCl rejection	Minimum NaCl rejection	Average MgSO4 rejection	Minimum MgSO4 rejection	Shipping Weight		Membrane Active Area		Max. Pressure		Max. Temperature	
			gpd	m³ / day	inch	cm	inch	cm	inch	cm	%	%	%	%	lbs	kg	ft²	m²	psi	KPa	°F	°C
	TM840V-1760	Sea water	39600	149.2	40	101.6	3.11	7.90	15.8	40.1	99.8	99.5					1760	163.2	1200	8273.74	113	45.0
	SUL-G20	Sea water	7900	29.8	40	101.6	1.125	2.86	7.9	20.1	99.5	99.0					380	35.2	600	4136.87	104	41.4
	SUL-G20F	Sea water	9800	36.9	40	101.6	1.125	2.86	7.9	20.1	99.8	99.5					420	39.0	600	4136.87	104	41.4
	SUL-G10	Sea water	1700	6.4	40	101.6	1.125	2.86	7.9	20.1	99.5	99.0					75	7.0	600	4136.87	104	41.4
	SU-720TS	Sanitary	6900	26.0	40	101.6	1.125	2.86	7.9	20.1	99.4	99.0							600	4136.87	185	73.7
	SUL-G20TS	Sanitary	7900	29.8	40	101.6	1.125	2.86	7.9	20.1	99.5	99.0							600	4136.87	185	73.7
	SUL-G20FTS	Sanitary	9500	35.8	40	101.6	1.125	2.86	7.9	20.1	99.4	99.0							600	4136.87	185	73.7
	SU-720P	Ultra Pure Water	8500	32.0	40	101.6	1.125	2.86	7.9	20.1									600	4136.87	113	45.0
	SUL-820P	Ultra Pure Water	8500	32.0	40	101.6	1.125	2.86	7.9	20.1									600	4136.87	113	45.0
	SUL-G20P	Ultra Pure Water	8500	32.0	40	101.6	1.125	2.86	7.9	20.1									600	4136.87	113	45.0
	SU-H20P	Ultra Pure Water																				
	SU-710P	Ultra Pure Water	2100	7.9	40	101.6	1.125	2.86	7.9	20.1									600	4136.87	104	41.4
	SUL-G10P	Ultra Pure Water																				
	SU-620	NanoFiltration																				
	SU-620F	NanoFiltration																				
	SU-610	NanoFiltration																				
	SC-2201	WW, Cellose, Brackish	9300	35.0	40	101.6	1.125	2.86	7.9	20.1	95.0	94.0							600	4136.87	104	41.4
	SC-4201	WW, Cellose, Brackish	7200	27.1	40	101.6	1.125	2.86	7.9	20.1	97.0	96.0							600	4136.87	104	41.4
	SC-6201X	WW, Cellose, Brackish	5400	20.3	40	101.6	1.125	2.86	7.9	20.1	95.0	92.5							600	4136.87	104	41.4
	SC-2101	WW, Cellose, Brackish	2300	8.7	40	101.6	1.125	2.86	7.9	20.1	95.0	92.5							600	4136.87	104	41.4
	SC-4101	WW, Cellose, Brackish	1800	6.8	40	101.6	1.125	2.86	7.9	20.1	97.0	96.0							600	4136.87	104	41.4
	SC-6101	WW, Cellose, Brackish	1400	5.3	40	101.6	1.125	2.86	7.9	20.1	98.0	97.0							600	4136.87	104	41.4