

PRODUCT DATA SHEET

AMBERJET™ I 300 Na

Industrial Grade Strong Acid Cation Exchanger

AMBERJET 1300 Na resin is a uniform particle size, gel type, cation exchange resin designed for use in all water treatment applications: softening as well as demineralization. Its sulfonated styrene divinylbenzene copolymer structure is formulated to provide high capacity coupled with exceptional physical and chemical stability. It has superior oxidation resistance compared to conventional resins. In the H^+ cycle, AMBERJET 1300 Na resin can be used in Stratabed™ (layered bed) columns together with AMBERLITE™ IRC86SB resin. In the sodium

cycle, the same resin couple provides a unique way of combining de-alkalization and softening with unsurpassed chemical efficiency. AMBERJET 1300 Na resin can also be combined with AMBERJET 4200 or AMBERJET 4400 anion exchangers in regenerable mixed bed units. The uniform particle size distribution of AMBERJET 1300 Na resin has been specifically selected to give optimum performance in AMBERPACK™ and other packed bed systems.

PROPERTIES

Service flow rate _____	5 to 50* BV/h		
Regeneration			
Regenerant _____	NaCl	HCl	H ₂ SO ₄
Level (g/L) _____	80 to 250	50 to 150	60 to 200
Concentration (%) _____	6-12	3 to 6	0.8 to 5
Minimum contact time _____	20 minutes		
Slow rinse _____	2 BV at regeneration flow rate		
Fast rinse _____	1 to 3 BV at service flow rate		

* 1 BV (Bed Volume) = 1 m³ solution per m³ resin

LIMITS OF USE

AMBERJET 1300 Na resin is suitable for industrial uses. For all other specific applications such as pharmaceutical, food processing or potable water applications, it is recommended that all potential users seek advice from Rohm and Haas in order to determine the best resin choice and optimum operating conditions.

HYDRAULIC CHARACTERISTICS

Figure 1 shows the bed expansion of AMBERJET 1300 Na resin as a function of backwash flow rate and water temperature. Figure 2 shows the pressure drop data for AMBERJET 1300 Na resin, as a function of service flow rate and water temperature. Pressure drop data are valid at the start of the service run with filtered water and a correctly classified bed.

Figure 1: Bed Expansion





Figure 2: Pressure Drop



ROHM and HAAS

AMBERJET is a trademark of Rohm and Haas Company and its affiliates, Philadelphia, U.S.A.

Ion exchange resins and polymeric adsorbents, as produced, contain by-products resulting from the manufacturing process. The user must determine the extent to which organic by-products must be removed for any particular use and establish techniques to assure that the appropriate level of purity is achieved for that use. The user must ensure compliance with all prudent safety standards and regulatory requirements governing the application. Except where specifically otherwise stated, Rohm and Haas Company does not recommend its ion exchange resins or polymeric adsorbents, as supplied, as being suitable or appropriately pure for any particular use. Consult your Rohm and Haas technical representative for further information. Acidic and basic regenerant solutions are corrosive and should be handled in a manner that will prevent eye and skin contact. Nitric acid and other strong oxidising agents can cause explosive type reactions when mixed with Ion Exchange resins. Proper design of process equipment to prevent rapid buildup of pressure is necessary if use of an oxidising agent such as nitric acid is contemplated. Before using strong oxidising agents in contact with Ion Exchange Resins, consult sources knowledgeable in the handling of these materials.

Rohm and Haas Company makes no warranties either expressed or implied as to the accuracy or appropriateness of these data and expressly excludes any liability upon Rohm and Haas arising out of its use. We recommend that the prospective users determine for themselves the suitability of Rohm and Haas materials and suggestions for any use prior to their adoption. Suggestions for uses of our products of the inclusion of descriptive material from patents and the citation of specific patents in this publication should not be understood as recommending the use of our products in violation of any patent or as permission or license to use any patents of the Rohm and Haas Company and its affiliates. Material Safety Data Sheets outlining the hazards and handling methods for our products are available on request.

LENNTECH WATER TREATMENT AND Air purification