

SP95- 2N Rp5 6"3X380-415/50 SD 9.2kW

Grundfos pump 19516902



Thank you for your interest in our products. Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/SPFAM/19516902/SP-95-2N.html>

info@lenntech.com

tel. +31 152 610 900

fax. +31 152 616 289

Position	Qty.	Description
	1	SP 95-2N Product No.: On request Submersible borehole pump, suitable for pumping clean water. Can be installed vertically or horizontally. All steel components are made in stainless steel, EN 1.4401 (AISI 316), that ensures high corrosive resistance. The pump is fitted with a 9.2 kW MS6000 motor with sand shield, mechanical shaft seal, water-lubricated journal bearings and a volume compensating diaphragm. The motor is a canned type submersible motor offering good mechanical stability and high efficiency. Suitable for temperatures up to 40 °C. The motor is fitted with the Grundfos Tempcon sensor that, by use of powerline communication together with a MP204 control panel, enables temperature monitoring. The motor is for star-delta starting (Y/D). Further product details The pump is suitable for applications similar to the following: - raw-water supply - irrigation - groundwater lowering - pressure boosting - fountain applications - mining applications - off-shore applications. Pump All pump surfaces that are in contact with pumped liquids are made in stainless steel which makes them corrosion- and wear-resistant. The corrosion diagram below shows the capabilities of the pump and motor in relation to the temperature in Celsius (y-axis) and the concentration of chloride in ppm (x-axis). The elastomer parts in the pump are made of NBR (Nitrile-Butadiene Rubber) which ensures good wear resistance and long service intervals. In case the pump is used for pumping water with high content of hydrocarbons or solvents, Grundfos offers FKM rubber parts (Fluorocarbon) which are oil and temperature-resistant up to 90 °C. The pump is built with octagonal bearings with sand flush channels that minimise wear. As wear of the pump is inevitable, the pump design allows for easy replacement of all internal wear parts (bearings, impeller, wear rings and seal rings) to maintain high performance and a long lifetime. The suction interconnector is fitted with a strainer to prevent large particles from entering the pump. The suction interconnector is designed to comply with NEMA standards for motor mounting/dimensions. Motor

The stator is hermetically encapsulated in stainless steel and the windings are embedded in polymer compound. This results in high mechanical stability, optimum cooling and reduces the risk of short circuits in the windings.

The shaft seal faces are SiC/SiC. The material combination gives good performance when abrasive particles (sand) is present. Together with the shaft seal housing, the sand shield forms a labyrinth seal which during normal operating conditions prevents penetration of sand particles into the shaft seal.

The motor is fitted with the Grundfos Tempcon temperature sensor device that includes a NTC-resistor which senses the temperature. The resistor is built-in close to the winding. The temperature is converted into a high-frequency signal which is sent via the submersible drop cable and which can be converted into a temperature reading by means of Grundfos MP204.

The MP204 is an electronic motor protection device that also monitors the supply network quality to protect the submersible motor against supply network disturbances.



Liquid:

Pumped liquid: Water
 Maximum liquid temperature: 40 °C
 Max liquid t at 0.15 m/sec: 40 °C
 Liquid temperature during operation: 20 °C
 Density: 998.2 kg/m³

Technical:

Rated flow: 95 m³/h
 Rated head: 24 m
 Shaft seal for motor: SIC/SICFKM
 Approvals on nameplate: CE,GOST2
 Curve tolerance: ISO9906:2012 3B
 Motor version: T40

Materials:

Pump: Stainless steel
 EN 1.4401
 AISI 316
 Impeller: Stainless steel
 EN 1.4401
 AISI 316
 Motor: Stainless steel
 DIN W.-Nr. 1.4539
 AISI 904 L

Installation:


Pump outlet: RP5
 Motor diameter: 6 inch

Electrical data:




Motor type: MS6000
 Rated power - P2: 9.2 kW
 Power (P2) required by pump: 9.2 kW
 Mains frequency: 50 Hz
 Rated voltage: 3 x 380-400-415 V
 Rated current: 21.8-21.2-21.2 A
 Starting current: 480-520-550 %
 Cos phi - power factor: 0.84-0.82-0.78
 Rated speed: 2850-2870-2880 rpm
 Start. method: star/delta
 Enclosure class (IEC 34-5): IP68

Position	Qty.	Description
		Insulation class (IEC 85): F Built-in temp. transmitter: yes Others: Minimum efficiency index, MEI ≥: --- ErP status: EuP Standalone/Prod. Net weight: 72.8 kg Gross weight: 97.1 kg Shipping volume: 0.179 m ³


On request SP 95-2N 50 Hz




Description	Value
General information:	
Product name:	SP 95-2N
Product No:	On request
EAN number:	On request
Technical:	
Rated flow:	95 m³/h
Rated head:	24 m
Stages:	2
Impeller reduc.:	NONE
Shaft seal for motor:	SIC/SICFKM
Approvals on nameplate:	CE,GOST2
Curve tolerance:	ISO9906:2012 3B
Model:	B
Valve:	YES
Motor version:	T40
Materials:	
Pump:	Stainless steel EN 1.4401 AISI 316
Impeller:	Stainless steel EN 1.4401 AISI 316
Motor:	Stainless steel DIN W.-Nr. 1.4539 AISI 904 L
Installation:	
Pump outlet:	RP5
Motor diameter:	6 inch
Liquid:	
Pumped liquid:	Water
Maximum liquid temperature:	40 °C
Max liquid t at 0.15 m/sec:	40 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	MS6000
Applic. motor:	GRUNDFOS
Rated power - P2:	9.2 kW
Power (P2) required by pump:	9.2 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-400-415 V
Rated current:	21.8-21.2-21.2 A
Starting current:	480-520-550 %
Cos phi - power factor:	0.84-0.82-0.78
Rated speed:	2850-2870-2880 rpm
Start. method:	star/delta
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	NONE
Thermal protec:	external
Built-in temp. transmitter:	yes
Motor No:	78695613
Others:	
Minimum efficiency index, MEI ≥:	---
ErP status:	EuP Standalone/Prod.
Net weight:	72.8 kg
Gross weight:	97.1 kg
Shipping volume:	0.179 m³



On request SP 95-2N 50 Hz



On request SP 95-2N 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Exploded view



Sectional drawing (TM058200 for TPE2,TPE3)



TM058200

Exploded view (TM057026 for MGE model H/I)



Parts list SP 95-2N, Product No. On request
Valid from 22.7.2011 (1129)

Pos	Description	Annotation	Données de classification	Référence	Quantité	Unité
-	Motor				1	pcs
	Stator cpl.				1	
2	Shaft w/rotor				1	
2	Shaft w/rotor				1	
2a	Stop ring				1	
3	Thrust ring support cpl.				1	
4	Radial bearing				1	
5	Bearing retainer cpl.				1	
6	Thrust bearing				1	
7	Clamping flange				1	
7.a	Clamping flange				1	
12	Diaphragm				1	
13	Bottom cover				1	
22	Hex head screw		Length (mm): 32 Thread: 1/2" UNF		4	
22a	Slot pan head screw				1	
25a	Slot cheese head screw				1	
27	Sand shield				1	
32	Shaft seal				1	
34	Shaft seal, rotating part				1	
41	Hex socket head cap screw				4	
42	Stop for bearing				2	
- 45	Shaft adjusting				1	
10	Thrust cover				1	
10a	Washer				1	
11	Adjusting screw				1	
41	Socket button head screw				1	
46	Hex socket head cap screw				1	
48	Cross recess Pan head screw				4	
49	Lock ring				1	
51	Compression spring				1	
1	Valve casing cpl.				1	pcs
- 2	Valve cup				1	pcs
	Valve cup				1	
	Shaft				1	
3	Valve seat				1	pcs
3a	Retainer for valve seat				1	pcs
3b	Retainer for valve seat				1	pcs
- 4	Chamber cpl.				1	pcs
	Chamber				1	
	Bearing retainer				1	
	Guide vane				9	
	Cone				1	
	Guide cup				1	
	Guide cup				1	
6b	Bearing				1	
8b	Stop ring				1	
10	Chamber, bottom				1	
7	Seal ring				1	pcs
8a	Washer				1	pcs
- 9	Chamber cpl.				1	pcs
7	Seal ring				1	
8	Bearing				1	
13	Impeller cpl.				1	pcs
13	Impeller cpl.				1	pcs
14	Suction interconnector				1	pcs
15	Strainer				1	pcs
- 17	Shaft,cableg,strap				1	pcs
- 16	Shaft cpl.		Length (mm): 428		1	

Pos	Description	Annotation	Données de classification	Référence	Quantité	Unité
-	Coupling cpl.				1	
	Washer					
	Coupling					
32	O-ring					
- 17	Strap cpl.		Length (mm): 537		4	
			Thread: M16			
	Threaded bush				1	
	Lug				1	
- 18	Cable guard cpl.				1	
	Holder for cable guard				2	
	Holder				1	
	Rail for cable guard				1	
- 18	Cable guard cpl.				1	pcs
	Holder for cable guard				2	
	Holder				1	
	Rail for cable guard				1	
18b	Screw		Length (mm): 6		4	pcs
			Thread: M5			
19	Nut				4	pcs
23	Rubber guard				2	pcs
28	Lock				1	pcs
39	Helical compression spring				1	pcs
- 70	Valve guide				1	pcs
	Pipe				1	
	Valve guide				1	
	Valve guide				1	
	Valve guide				1	
	Cone				1	
71	Washer				4	pcs
77a	Cross recess Pan head screw				4	pcs
78	Nameplate				2	pcs
78a	Rivet				2	pcs
107	O-ring		Diameter: 134.5		1	pcs
			Material type: NBR			
			Thickness: 3			
220	Motor cable		Length (M): 5M		2	pcs

Disclaimer: The information about the Grundfos pump in this document may be outdated.

Data may be subject to alterations without further notice.

Please contact us to verify the data above is still accurate/up-to-date.

All information is copyright Grundfos.



info@lenntech.com

<https://www.lenntech.com>

tel. +31 152 610 900

fax. +31 152 616 289