

SP5A-17NE 1.5kW 3x380-415V 50Hz

Grundfos Pump 5221917



Thank you for your interest in our products

Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/SPNE05/5221917/SP-5A-17NE.html>

info@lenntech.com


tel. +31-15-261.09.00

fax. +31-15-261.62.89





Position	Qty.	Description																																																		
	1	 Note! Product picture may differ from actual product Product No.: 5221917 Multi-stage submersible pump designed for pumping of chemically polluted groundwater. The pump is made entirely of Stainless steel DIN W.-Nr. DIN W.-Nr. 1.4401. The motor is a 3-phase motor with sand shield, mechanical shaft seal, liquid-lubricated bearings and pressure equalizing diaphragm. Pumpset delivered without motor cable. Motor cable to be ordered separately – EPR, Teflon or XLPE. Liquid: <table><tr><td>Pumped liquid:</td><td>Water</td></tr><tr><td>Max liquid t at 0.15 m/sec:</td><td>40 °C</td></tr><tr><td>Liquid temperature during operation:</td><td>20 °C</td></tr><tr><td>Density:</td><td>998.2 kg/m³</td></tr></table> Technical: <table><tr><td>Speed for pump data:</td><td>2900 rpm</td></tr><tr><td>Rated flow:</td><td>5 m³/h</td></tr><tr><td>Rated head:</td><td>70 m</td></tr><tr><td>Shaft seal for motor:</td><td>SIC/SIC</td></tr><tr><td>Curve tolerance:</td><td>ISO9906:2012 3B</td></tr></table> Materials: <table><tr><td>Pump:</td><td>Stainless steel DIN W.-Nr. 1.4401 AISI 316</td></tr><tr><td>Impeller:</td><td>Stainless steel DIN W.-Nr. 1.4401 AISI 316</td></tr><tr><td>Motor:</td><td>Stainless steel DIN W.-Nr. 1.4539 AISI 904 L</td></tr></table> Installation: <table><tr><td>Pump outlet:</td><td>Rp 1 1/2</td></tr><tr><td>Motor diameter:</td><td>4 inch</td></tr></table> Electrical data: <table><tr><td>Motor type:</td><td>MS4000</td></tr><tr><td>Rated power - P2:</td><td>1.5 kW</td></tr><tr><td>Mains frequency:</td><td>50 Hz</td></tr><tr><td>Rated voltage:</td><td>3 x 380-400-415 V</td></tr><tr><td>Rated current:</td><td>3.95-4,00-4,10 A</td></tr><tr><td>Cos phi - power factor:</td><td>0.84-0,78-0,74</td></tr><tr><td>Rated speed:</td><td>2840-2860-2870 rpm</td></tr><tr><td>Start. method:</td><td>direct-on-line</td></tr><tr><td>Enclosure class (IEC 34-5):</td><td>IP68</td></tr><tr><td>Insulation class (IEC 85):</td><td>F</td></tr><tr><td>Built-in temp. transmitter:</td><td>yes</td></tr></table>	Pumped liquid:	Water	Max liquid t at 0.15 m/sec:	40 °C	Liquid temperature during operation:	20 °C	Density:	998.2 kg/m³	Speed for pump data:	2900 rpm	Rated flow:	5 m³/h	Rated head:	70 m	Shaft seal for motor:	SIC/SIC	Curve tolerance:	ISO9906:2012 3B	Pump:	Stainless steel DIN W.-Nr. 1.4401 AISI 316	Impeller:	Stainless steel DIN W.-Nr. 1.4401 AISI 316	Motor:	Stainless steel DIN W.-Nr. 1.4539 AISI 904 L	Pump outlet:	Rp 1 1/2	Motor diameter:	4 inch	Motor type:	MS4000	Rated power - P2:	1.5 kW	Mains frequency:	50 Hz	Rated voltage:	3 x 380-400-415 V	Rated current:	3.95-4,00-4,10 A	Cos phi - power factor:	0.84-0,78-0,74	Rated speed:	2840-2860-2870 rpm	Start. method:	direct-on-line	Enclosure class (IEC 34-5):	IP68	Insulation class (IEC 85):	F	Built-in temp. transmitter:	yes
Pumped liquid:	Water																																																			
Max liquid t at 0.15 m/sec:	40 °C																																																			
Liquid temperature during operation:	20 °C																																																			
Density:	998.2 kg/m³																																																			
Speed for pump data:	2900 rpm																																																			
Rated flow:	5 m³/h																																																			
Rated head:	70 m																																																			
Shaft seal for motor:	SIC/SIC																																																			
Curve tolerance:	ISO9906:2012 3B																																																			
Pump:	Stainless steel DIN W.-Nr. 1.4401 AISI 316																																																			
Impeller:	Stainless steel DIN W.-Nr. 1.4401 AISI 316																																																			
Motor:	Stainless steel DIN W.-Nr. 1.4539 AISI 904 L																																																			
Pump outlet:	Rp 1 1/2																																																			
Motor diameter:	4 inch																																																			
Motor type:	MS4000																																																			
Rated power - P2:	1.5 kW																																																			
Mains frequency:	50 Hz																																																			
Rated voltage:	3 x 380-400-415 V																																																			
Rated current:	3.95-4,00-4,10 A																																																			
Cos phi - power factor:	0.84-0,78-0,74																																																			
Rated speed:	2840-2860-2870 rpm																																																			
Start. method:	direct-on-line																																																			
Enclosure class (IEC 34-5):	IP68																																																			
Insulation class (IEC 85):	F																																																			
Built-in temp. transmitter:	yes																																																			

Position	Qty.	Description
		Others: Minimum efficiency index, MEI ≥: 0.50 Net weight: 22.8 kg Danish VVS No.: 388316170


5221917 SP 5A-17NE 50 Hz




Description	Value
General information:	
Product name:	SP 5A-17NE
Product No:	5221917
EAN number:	5700390241636
Technical:	
Speed for pump data:	2900 rpm
Rated flow:	5 m³/h
Rated head:	70 m
Stages:	17
Shaft seal for motor:	SIC/SIC
Curve tolerance:	ISO9906:2012 3B
Pump No:	05220017
Model:	A
Valve:	no non-return valve
Materials:	
Pump:	Stainless steel
	DIN W.-Nr. 1.4401
	AISI 316
Impeller:	Stainless steel
	DIN W.-Nr. 1.4401
	AISI 316
Motor:	Stainless steel
	DIN W.-Nr. 1.4539
	AISI 904 L
Installation:	
Pump outlet:	Rp 1 1/2
Motor diameter:	4 inch
Liquid:	
Pumped liquid:	Water
Max liquid t at 0.15 m/sec:	40 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	MS4000
Rated power - P2:	1.5 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-400-415 V
Rated current:	3.95-4,00-4,10 A
Cos phi - power factor:	0.84-0,78-0,74
Rated speed:	2840-2860-2870 rpm
Start. method:	direct-on-line
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	NONE
Thermal protec:	external
Built-in temp. transmitter:	yes
Motor No:	79195406
Others:	
Minimum efficiency index, MEI ≥:	0.50
Net weight:	22.8 kg
Danish VVS No.:	388316170



5221917 SP 5A-17NE 50 Hz




5221917 SP 5A-17NE 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

5221917 SP 5A-17NE 50 Hz



Note! All units are in [mm] unless others are stated.

*Disclaimer: The information about the Grundfos pump in this document may be outdated.
Data may be subject to alterations without further notice.
Please contact us to verify the data above is still accurate/up-to-date.*

All information is copyright Grundfos.



info@lenntech.com

www.lenntech.com

tel. +31-15-261.09.00

fax. +31-15-261.62.89