

UPS20-62 N 150 1x220V 60Hz 9H

Grundfos pump 95906736



Thank you for your interest in our products. Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/UPSB1/95906736/UPS-20-62-N-150.html>

info@lenntech.com


tel. +31 152 610 900

fax. +31 152 616 289





Position	Qty.	Description
	1	UPS 20-62 N 150  Note! Product picture may differ from actual product Product No.: On request The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid. The pump is characterized by: * Ceramic shaft and radial bearings. * Carbon axial bearing. * Stainless steel rotor can and bearing plate. * Corrosion-resistant impeller, Composite, PES/PP. * Stainless steel pump housing. The motor is a 1-phase motor. No additional motor protection is required. Liquid: Pumped liquid: Water Liquid temperature range: 2 .. 110 °C Liquid temperature during operation: 60 °C Density: 983.2 kg/m³ Technical: TF class: 110 Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4301 Impeller: Composite, PES/PP Installation: Amb. max at 80 dgr C liquid: 40 °C Maximum operating pressure: 10 bar Pipe connection: G 1 1/4 Pressure rating: PN 10 (@): 150 mm Electrical data: Power input in speed 1: 90 W Power input in speed 2: 135 W Max. power input: 150 W Mains frequency: 60 Hz Rated voltage: 1 x 220 V Current in speed 1: 0.44 A Current in speed 2: 0.64 A Current in speed 3: 0.68 A Capacitor size - run: 3 µF Enclosure class (IEC 34-5): X2D Insulation class (IEC 85): F Others:

Position	Qty.	Description
		Net weight: 3 kg Gross weight: 3.8 kg Shipping volume: 0.008 m³


On request UPS 20-62 N 150 60 Hz



Description	Value
General information:	
Product name:	UPS 20-62 N 150
Product No:	On request
EAN number:	On request
Technical:	
Speed no:	3
Head max:	62 dm
TF class:	110
Materials:	
Pump housing:	Stainless steel
	DIN W.-Nr. 1.4301
Impeller:	Composite, PES/PP
Installation:	
Amb. max at 80 dgr C liquid:	40 °C
Maximum operating pressure:	10 bar
Pipe connection:	G 1 1/4
Pressure rating:	PN 10
(@)	150 mm
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	2 .. 110 °C
Liquid temperature during operation:	60 °C
Density:	983.2 kg/m ³
Electrical data:	
Power input in speed 1:	90 W
Power input in speed 2:	135 W
Max. power input:	150 W
Mains frequency:	60 Hz
Rated voltage:	1 x 220 V
Current in speed 1:	0.44 A
Current in speed 2:	0.64 A
Current in speed 3:	0.68 A
Capacitor size - run:	3 µF
Enclosure class (IEC 34-5):	X2D
Insulation class (IEC 85):	F
Motor protec:	CONTACT
Thermal protec:	internal
Controls:	
Pos term box:	9H
Others:	
Net weight:	3 kg
Gross weight:	3.8 kg
Shipping volume:	0.008 m ³



On request UPS 20-62 N 150 60 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Exploded view




Sectional drawing (TM058200 for TPE2,TPE3)



TM058200

Exploded view (TM057026 for MGE model H/I)



Disclaimer: The information about the Grundfos pump in this document may be outdated.

Data may be subject to alterations without further notice.

Please contact us to verify the data above is still accurate/up-to-date.

All information is copyright Grundfos.



info@lenntech.com

<https://www.lenntech.com>

tel. +31 152 610 900

fax. +31 152 616 289