

UNILIFT AP35B.50.08.1V 1x230V 10m SCH

Grundfos Pump 96004575



Thank you for your interest in our products

Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/AP35B/96004575/UNILIFT-AP35B-50-08-1-V.html>

info@lenntech.com


tel. +31-15-261.09.00

fax. +31-15-261.62.89






Position	Qty.	Description
	1	Unilift AP35B.50.08.1.V  Note! Product picture may differ from actual product Product No.: 96004575 Submersible effluent pump Vertical single-stage stainless steel submersible pump with integrated submersible 1-phase motor. The pump is fitted with ring stand and carrying handle and is supplied with a 10 m mains cable. The impeller is a VORTEX impeller for 35 mm free passage suitable for pumping surface water, groundwater, wastewater and similar. The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil. The motor is insulation class F with thermal overload protection and has long-life deep-groove greased-for-life ball bearings. The pump has R 2" discharge port and is ready for installation either free-standing or on an auto-coupling system. Liquid: Maximum liquid temperature: 40 °C Density: 998.2 kg/m³ Technical: Type of impeller: VORTEX Maximum particle size: 35 mm Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304 Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304 Installation: Pump outlet: R 2" Maximum installation depth: 7 m Auto-coupling: Y Electrical data:

Position	Qty.	Description
		Type of motor: PSC Power input - P1: 1.25 kW Mains frequency: 50 Hz Rated voltage: 1 x 230 V Rated current: 5.44 A Cos phi - power factor: 0,98 Rated speed: 2795 rpm Capacitor size - run: 16 µF/400 V Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 10 m Type of cable plug: SCHUKO Others: Net weight: 11.4 kg Gross weight: 12 kg Danish VVS No.: 391270132 Swedish RSK No.: 5885935



96004575 Unilift AP35B.50.08.1.V 50 Hz



Description	Value
General information:	
Product name:	Unilift AP35B.50.08.1.V
Product No:	96004575
EAN number:	5700391489075
Technical:	
Max flow:	5.83 l/s
Head max:	13 m
Type of impeller:	VORTEX
Maximum particle size:	35 mm
Materials:	
Pump housing:	Stainless steel
	DIN W.-Nr. 1.4301
	AISI 304
Impeller:	Stainless steel
	DIN W.-Nr. 1.4301
	AISI 304
Installation:	
Pump outlet:	R 2"
Maximum installation depth:	7 m
Inst dry/wet:	S
Installation:	horizontal or vertical
Auto-coupling:	Y
Liquid:	
Maximum liquid temperature:	40 °C
Density:	998.2 kg/m ³
Electrical data:	
Type of motor:	PSC
Power input - P1:	1.25 kW
P2:	0.71 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 230 V
Rated current:	5.44 A
Cos phi - power factor:	0,98
Rated speed:	2795 rpm
Capacitor size - run:	16 µF/400 V
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	CONTACT
Thermal protec:	internal
Length of cable:	10 m
Type of cable plug:	SCHUKO
Others:	
Net weight:	11.4 kg
Gross weight:	12 kg
Danish VVS No.:	391270132
Swedish RSK No.:	5885935




96004575 Unilift AP35B.50.08.1.V 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

96004575 Unilift AP35B.50.08.1.V 50 Hz



Note! All units are in [mm] unless others are stated.

*Disclaimer: The information about the Grundfos pump in this document may be outdated.
Data may be subject to alterations without further notice.
Please contact us to verify the data above is still accurate/up-to-date.*

All information is copyright Grundfos.



info@lenntech.com

www.lenntech.com

tel. +31-15-261.09.00

fax. +31-15-261.62.89