

MMS8000 400/50 460/60 45kW DOL PE2 SIC Grundfos pump 96476891



Thank you for your interest in our products. Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/MMS08/96476891/MMS-8000.html>




info@lenntech.com

tel. +31 152 610 900


fax. +31 152 616 289

Position	Qty.	Description
	1	MMS 8000  Note! Product picture may differ from actual product Product No.: On request The motor is a 3-phase motor of the wet wound rewindable type with sand shield, liquid-lubricated bearings and pressure equalizing diaphragm. Liquid: Max liquid t at 0.15 m/sec: 40 °C Max liquid t at 0.5 m/sec: 45 °C Technical: Shaft seal for motor: SIC/SIC Motor version: T45 Materials: Motor: Cast iron DIN W.-Nr. 0.6025 ASTM 35-40 Installation: Motor diameter: 8 inch Electrical data: Motor type: MMS8000 Rated power - P2: 45 kW Mains frequency: 50 Hz Rated voltage: 3 x 380-400-415 V Voltage tolerance: +6/-10 % Rated current: 95.5-96.5-96.0 A Starting current: 560-600-680 % Cos phi - power factor: 0.88-0.82-0.80 Rated speed: 2900-2910-2920 rpm Rated full-load torque: 148 Nm Locked-rotor torque: 180-200-220 % Breakdown torque: 280-320-340 % Moment of inertia: 0.0395 kg m² Start. method: direct-on-line Enclosure class (IEC 34-5): IP58 Built-in temp. transmitter: no Winding resistance: 0.252 ohm Windings: PE2/PA Others: Net weight: 177 kg Shipping volume: 0.156 m³



Description	Value
General information:	
Product name:	MMS 8000
Product No:	On request
EAN number:	On request
Technical:	
Shaft seal for motor:	SIC/SIC
Motor version:	T45
Materials:	
Motor:	Cast iron
	DIN W.-Nr. 0.6025
	ASTM 35-40
Installation:	
Motor diameter:	8 inch
Liquid:	
Max liquid t at 0.15 m/sec:	40 °C
Max liquid t at 0.5 m/sec:	45 °C
Electrical data:	
Motor type:	MMS8000
Rated power - P2:	45 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-400-415 V
Voltage tolerance:	+6/-10 %
Rated current:	95.5-96.5-96.0 A
Starting current:	560-600-680 %
Cos phi - power factor:	0.88-0.82-0.80
Rated speed:	2900-2910-2920 rpm
Rated full-load torque:	148 Nm
Locked-rotor torque:	180-200-220 %
Breakdown torque:	280-320-340 %
Moment of inertia:	0.0395 kg m ²
Axial load max:	5000 kg
Start. method:	direct-on-line
Enclosure class (IEC 34-5):	IP58
Motor protec:	NONE
Thermal protec:	external
Built-in temp. transmitter:	no
Winding resistance:	0.252 ohm
Windings:	PE2/PA
Others:	
Net weight:	177 kg
Shipping volume:	0.156 m ³



On request MMS 8000 50 Hz




On request MMS 8000 50 Hz




Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Exploded view




Sectional drawing (TM058200 for TPE2,TPE3)



TM058200

Exploded view (TM057026 for MGE model H/I)



Parts list MMS 8000, Product No. On request
Valid from 23.2.2004 (0409)

Pos	Description	Annotation	Données de classification	Référence	Quantité	Unité
	Stator				1	pcs
-	Bearing bracket, upper				1	pcs
204	Bearing ring				2	
205	Bearing housing, upper				1	
-	Bearing bracket, lower				1	pcs
204	Bearing ring				2	
236	Bearing housing, lower				1	
242	Upthrust spacer				1	
242a	Hex socket head cap screw				4	
202	Shaft w/rotor				1	pcs
202a	Key				1	pcs
203	Thrust bearing part stationary				1	pcs
206	Thrust bearing part, rotating				1	pcs
212	Diaphragm				1	pcs
213	End shield				1	pcs
214	Washer		Internal diameter: 17 Outer diameter: 27		4	pcs
214a	Nut		Thread: M16		4	pcs
215	Stud		Length (mm): 35 Thread: M16		4	pcs
215	Socket set screw				3	pcs
216	Washer		Designation: M10 Internal diameter: 22,5 Outer diameter: 46		1	pcs
216a	Washer		Internal diameter: 35 Outer diameter: 45 Thickness: 0.2		1	pcs
216a	Washer		Internal diameter: 35 Outer diameter: 45 Thickness: 0.3		1	pcs
216a	Diverting disc				2	pcs
216b	Hex socket countersunk screw		Designation: ALLEN SCREW Length (mm): 16 Thread: M10		1	pcs
220	Motor cable		Length (M): 8		3	pcs
222a	Air vent screw				1	pcs
222b	Washer				2	pcs
223a	Plug				1	pcs
224	O-ring		Diameter: 164.7 Thickness: 3.5		2	pcs
226	Mechanical seal		Material type: SIC/SIC		1	pcs
227	Seal ring				1	pcs
228	Lock washer				1	pcs
229	Sand slinger				1	pcs
230a	Hex head screw				1	pcs
230b	Lock washer		Internal diameter: 8,4 Outer diameter: 14 Thickness: 1,6		1	pcs
230c	Plate				1	pcs
234	Gasket				2	pcs
235	Intermediate housing				1	pcs
235a	Socket set screw		Length (mm): 10 Thread: M8		2	pcs
237	Stud		Length (mm): 35 Thread: M16		4	pcs
238	Washer		Internal diameter: 17 Outer diameter: 27		4	pcs
238a	Nut		Thread: M16		4	pcs
247	Hex socket head cap screw				1	pcs

Pos	Description	Annotation	Données de classification	Référence	Quantité	Unité
248	Hex socket head cap screw		Designation: ALLEN A4		2	pcs
			Length (mm): 20			
			Thread: M8			
250	Flange, cable gland				1	pcs
250a	Grommet				1	pcs
250b	Cable ring				2	pcs
250c	Ring				1	pcs

Disclaimer: The information about the Grundfos pump in this document may be outdated.

Data may be subject to alterations without further notice.

Please contact us to verify the data above is still accurate/up-to-date.

All information is copyright Grundfos.



info@lenntech.com

<https://www.lenntech.com>

tel. +31 152 610 900

fax. +31 152 616 289