CRN15-17 A-FGJ-G-E-HQQE 3x400/690 50 HZ

Grundfos pump 96501970

Thank you for your interest in our products. Please contact us for more information, or visit our website

https://www.lenntech.com/grundfos/CRN15/96501970/CRN-15-17-A-FGJ-G-E-HQQE.html

info@lenntech.com
tel. +31 152 610 900
fax. +31 152 616 289

Position	Qty.	Description
	1	**CRN 15-17 A-FGJ-A-E-HQQE**

Product No.: On request

Vertical, multistage centrifugal pump with inlet and outlet ports on same the level (inline). Pump materials in contact with the liquid are in high-grade stainless steel. A cartridge shaft seal ensures high reliability, safe handling, and easy access and service. Power transmission is via a rigid split coupling. Pipe connection is via combined DIN-ANSI-JIS flanges.

The pump is fitted with a 3-phase, fan-cooled asynchronous motor.

Further product details

Steel, cast iron and aluminium components have an epoxy-based coating made in a cathodic electro-deposition (CED) process. CED is a high-quality dip-painting process where an electrical field around the products ensures deposition of paint particles as a thin, well-controlled layer on the surface. An integral part of the process is a pretreatment. The entire process consists of these elements:

1) Alkaline-based cleaning.
2) Zinc phosphating.
3) Cathodic electro-deposition.
4) Curing to a dry film thickness 18-22 my m.

The colour code for the finished product is NCS 9000/RAL 9005.

Pump

A long split coupling connects the pump and motor shaft. It is enclosed in the motor stool by means of two coupling guards. The long coupling makes it possible to replace the shaft seal without removing the motor from the pump.



The pump head and flange for motor mounting is made in one piece (cast iron). The pump head cover is a separate component (stainless steel). The pump head has a combined 1/2" priming plug and vent screw.



The pump is fitted with a balanced O-ring seal unit with a rigid torque-transmission system. This seal type is assembled in a cartridge unit which makes replacement safe and easy. Due to the balancing, this seal type is suitable for high-pressure applications. The cartridge construction also protects the pump shaft from possible wear from a dynamic O-ring between pump shaft and shaft seal.

Primary seal:

- Rotating seal ring material: silicon carbide (SiC)
- Stationary seat material: silicon carbide (SiC)

This material pairing is used where higher corrosion resistance is required. The high hardness of this material pairing offers good resistance against abrasive particles.

Secondary seal material: EPDM (ethylene-propylene rubber)
EPDM has excellent resistance to hot water. EPDM is not suitable for mineral oils.



The shaft seal is screwed into the pump head.

The chambers and impellers are made of stainless-steel sheet. The chambers are provided with a PTFE neck ring offering improved sealing and high efficiency. The impellers have smooth surfaces, and the shape of the blades ensure a high efficiency.

The pump has a stainless steel base mounted on a separate base plate. This base and base plate are kept in position by the tension of the staybolts which hold the pump together. The outlet side of the base has a combined drain plug and bypass valve. The pump is secured to the foundation by four bolts through the base plate. The flanges and base are cast in one piece and prepared for connection by means of DIN, ANSI or JIS.

Motor

The motor is a totally enclosed, fan-cooled motor with principal dimensions to IEC and DIN standards. The motor is flange-mounted with free-hole flange (FF).

Motor-mounting designation in accordance with IEC 60034-7: IM B 5 (Code I) / IM 3001 (Code II).

Electrical tolerances comply with IEC 60034.

The motor efficiency is classified as IE3 in accordance with IEC 60034-30-1.

The motor has thermistors (PTC sensors) in the windings in accordance with DIN 44081/DIN 44082. The protection reacts to both slow- and quick-rising temperatures, e.g. constant overload and stalled conditions.

Thermal switches must be connected to an external control circuit in a way which ensures that the automatic reset cannot cause accidents. The motors must be connected to a motor-protective circuit breaker according to local regulations.

The motor can be connected to a variable speed drive for adjustment of pump performance to any duty point. Grundfos CUE offers a range of variable speed drives. Please find more information in Grundfos Product Center.

Technical data

Controls:

Frequency converter:	NONE

Liquid:

Pumped liquid:	Water
Liquid temperature range:	-20 .. 120 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m³

Technical:

Rated flow:	17 m³/h
Rated head:	191.9 m
Pump orientation:	Vertical
Shaft seal arrangement:	Single
Code for shaft seal:	HQQE
Approvals on nameplate:	CE, EAC,ACS
Curve tolerance:	ISO9906:2012 3B

Materials:

Base:	Stainless steel EN 1.4408 AISI 316

Position	Qty.	Description	
		Impeller:	Stainless steel EN 1.4401 AISI 316
		Bearing:	SIC
		Installation:	
		Maximum ambient temperature:	60 °C
		Maximum operating pressure:	25 bar
		Max pressure at stated temp:	25 bar / 120 °C 25 bar / -20 °C
		Type of connection:	DIN / ANSI / JIS
		Size of inlet connection:	DN 50 2 inch
		Size of outlet connection:	DN 50 2 inch
		Pressure rating for pipe connection:	PN 25
		Flange rating inlet:	300 lb
		Flange size for motor:	FF300
		Electrical data:	
		Motor standard:	IEC
		Motor type:	160MD
		IE Efficiency class:	IE3
		Rated power - P2:	15 kW
		Power (P2) required by pump:	15 kW
		Mains frequency:	50 Hz
		Rated voltage:	3 x 380-415D/660-690Y V
		Rated current:	28,0-26,0/16,2-15,6 A
		Starting current:	660-780 %
		Cos phi - power factor:	0.89-0.87
		Rated speed:	2930-2950 rpm
		Efficiency:	IE3 91,9%
		Motor efficiency at full load:	91.9-91.9 %
		Motor efficiency at 3/4 load:	92.4 %
		Motor efficiency at 1/2 load:	92.4 %
		Number of poles:	2
		Enclosure class (IEC 34-5):	55 Dust/Jetting
		Insulation class (IEC 85):	F
		Others:	
		Minimum efficiency index, MEI ≥:	0.70
		Net weight:	170 kg
		Gross weight:	201 kg
		Shipping volume:	0.619 m^3

On request CRN 15-17 A-FGJ-A-E-HQQE 50 Hz





Description	Value
General information:	
Product name:	CRN 15-17 A-FGJ-A-E-HQQE
Product No:	On request
EAN number:	On request
Technical:	
Rated flow:	17 m³/h
Rated head:	191.9 m
Stages:	17
Impellers:	17
Number of reduced-diameter impellers:	0
Low NPSH:	N
Pump orientation:	Vertical
Shaft seal arrangement:	Single
Code for shaft seal:	HQQE
Approvals on nameplate:	CE, EAC,ACS
Curve tolerance:	ISO9906:2012 3B
Pump version:	A
Model:	A
Materials:	
Base:	Stainless steel
	EN 1.4408
	AISI 316
Impeller:	Stainless steel
	EN 1.4401
	AISI 316
Material code:	A
Code for rubber:	E
Bearing:	SIC
Installation:	
Maximum ambient temperature:	60 °C
Maximum operating pressure:	25 bar
Max pressure at stated temp:	25 bar / 120 °C
	25 bar / -20 °C
Type of connection:	DIN / ANSI / JIS
Size of inlet connection:	DN 50
	2 inch
Size of outlet connection:	DN 50
	2 inch
Pressure rating for pipe connection:	PN 25
Flange rating inlet:	300 lb
Flange size for motor:	FF300
Connect code:	FGJ
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-20 .. 120 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor standard:	IEC
Motor type:	160MD
IE Efficiency class:	IE3
Rated power - P2:	15 kW
Power (P2) required by pump:	15 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-415D/660-690Y V
Rated current:	28,0-26,0/16,2-15,6 A
Starting current:	660-780 %
Cos phi - power factor:	0.89-0.87
Rated speed:	2930-2950 rpm
Efficiency:	IE3 91,9%
Motor efficiency at full load:	91.9-91.9 %
Motor efficiency at 3/4 load:	92.4 %







Description	Value
Motor efficiency at 1/2 load:	92.4 %
Number of poles:	2
Enclosure class (IEC 34-5):	55 Dust/Jetting
Insulation class (IEC 85):	F
Motor protec:	PTC
Motor No:	85U17526
Controls:	
Frequency converter:	NONE
Others:	
Minimum efficiency index, MEI ≥:	0.70
Net weight:	170 kg
Gross weight:	201 kg
Shipping volume:	0.619 m³

On request CRN 15-17 A-FGJ-A-E-HQQE 50 Hz



On request CRN 15-17 A-FGJ-A-E-HQQE 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Exploded view



Sectional drawing (TM058200 for TPE2,TPE3)



TM058200

Exploded view (TM057026 for MGE model H/I)



Parts list CRN 15-17, Product No. On request
Valid from 1.1.2011 (1152)

	Pos	Description	Annotation	Données de classification	Référence	Quantité	Unité
+		Motor				1	pcs
-		Base cpl.				1	pcs
	6	Base				1	
	25	Drain plug				1	
	56	Base plate				1	
	201	Flange				2	
	203	Lock ring				2	
-		Rubber module				1	pcs
	20	Spring				4	
	37	O-ring				2	
	38	O-ring		Diameter: 16,3		1	
				Material type: EPDM			
				Thickness: 2,4			
	38a	O-ring		Diameter: 5,3		1	
				Material type: EPDM			
				Thickness: 2,4			
	100	O-ring		Diameter: 16,3		2	
				Material type: EPDM			
				Thickness: 2,4			
-	2	Pump head cpl.				1	pcs
	1	Flange				1	
	2	Pump head				1	
	7	Coupling guard				2	
-	18	Air vent screw				1	
		Plug				1	
		Spindle				1	
	23	Plug				1	
	28	Hex head screw		Length (mm): 25		4	
				Thread: M12			
	28a	Hex head screw		Length (mm): 45		4	
				Thread: M16			
	36	Hex nut		Thread: M16		4	
	37.a	O-ring				1	
	76	Nameplate				1	
	76a	Rivet				1	
	77	Pump cover				1	
-	8	Coupling				1	pcs
	9	Hex socket head cap screw		Designation: DIN 912		4	
				Length (mm): 25			
				Thread: M10			
	10	Shaft pin		Diameter: 5		1	
				Length (mm): 26			
	10a	Coupling half				2	
	26	Staybolt		Length (mm): 945		4	pcs
	36	Nut		Thread: M16		4	pcs
	55	Outer sleeve				1	pcs
	66a	Washer		Designation: DIN 125 A2		4	pcs
				Internal diameter: 17			
				Outer diameter: 30			
				Thickness: 3			
-	80	Chamber stack				1	pcs
-	3	Top intermediate chamber				1	
		Cover plate				1	
		Guide vane				10	
	3	Intermediate chamber				1	
-	4	Intermediate chamber cpl.				13	
		Intermediate chamber				1	
	45	Neck ring cpl.				1	
	65	Retainer				1	

	Pos	Description	Annotation	Données de classification	Référence	Quantité	Unité
-	4a	Intermediate chamber cpl.				3	
		Guide vane				10	
		Bearing plate				1	
		Bearing bush				1	
		Intermediate chamber				1	
		Guide cup				1	
		Sand Lifter				1	
	45	Neck ring cpl.				1	
	65	Retainer				1	
	26.b	Hex head screw				2	
	26.c	Washer		Designation: DIN 125A		2	
				Thickness: 1,6			
	26a	Strap cpl.				2	
	36	Lock nut		Thread: M8		1	
-	44a	Inlet part cpl.				1	
	45	Neck ring cpl.				1	
	65	Retainer				1	
	44b	Inlet part				1	
	47a	Bearing ring				3	
-	49	Impeller cpl.				17	
		Impeller				1	
	49c	Wear ring				1	
-	51	Shaft, spline, cpl.				1	
		Bar				1	
	62	Stop ring				1	
	64b	Spacing bush				3	
	64c	Spacing pipe		Length (mm): 12.7		1	
	66	Wedge lock washer				1	
	69	Spacing pipe		Length (mm): 43.6		13	
	69	Spacing pipe		Internal diameter: 17,5		3	
				Length (mm): 17			
	69	Spacing bush				1	
	105	Shaft seal		Material type: HQQE		1	pcs

Disclaimer: The information about the Grundfos pump in this document may be outdated.
Data may be subject to alterations without further notice.
Please contact us to verify the data above is still accurate/up-to-date.

All information is copyright Grundfos.

info@lenntech.com
https://www.lenntech.com
tel. +31 152 610 900
fax. +31 152 616 289