

SQ 2- 55 0.70kW 200-240V 50/60Hz 10m

Grundfos Pump 96524430



Thank you for your interest in our products

Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/SQC02/96524430/SQ-2-55.html>

info@lenntech.com


tel. +31-15-261.09.00

fax. +31-15-261.62.89





Position	Qty.	Description																																														
	1	 Note! Product picture may differ from actual product Product No.: 96524430 3" multi-stage, submersible pump designed for domestic water supply, liquid transfer in tanks, irrigation and environmental applications. The pump has "floating" impellers, each with its own tungsten carbide/ceramic bearing. The pump features soft starting and protection against dry-running, upthrust, overvoltage, undervoltage, overload and overtemperature. The motor is a single-phase motor of the permanent magnet rotor type ensuring optimum efficiency within a wide load range. The motor is fitted with a replaceable end cover with socket. Liquid: <table><tr><td>Pumped liquid:</td><td>Water</td></tr><tr><td>Maximum liquid temperature:</td><td>35 °C</td></tr><tr><td>Max liquid t at 0.15 m/sec:</td><td>35 °C</td></tr><tr><td>Liquid temperature during operation:</td><td>20 °C</td></tr><tr><td>Density:</td><td>998.2 kg/m³</td></tr></table> Technical: <table><tr><td>Speed for pump data:</td><td>10700 rpm</td></tr><tr><td>Rated flow:</td><td>2 m³/h</td></tr><tr><td>Rated head:</td><td>54 m</td></tr><tr><td>Approvals on motor nameplate:</td><td>CE,UL,CUL</td></tr><tr><td>Curve tolerance:</td><td>ISO9906:2012 3B</td></tr></table> Materials: <table><tr><td>Pump:</td><td>Polyamide / Stainless steel DIN W.-Nr. 1.4301 AISI 304</td></tr><tr><td>Impeller:</td><td>Polyamide</td></tr><tr><td>Motor:</td><td>Stainless steel DIN W.-Nr. 1.4301 AISI 304</td></tr></table> Installation: <table><tr><td>Pump outlet:</td><td>Rp 1 1/4</td></tr><tr><td>Minimum borehole diameter:</td><td>76 mm</td></tr></table> Electrical data: <table><tr><td>Motor type:</td><td>MS3</td></tr><tr><td>Power input - P1:</td><td>1.02 kW</td></tr><tr><td>Rated power - P2:</td><td>0.7 kW</td></tr><tr><td>Mains frequency:</td><td>50 Hz</td></tr><tr><td>Rated voltage:</td><td>1 x 200-240 V</td></tr><tr><td>Rated current:</td><td>5.2 A</td></tr><tr><td>Power factor:</td><td>1,00</td></tr><tr><td>Rated speed:</td><td>10700 rpm</td></tr></table>	Pumped liquid:	Water	Maximum liquid temperature:	35 °C	Max liquid t at 0.15 m/sec:	35 °C	Liquid temperature during operation:	20 °C	Density:	998.2 kg/m³	Speed for pump data:	10700 rpm	Rated flow:	2 m³/h	Rated head:	54 m	Approvals on motor nameplate:	CE,UL,CUL	Curve tolerance:	ISO9906:2012 3B	Pump:	Polyamide / Stainless steel DIN W.-Nr. 1.4301 AISI 304	Impeller:	Polyamide	Motor:	Stainless steel DIN W.-Nr. 1.4301 AISI 304	Pump outlet:	Rp 1 1/4	Minimum borehole diameter:	76 mm	Motor type:	MS3	Power input - P1:	1.02 kW	Rated power - P2:	0.7 kW	Mains frequency:	50 Hz	Rated voltage:	1 x 200-240 V	Rated current:	5.2 A	Power factor:	1,00	Rated speed:	10700 rpm
Pumped liquid:	Water																																															
Maximum liquid temperature:	35 °C																																															
Max liquid t at 0.15 m/sec:	35 °C																																															
Liquid temperature during operation:	20 °C																																															
Density:	998.2 kg/m³																																															
Speed for pump data:	10700 rpm																																															
Rated flow:	2 m³/h																																															
Rated head:	54 m																																															
Approvals on motor nameplate:	CE,UL,CUL																																															
Curve tolerance:	ISO9906:2012 3B																																															
Pump:	Polyamide / Stainless steel DIN W.-Nr. 1.4301 AISI 304																																															
Impeller:	Polyamide																																															
Motor:	Stainless steel DIN W.-Nr. 1.4301 AISI 304																																															
Pump outlet:	Rp 1 1/4																																															
Minimum borehole diameter:	76 mm																																															
Motor type:	MS3																																															
Power input - P1:	1.02 kW																																															
Rated power - P2:	0.7 kW																																															
Mains frequency:	50 Hz																																															
Rated voltage:	1 x 200-240 V																																															
Rated current:	5.2 A																																															
Power factor:	1,00																																															
Rated speed:	10700 rpm																																															

Position	Qty.	Description
		Start. method: direct-on-line Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 10 m Others: Net weight: 5.9 kg Gross weight: 7.3 kg Finnish: LVI NO 4762602


96524430 SQ 2-55 50 Hz



Description	Value
General information:	
Product name:	SQ 2-55
Product No:	96524430
EAN number:	5700396929903
Technical:	
Speed for pump data:	10700 rpm
Rated flow:	2 m³/h
Rated head:	54 m
Stages:	3
Approvals on motor nameplate:	CE,UL,CUL
Curve tolerance:	ISO9906:2012 3B
Pump No:	96080385
Model:	B
Valve:	pump with built-in non-return valve
Materials:	
Pump:	Polyamide / Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller:	Polyamide
Motor:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Installation:	
Pump outlet:	Rp 1 1/4
Minimum borehole diameter:	76 mm
Liquid:	
Pumped liquid:	Water
Maximum liquid temperature:	35 °C
Max liquid t at 0.15 m/sec:	35 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	MS3
Power input - P1:	1.02 kW
Rated power - P2:	0.7 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 200-240 V
Rated current:	5.2 A
Power factor:	1,00
Rated speed:	10700 rpm
Start. method:	direct-on-line
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	Y
Thermal protec:	internal
Length of cable:	10 m
Motor No:	96160570
Controls:	
CU 300/CU 301:	no communication possible
Others:	
Net weight:	5.9 kg
Gross weight:	7.3 kg
Sales region:	EU/S-AMREG/APREG
Finnish:	LVI NO 4762602




96524430 SQ 2-55 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

96524430 SQ 2-55 50 Hz



Note! All units are in [mm] unless others are stated.

*Disclaimer: The information about the Grundfos pump in this document may be outdated.
Data may be subject to alterations without further notice.
Please contact us to verify the data above is still accurate/up-to-date.*

All information is copyright Grundfos.



info@lenntech.com

www.lenntech.com

tel. +31-15-261.09.00

fax. +31-15-261.62.89