

NBE50-160/167 A-F2-A-GQQE

Grundfos Pump 96539137



Thank you for your interest in our products

Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/NBE00/96539137/NBE-50-160-167-A-F-A-GQQE.html>

info@lenntech.com


tel. +31-15-261.09.00

fax. +31-15-261.62.89




Position	Qty.	Description
	1	NBE 50-160/167 A-F-A-GQQE  Note! Product picture may differ from actual product Product No.: 96539137 Non-self priming, single-stage centrifugal pump according to DIN. The pump is for the pumping of thin, clean or slightly contaminated liquids without abrasive or long-fibred solids. The impeller is hydraulically as well as dynamically balanced. The pump has the following characteristics: - flange dimensions according to EN 1092-2, - Cast iron volute pump housing, - stainless steel shaft and Cast iron impeller and bronze wear rings, - unbalanced mechanical shaft seal according to EN 12756. The pump is fitted with an IEC-flanged three-phase MGE motor with frequency converter and PI-controller integrated in the motor terminal box. No additional motor protection is required, as both motor and electronics are protected by integrated overload and temperature protection. An external sensor can be connected if controlled pump operation based on for example flow, differential pressure or temperature is required. A control panel enables setting of required setpoint as well as setting of pump to MIN or MAX operation or to STOP. The control panel has indicator lights for "Operation" and "Fault". Communication with the pump is possible by means of Grundfos R100 Remote Control enabling further settings as well as reading out of a number of parameters such as "Actual value", "Speed", "Power input" and total "Power consumption". The terminal box holds terminals for the connection of: - pump start/stop (potential-free contact), - external remote setpoint setting via analog signal, 0 - 5 V, 0 - 10 V, 0(4) - 20 mA, - 5 V voltage supply for setpoint potentiometer, I_{max} = 5 mA, - sensor, 0 - 5 V, 0 - 10 V, 0(4) - 20 mA, - 24 V voltage supply for sensor, I_{max} = 40 mA,

Position	Qty.	Description
		- input for forced control to MIN or MAX (potential-free contact), - potential-free fault signal relay with changeover contact, - RS485 GENIbus. Liquid: Pumped liquid: Water Liquid temperature range: -25 .. 90 °C Liquid temperature during operation: 20 °C Density: 998.2 kg/m³ Technical: Speed for pump data: 2900 rpm Rated flow: 87.4 m³/h Rated head: 32.1 m Actual impeller diameter: 167 mm Impeller nom: 160 mm Primary shaft seal: GQQE Materials: Pump housing: Cast iron EN-JL1040 Impeller: Cast iron EN-JL1030 ASTM A48-30 B Installation: Maximum ambient temperature: 40 °C Maximum operating pressure: 16 bar Flange standard: DIN Pump inlet: DN 65 Pump outlet: DN 50 Pressure rating: PN 16 Electrical data: Motor type: 160M Rated power - P2: 11 kW Mains frequency: 50 Hz Rated voltage: 3 x 380-415 V Rated current: 21.4 A Cos phi - power factor: 0,93 Rated speed: 360-2900 rpm Number of poles: 2 Enclosure class (IEC 34-5): IP54 Insulation class (IEC 85): F Others: Net weight: 167 kg Gross weight: 175 kg Shipping volume: 0.518 m³

96539137 NBE 50-160/167 50 Hz





Description	Value
General information:	
Product name:	NBE 50-160/167 A-F-A-GQQE
Product No:	96539137
EAN number:	5700397660836
Technical:	
Speed for pump data:	2900 rpm
Rated flow:	87.4 m³/h
Rated head:	32.1 m
Actual impeller diameter:	167 mm
Impeller nom:	160 mm
Primary shaft seal:	GQQE
Pump version:	A
Materials:	
Pump housing:	Cast iron
	EN-JL1040
Impeller:	Cast iron
	EN-JL1030
	ASTM A48-30 B
Material code:	A
Installation:	
Maximum ambient temperature:	40 °C
Maximum operating pressure:	16 bar
Flange standard:	DIN
Connect code:	F
Pump inlet:	DN 65
Pump outlet:	DN 50
Pressure rating:	PN 16
Wear ring(s):	neckring(s)
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-25 .. 90 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	160M
Rated power - P2:	11 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-415 V
Rated current:	21.4 A
Cos phi - power factor:	0,93
Rated speed:	360-2900 rpm
Number of poles:	2
Enclosure class (IEC 34-5):	IP54
Insulation class (IEC 85):	F
Motor protec:	PTC
Motor No:	96078155
Mount. design. acc. IEC 34-7:	IM B35
Others:	
Net weight:	167 kg
Gross weight:	175 kg
Shipping volume:	0.518 m³
Config. file no:	96078387




96539137 NBE 50-160/167 50 Hz

cos phi
eta

NBE50-160/167 + 160M 11 kW 3*400 V, 50 Hz




96539137 NBE 50-160/167 50 Hz




Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

96539137 NBE 50-160/167 50 Hz

Mains connection



Other connections



Note! All units are in [mm] unless others are stated.

*Disclaimer: The information about the Grundfos pump in this document may be outdated.
Data may be subject to alterations without further notice.
Please contact us to verify the data above is still accurate/up-to-date.*

All information is copyright Grundfos.



info@lenntech.com

www.lenntech.com

tel. +31-15-261.09.00

fax. +31-15-261.62.89