

NBE125-250/236 A-F2-A-GQQE

Grundfos Pump 96539217



Thank you for your interest in our products

Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/NBE00/96539217/NBE-125-250-236-A-F-A-GQQE.html>

info@lenntech.com


tel. +31-15-261.09.00

fax. +31-15-261.62.89

Position	Qty.	Description
	1	NBE 125-250/236 A-F-A-GQQE  Note! Product picture may differ from actual product Product No.: 96539217 Non-self priming, single-stage centrifugal pump according to DIN. The pump is for the pumping of thin, clean or slightly contaminated liquids without abrasive or long-fibred solids. The impeller is hydraulically as well as dynamically balanced. The pump has the following characteristics: - flange dimensions according to EN 1092-2, - Cast iron volute pump housing, - stainless steel shaft and Cast iron impeller and bronze wear rings, - unbalanced mechanical shaft seal according to EN 12756. The pump is fitted with an IEC-flanged three-phase MGE motor with frequency converter and PI-controller integrated in the motor terminal box. No additional motor protection is required, as both motor and electronics are protected by integrated overload and temperature protection. An external sensor can be connected if controlled pump operation based on for example flow, differential pressure or temperature is required. A control panel enables setting of required setpoint as well as setting of pump to MIN or MAX operation or to STOP. The control panel has indicator lights for "Operation" and "Fault". Communication with the pump is possible by means of Grundfos R100 Remote Control enabling further settings as well as reading out of a number of parameters such as "Actual value", "Speed", "Power input" and total "Power consumption". The terminal box holds terminals for the connection of: - pump start/stop (potential-free contact), - external remote setpoint setting via analog signal, 0 - 5 V, 0 - 10 V, 0(4) - 20 mA, - 5 V voltage supply for setpoint potentiometer, I_{max} = 5 mA, - sensor, 0 - 5 V, 0 - 10 V, 0(4) - 20 mA, - 24 V voltage supply for sensor, I_{max} = 40 mA,


Position	Qty.	Description
		- input for forced control to MIN or MAX (potential-free contact), - potential-free fault signal relay with changeover contact, - RS485 GENIbus. Liquid: Pumped liquid: Water Liquid temperature range: -25 .. 90 °C Liquid temperature during operation: 20 °C Density: 998.2 kg/m³ Technical: Speed for pump data: 1450 rpm Rated flow: 252 m³/h Rated head: 15 m Actual impeller diameter: 236 mm Impeller nom: 250 mm Primary shaft seal: GQQE Materials: Pump housing: Cast iron EN-JL1040 Impeller: Cast iron EN-JL1030 ASTM A48-30 B Installation: Maximum ambient temperature: 40 °C Maximum operating pressure: 16 bar Flange standard: DIN Pump inlet: DN 150 Pump outlet: DN 125 Pressure rating: PN 16 Electrical data: Motor type: 160L Rated power - P2: 15 kW Mains frequency: 50 Hz Rated voltage: 3 x 380-415 V Rated current: 28.5 A Cos phi - power factor: 0,94 Rated speed: 180-1450 rpm Number of poles: 4 Enclosure class (IEC 34-5): IP54 Insulation class (IEC 85): F Others: Net weight: 274 kg Gross weight: 295 kg Shipping volume: 0.96 m³

96539217 NBE 125-250/236 50 Hz




Description	Value
General information:	
Product name:	NBE 125-250/236 A-F-A-GQQE
Product No:	96539217
EAN number:	5700397662045
Technical:	
Speed for pump data:	1450 rpm
Rated flow:	252 m³/h
Rated head:	15 m
Actual impeller diameter:	236 mm
Impeller nom:	250 mm
Primary shaft seal:	GQQE
Pump version:	A
Materials:	
Pump housing:	Cast iron EN-JL1040
Impeller:	Cast iron EN-JL1030
	ASTM A48-30 B
Material code:	A
Installation:	
Maximum ambient temperature:	40 °C
Maximum operating pressure:	16 bar
Flange standard:	DIN
Connect code:	F
Pump inlet:	DN 150
Pump outlet:	DN 125
Pressure rating:	PN 16
Wear ring(s):	neckring(s)
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-25 .. 90 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	160L
Rated power - P2:	15 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-415 V
Rated current:	28.5 A
Cos phi - power factor:	0,94
Rated speed:	180-1450 rpm
Number of poles:	4
Enclosure class (IEC 34-5):	IP54
Insulation class (IEC 85):	F
Motor protec:	PTC
Motor No:	96078179
Mount. design. acc. IEC 34-7:	IM B35
Others:	
Net weight:	274 kg
Gross weight:	295 kg
Shipping volume:	0.96 m³
Config. file no:	96078405

96539217 NBE 125-250/236 50 Hz




96539217 NBE 125-250/236 50 Hz




Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

96539217 NBE 125-250/236 50 Hz

Mains connection



Other connections



Note! All units are in [mm] unless others are stated.

*Disclaimer: The information about the Grundfos pump in this document may be outdated.
Data may be subject to alterations without further notice.
Please contact us to verify the data above is still accurate/up-to-date.*

All information is copyright Grundfos.



info@lenntech.com

www.lenntech.com

tel. +31-15-261.09.00

fax. +31-15-261.62.89