

NK40-125/130A2F2AE-SBAQE

Grundfos pump 96594544




Thank you for your interest in our products. Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/NKBASIS/96594544/NK-40-125-130-A2-F-A-E-BAQE.html>

info@lenntech.com

tel. +31 152 610 900

fax. +31 152 616 289

Position	Qty.	Description
	1	NK 40-125/130 A2-F-A-E-BAQE  Product No.: On request Non-self-priming, single-stage, centrifugal volute pump designed according to ISO 5199 with dimensions and rated performance according to EN 733. Flanges are PN 16 with dimensions according to EN 1092-2. The pump has an axial suction port, a radial discharge port and horizontal shaft. It is of the back pull-out design enabling removal of the coupling, bearing bracket and impeller without disturbing the motor, pump housing or pipework. The unbalanced rubber bellows seal is according to DIN EN 12756. The pump is fitted with a foot-mounted, fan-cooled asynchronous motor. Pump and motor are mounted on a common base frame. Further product details The product's minimum efficiency index (MEI) is greater or equal to 0.70. This is by the Commission Regulation (EU) considered as an indicative benchmark for best-performing water pump available on the market as from 1 January 2013. Pump and motor are mounted on a common steel base frame in accordance with ISO 3661. The back pull-out design together with a spacer coupling makes it possible to make service on the pump without dismantling the pump housing and motor from the base frame. This saves realignment of pump and motor after service. 1) Remove coupling. 2) Remove the bolts in the bearing bracket support foot. 3) Remove the bearing bracket from the pump housing.  Cast-iron parts have an epoxy-based coating made in a cathodic electro-deposition (CED) process. CED is a high-quality dip-painting process where an electrical field around the products ensures deposition of paint particles as a thin, well-controlled layer on the surface. An integral part of the process is a pretreatment. The entire process consists of these elements: 1) Alkaline-based cleaning. 2) Zinc phosphating. 3) Cathodic electro-deposition. 4) Curing to a dry film thickness 18-22 my m. The colour code for the finished product is NCS 9000/RAL 9005. Pump The pump housing has both a priming and a drain hole closed by plugs. The impeller is a closed impeller with double-curved blades with smooth surfaces. The impeller is statically balanced according to ISO 1940-1 class G6.3 and hydraulically balanced to compensate for axial thrust. Wear rings used in pump housing and for impeller are made of bronze/brass or cast iron. The pump is fitted with an unbalanced rubber bellows seal with torque transmission across the spring and around the bellows. Due to the bellows, the seal does not wear the shaft, and the axial movement is not prevented by deposits on the shaft. Primary seal: • Rotating seal ring material: carbon graphite, metal-impregnated • Stationary seat material: silicon carbide (SiC)

This material pairing has a very good corrosion resistance and is especially suitable for water up to 120 °C. However, seal life will be reduced at temperatures above 90 °C. The material pairing is not recommended for liquids containing particles as this will result in heavy wear on the SiC face.

Secondary seal material: EPDM (ethylene-propylene rubber)

EPDM has excellent resistance to hot water. EPDM is not suitable for mineral oils.

The shaft is made of stainless steel and has a diameter of 24 mm where the coupling is mounted.

The pump uses a spacer coupling between the pump and motor shaft.



Motor

The motor is a totally enclosed, fan-cooled motor with principal dimensions to IEC and DIN standards and mounting designation B3 (IM 1001). Electrical tolerances comply with IEC 60034.

The motor does not incorporate motor protection and must be connected to a motor-protective circuit breaker which can be manually reset. The motor-protective circuit breaker must be set according to the rated current of the motor (I₁/1).

Technical data

Liquid:

Pumped liquid:	Water
Liquid temperature range:	0 .. 120 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m ³

Technical:

Rated flow:	22.3 m ³ /h
Rated head:	4.1 m
Actual impeller diameter:	130 mm
Impeller nom:	125 mm
Primary shaft seal:	BAQE
Secondary shaft seal:	NONE
Curve tolerance:	ISO9906:2012 3B

Materials:

Pump housing:	Cast iron EN-GJL-250 ASTM A48-40 B
Impeller:	Cast iron EN-GJL-200 ASTM A48-30 B
Rubber:	EPDM
Wear ring mat.:	High alloy brass(CuZn34Mn3Al2

Installation:


Maximum ambient temperature:	40 °C
Maximum operating pressure:	16 bar
Flange standard:	EN 1092-2
Pump inlet:	DN 65
Pump outlet:	DN 40
Pressure rating:	PN 16
Coupling type:	Spacer
Base frame:	EN / ISO

Electrical data:

Motor type:	71B
Rated power - P ₂ :	0.37 kW
Mains frequency:	50 Hz

Position	Qty.	Description
		Rated voltage: 3 x 220-240D/380-415Y V Rated current: 1.90/1.10 A Starting current: 400-440 % Cos phi - power factor: 0.77-0.67 Rated speed: 1400-1420 rpm Efficiency: 66.0% Motor efficiency at full load: 66.0 % Motor efficiency at 3/4 load: 72.2 % Motor efficiency at 1/2 load: 67.6 % Number of poles: 4 Enclosure class (IEC 34-5): 55 Dust/Jetting Insulation class (IEC 85): F Lubricant type: Grease Others: Minimum efficiency index, MEI $\geq$ 0.70 ErP status: EuP Standalone/Prod. Net weight: 87 kg Gross weight: 101 kg Shipping volume: 0.249 m³

On request NK 40-125/130 A2-F-A-E-BAQE 50 Hz



Description	Value		
General information:			
Product name:	NK 40-125/130		
Product No:	A2-F-A-E-BAQE		
EAN number:	On request		
Technical:			
Rated flow:	22.3 m³/h		
Rated head:	4.1 m		
Actual impeller diameter:	130 mm		
Impeller nom:	125 mm		
Primary shaft seal:	BAQE		
Secondary shaft seal:	NONE		
Shaft diameter:	24 mm		
Curve tolerance:	ISO9906:2012 3B		
Pump version:	A2		
Materials:			
Pump housing:	Cast iron		
	EN-GJL-250		
	ASTM A48-40 B		
Impeller:	Cast iron		
	EN-GJL-200		
	ASTM A48-30 B		
Material code:	A		
Rubber:	EPDM		
Code for rubber:	E		
Wear ring mat.:	High alloy brass(CuZn34Mn3Al2		
Installation:			
Maximum ambient temperature:	40 °C		
Maximum operating pressure:	16 bar		
Flange standard:	EN 1092-2		
Pump inlet:	DN 65		
Pump outlet:	DN 40		
Pressure rating:	PN 16		
Coupling type:	Spacer		
Wear ring(s):	neckring(s)		
Base frame:	EN / ISO		
Connect code:	F		
Liquid:			
Pumped liquid:	Water		
Liquid temperature range:	0 .. 120 °C		
Liquid temperature during operation:	20 °C		
Density:	998.2 kg/m³		
Electrical data:			
Motor type:	71B		
Rated power - P2:	0.37 kW		
Mains frequency:	50 Hz		
Rated voltage:	3 x 220-240D/380-415Y V		
Rated current:	1.90/1.10 A		
Starting current:	400-440 %		
Cos phi - power factor:	0.77-0.67		
Rated speed:	1400-1420 rpm		
Efficiency:	66.0%		
Motor efficiency at full load:	66.0 %		
Motor efficiency at 3/4 load:	72.2 %		
Motor efficiency at 1/2 load:	67.6 %		
Number of poles:	4		
Enclosure class (IEC 34-5):	55 Dust/Jetting		
Insulation class (IEC 85):	F		
Motor protec:	NONE		
Motor No:	87100381		
Lubricant type:	Grease		
Others:			
Minimum efficiency index, MEI ≥:	0.70		

Performance Curves:

Head (H) vs. Flow (Q): The graph shows the pump's head performance. The blue curve represents the 130 mm impeller. The black curve represents the 125 mm impeller. The x-axis is Flow (Q) in m³/h, ranging from 0 to 25. The y-axis is Head (H) in meters, ranging from 0.0 to 5.5. The efficiency (eta) is shown on the right y-axis, ranging from 0 to 100%.

Power (P) vs. Flow (Q): The graph shows the pump's power performance. The blue curve represents the 130 mm impeller (P1). The black curve represents the 125 mm impeller (P2). The x-axis is Flow (Q) in m³/h, ranging from 0 to 25. The y-axis is Power (P) in Watts (W), ranging from 0 to 500. The Net Positive Suction Head (NPSH) is shown on the right y-axis, ranging from 0.0 to 2.5 meters.




Dimensions:

Front View: The pump has a total width of 753 mm and a total height of 286 mm. The inlet flange has a diameter of 65 mm. The outlet flange has a diameter of 40 mm. The base frame has a width of 600 mm and a height of 900 mm.

Top View: The pump has a total width of 390 mm and a total height of 177 mm. The inlet flange has a diameter of 65 mm. The outlet flange has a diameter of 40 mm. The base frame has a width of 300 mm and a height of 345 mm.


Wiring Diagram:

The diagram shows the electrical connections for the pump. The top section is for High Voltage (3 x 220-240D/380-415Y V) and the bottom section is for Low Voltage (3 x 220-240D/380-415Y V). The connections are labeled L1, L2, L3, N, and PE. The diagram also shows the direction of rotation for the motor.





Description	Value
ErP status:	EuP Standalone/Prod.
Net weight:	87 kg
Gross weight:	101 kg
Shipping volume:	0.249 m³

On request NK 40-125/130 A2-F-A-E-BAQE 50 Hz



On request NK 40-125/130 A2-F-A-E-BAQE 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Exploded view



Sectional drawing (TM058200 for TPE2,TPE3)



TM058200

Exploded view (TM057026 for MGE model H/I)



Parts list NK 40-125/130, Product No. On request
Valid from 1.1.2008 (0801)

Pos	Description	Annotation	Données de classification	Référence	Quantité	Unité
+	Motor				1	pcs
-	Coupling cpl.				1	pcs
9	Socket set screw				1	
89.b	Socket set screw		Length (mm): 8		1	
			Thread: M6			
89.d	Hex socket head cap screw		Length (mm): 16		6	
			Thread: M6			
89.p	Coupling female				1	
89o	Coupling part spacer side				12	
89o	Coupling part spacer side				1	
89r	Spacer sleeve				1	
89s	Spacer ring				1	
-	Nut				1	pcs
66	Washer				1	
66a	Spring lock washer				1	
67	Nut		Thread: M14		1	
-	Pump housing cpl.				1	pcs
6	Pump housing				1	
36	Nut		Thread: M10		6	
	Bearing bracket				1	pcs
-	Shaft seal cpl.				1	pcs
72a	O-ring		Diameter: 177,39		1	
			Material type: EPDM			
			Thickness: 3,53			
105	Shaft seal		Material type: BAQE		1	
-	7 Coupling guard cpl.				1	pcs
7	Coupling guard cpl.				1	
7b	Retainer for coupling guard				1	
186	Hex socket head cap screw		Length (mm): 10		4	
			Thread: M6			
-	7.d Foot for coupling guard				1	pcs
7d	Foot for coupling guard				1	
49	Impeller		Outer diameter: 130		1	pcs
72a	O-ring		Diameter: 177,39		1	pcs
			Material type: EPDM			
			Thickness: 3,53			
-	77 Cover				1	pcs
77	Cover				1	
-	90 Base plate				1	pcs
	Hex head screw		Length (mm): 35MM		4	
			Thread: M12			
	Hex head screw		Length (mm): 35MM		2	
			Thread: M12			
	Washer				4	
	Base plate				1	
	Support block				2	
	Support block				2	
	Hex head bolt				4	
7h	Hex head screw		Length (mm): 16		2	
			Thread: M8			
66	Washer				4	
66	Washer				2	
66	Washer				2	

Disclaimer: The information about the Grundfos pump in this document may be outdated.

Data may be subject to alterations without further notice.

Please contact us to verify the data above is still accurate/up-to-date.

All information is copyright Grundfos.



info@lenntech.com

<https://www.lenntech.com>

tel. +31 152 610 900

fax. +31 152 616 289