

EF30.50.06.E.2.50B

Grundfos pump 96877510



Thank you for your interest in our products. Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/EFFAM/96877510/EF30-50-06-E-2-50B.html>

info@lenntech.com


tel. +31 152 610 900

fax. +31 152 616 289




Position	Qty.	Description				
	1	 Product No.: On request GRUNDFOS EF AUTOADAPT pump is a portable pump for both domestic and industrial applications. The pump has a single-vane, semi-open impeller for 30 mm free passage and is suitable for pumping • drainage and surface water with small impurities • wastewater with fibres, e.g. from laundries • wastewater without discharge from toilets • wastewater from commercial buildings without discharge from toilets. The compact design makes the pump suitable for both temporary and permanent installation. The pump has an intermediate oil chamber pre-filled with non-toxic special oil. The pump is fitted with a cable plug for easy dismantling. This plug is hermetically sealed with polyurethane to prevent water from penetrating through the cable into the motor. A clamp between pump housing and motor ensures easy and safe dismantling and assembly. Inspection can be done in the field without any special tools. The pump is fitted with a double shaft seal in the unique cartridge design. This makes it easy to replace the shaft seal very quickly in the field without any special tools. It also eliminates the risk of faulty installation. The motor is insulation class F and has long-life, deep-groove, greased-for-life ball bearings. The pump has R 2 discharge port and is ready for installation either free-standing or on an auto-coupling system. The Grundfos EF AUTOADAPT pumps incorporate a controller, sensors and motor-protection. They only need to be connected to the mains supply. If several pumps are installed in the same tank, the control logic incorporated in the pump will ensure that the load is distributed evenly among the pumps over time. • Alarm relay output. The pump incorporates an alarm relay output. NC and NO are available and can be used as required, for example for acoustic or visual alarms. • Random start delay in case of general power shutdown. • The pump does not start unless the phase sequence is correct. • Self-calibration after each pump cycle. • Anti-seizing system. The anti-seizing system start the pump at programmed intervals to prevent the impeller from seizing up. This function will overwrite the dry-run sensor for non EX versions. • After-run possibility (foam draining) After-run is possible in programmed intervals if risk of floating layer. The Grundfos CIU unit can be connected permanent or temporarily for changing the pre-setting, further settings or read out from the logging and operation parameters like no. of starts and operating hours. Controls: <table><tr><td>Moisture sensor:</td><td>without moisture sensors</td></tr><tr><td>Water-in-oil sensor:</td><td>without water-in-oil sensor</td></tr></table>	Moisture sensor:	without moisture sensors	Water-in-oil sensor:	without water-in-oil sensor
Moisture sensor:	without moisture sensors					
Water-in-oil sensor:	without water-in-oil sensor					

Position	Qty.	Description
		AUTOADAPT: YES Liquid: Liquid temperature range: 0 .. 40 °C Density: 998.2 kg/m³ Technical: Type of impeller: SEMI OPEN Maximum particle size: 30 mm Primary shaft seal: SIC/SIC Secondary shaft seal: LIPSEAL Max. hydraulic efficiency: 60 % Curve tolerance: ISO9906:2012 3B2 Materials: Pump housing: Cast iron EN-GJL-200 Impeller: Cast iron EN-GJS-500-7 Installation: Maximum ambient temperature: 40 °C Maximum operating pressure: 6 bar Pump outlet: R 2 Maximum installation depth: 10 m Auto-coupling: Y Electrical data: Power input - P1: 1 kW Rated power - P2: 0.6 kW Mains frequency: 50 Hz Rated voltage: 3 x 400-415 V Voltage tolerance: +6/-10 % Max starts per. hour: 30 Rated current: 2.3/2.3 A Rated current at 3/4 load: 2.1 A Rated current at 1/2 load: 2 A Starting current: 21 A Rated current at no load: 1.9 A Cos phi - power factor: 0.65 Cos phi - p.f. at 3/4 load: 0.58 Cos phi - p.f. at 1/2 load: 0.50 Rated speed: 2920 rpm Locked-rotor torque: 11 Nm Breakdown torque: 12 Nm Moment of inertia: 0.0035 kg m² Motor efficiency at full load: 59 % Motor efficiency at 3/4 load: 53 % Motor efficiency at 1/2 load: 43 % Number of poles: 2 Start. method: direct-on-line Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Explosion proof: no Length of cable: 10 m Cable type: LYNIFLEX Type of cable plug: NO PLUG Others: Net weight: 38 kg

On request EF30.50.06.E.2.50B 50 Hz





Description	Value
General information:	
Product name:	EF30.50.06.E.2.50B
Product No:	On request
EAN number:	On request
Technical:	
Max flow:	9.11 l/s
Head max:	13.7 m
Type of impeller:	SEMI OPEN
Maximum particle size:	30 mm
Primary shaft seal:	SIC/SIC
Secondary shaft seal:	LIPSEAL
Max. hydraulic efficiency:	60 %
Curve tolerance:	ISO9906:2012 3B2
Materials:	
Pump housing:	Cast iron
	EN-GJL-200
Impeller:	Cast iron
	EN-GJS-500-7
Installation:	
Maximum ambient temperature:	40 °C
Maximum operating pressure:	6 bar
Pump outlet:	R 2
Maximum installation depth:	10 m
Inst dry/wet:	S
Installation:	vertical
Auto-coupling:	Y
Liquid:	
Liquid temperature range:	0 .. 40 °C
Density:	998.2 kg/m ³
Electrical data:	
Power input - P1:	1 kW
Rated power - P2:	0.6 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 400-415 V
Voltage tolerance:	+6/-10 %
Max starts per. hour:	30
Rated current:	2.3/2.3 A
Rated current at 3/4 load:	2.1 A
Rated current at 1/2 load:	2 A
Starting current:	21 A
Rated current at no load:	1.9 A
Cos phi - power factor:	0.65
Cos phi - p.f. at 3/4 load:	0.58
Cos phi - p.f. at 1/2 load:	0.50
Rated speed:	2920 rpm
Locked-rotor torque:	11 Nm
Breakdown torque:	12 Nm
Moment of inertia:	0.0035 kg m ²
Motor efficiency at full load:	59 %
Motor efficiency at 3/4 load:	53 %
Motor efficiency at 1/2 load:	43 %
Number of poles:	2
Start. method:	direct-on-line
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Explosion proof:	no
Motor protec:	THERMAL SWITCH
Length of cable:	10 m
Cable type:	LYNIFLEX
Type of cable plug:	NO PLUG
Controls:	
Control box:	not included
Additional I/O:	Build in
Moisture sensor:	without moisture sensors





Description	Value
Water-in-oil sensor:	without water-in-oil sensor
AUTOADAPT:	YES
Others:	
Net weight:	38 kg

On request EF30.50.06.E.2.50B 50 Hz




Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

On request EF30.50.06.E.2.50B 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

On request EF30.50.06.E.2.50B 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Exploded view



Sectional drawing (TM058200 for TPE2,TPE3)



TM058200

Exploded view (TM057026 for MGE model H/I)



Disclaimer: The information about the Grundfos pump in this document may be outdated.

Data may be subject to alterations without further notice.

Please contact us to verify the data above is still accurate/up-to-date.

All information is copyright Grundfos.



info@lenntech.com

<https://www.lenntech.com>

tel. +31 152 610 900

fax. +31 152 616 289