

SL1.50.65.11.E.Ex.2.1.502

Grundfos Pump 96878456



Thank you for your interest in our products

Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/SL1000/96878456/SL1-50-65-11-E-EX-2-1-502.html>

info@lenntech.com

tel. +31-15-261.09.00


fax. +31-15-261.62.89

Position	Qty.	Description
	1	SL1.50.65.11.E.EX.2.1.502  Product No.: 96878456 Non-self-priming, single-stage, centrifugal pump designed for handling wastewater, process water and unscreened raw sewage. The pump is designed for intermittent and continuous operations in submerged installation. The revolutionary S-tube® impeller provides free spherical passage of solids up to 50 mm and is suitable for wastewater with a dry matter content of up to 3 %. A unique stainless-steel clamp assembling system enables quick and easy disassembly of the pump from the motor unit for service and inspection. No special tools are required. Pipework connection is via a DIN flange. The pump is explosion-proof. Further product details Typical application is transfer of liquid, such as: - large quantities of drainage and surface water - domestic wastewater with discharge from toilets - wastewater from commercial buildings without discharge from toilets - sludge-containing industrial wastewater. The pump is ideal for pumping of the above liquids from for instance: - municipal network pumping stations - public buildings - blocks of flats - factories/industry. The pump is suitable for both temporary and permanent installation either as free-standing on ring stand or on an auto-coupling system. Pump The pump housing, motor top and impeller are made of cast iron (EN-GJL-250). The S-tube® impeller is providing free spherical passage through the impeller and pump housing and creates a natural extension of the pipework connected to the pump. The S-tube® impeller is a wet-balanced and tube-shaped channel impeller placed in a pump housing that matches the smooth tube shape leaving no obstructions or dead zones. The key to the S-tube® design is simplicity, with no cutting or moving functions that can get worn over time, thereby ensuring constant, superior efficiency. The simple design means lower life cycle costs because abrasive wear is reduced and there are fewer clogging incidents.  The shaft seal consists of two mechanical seals that ensure a reliable sealing between the pumped liquid and motor. The shaft seals are incorporated in a single-unit cartridge shaft seal system that is easy to replace in the field without use of special tools. The combination of the primary and secondary seals in a cartridge shaft seal system results in a shorter assembly length compared to conventional shaft seals. - Primary seal: Silicon carbide/silicon carbide (SiC/SiC) - Secondary seal: Carbon/Ceramics




Position	Qty.	Description																																																												
		The shaft seal is bidirectional, meaning it operates correctly in case of backflow through the pump.  The pump is approved according to CE 0344. Motor The motor is a watertight, totally encapsulated motor supplied with a 10 m power cable. The stainless steel plug is fastened with a union nut. This nut and the O-rings provide sealing against ingress of the liquid. The plug is polyurethane-embedded, ensuring a watertight and durable seal around the leads of the cable. This prevents the ingress of water into the motor through the cable in case of cable breakage or adverse handling in connection with installation or service. A compact motor construction with a short shaft reduces vibrations, resulting in an increased efficiency and lifetime of the shaft seal and ball bearings. The motor features built-in thermal protection to protect the motor against overheating and ensure the reliability. The pump is designed for speed-controlled operation to keep the energy consumption at a minimum. To avoid the risk of sedimentation in the pipes, we recommend that you operate the speed-controlled pump within a speed range of 30 % to 100 % and at a flow rate above 1 m/s. Controls: <table><tr><td>Moisture sensor:</td><td>without moisture sensors</td></tr><tr><td>Water-in-oil sensor:</td><td>without water-in-oil sensor</td></tr><tr><td>AUTOADAPT:</td><td>YES</td></tr></table> Liquid: <table><tr><td>Maximum liquid temperature:</td><td>40 °C</td></tr><tr><td>Density:</td><td>998.2 kg/m³</td></tr></table> Technical: <table><tr><td>Type of impeller:</td><td>SINGLE CHANNEL</td></tr><tr><td>Maximum particle size:</td><td>50 mm</td></tr><tr><td>Primary shaft seal:</td><td>SIC/SIC</td></tr><tr><td>Secondary shaft seal:</td><td>LIPSEAL</td></tr><tr><td>Approvals on nameplate:</td><td>CE 0344</td></tr><tr><td>Curve tolerance:</td><td>ISO9906:2012 3B2</td></tr></table> Materials: <table><tr><td>Pump housing:</td><td>EN-GJL-200</td></tr><tr><td></td><td>EN-GJL-200</td></tr><tr><td>Impeller:</td><td>EN-GJS-500-7</td></tr><tr><td></td><td>EN-GJS-500-7</td></tr><tr><td>Motor:</td><td>EN-GJL-200</td></tr></table> Installation: <table><tr><td>Maximum ambient temperature:</td><td>40 °C</td></tr><tr><td>Flange standard:</td><td>DIN</td></tr><tr><td>Pump inlet:</td><td>65</td></tr><tr><td>Pump outlet:</td><td>65</td></tr><tr><td>Pressure rating:</td><td>PN10</td></tr><tr><td>Maximum installation depth:</td><td>10 m</td></tr><tr><td>Frame range:</td><td>A</td></tr></table> Electrical data: <table><tr><td>Power input - P1:</td><td>1.6 kW</td></tr><tr><td>Rated power - P2:</td><td>1.1 kW</td></tr><tr><td>Mains frequency:</td><td>50 Hz</td></tr><tr><td>Rated voltage:</td><td>1 x 230 V</td></tr><tr><td>Voltage tolerance:</td><td>+6/-10 %</td></tr><tr><td>Max starts per. hour:</td><td>30</td></tr><tr><td>Rated current:</td><td>7.4 A</td></tr></table>	Moisture sensor:	without moisture sensors	Water-in-oil sensor:	without water-in-oil sensor	AUTOADAPT:	YES	Maximum liquid temperature:	40 °C	Density:	998.2 kg/m³	Type of impeller:	SINGLE CHANNEL	Maximum particle size:	50 mm	Primary shaft seal:	SIC/SIC	Secondary shaft seal:	LIPSEAL	Approvals on nameplate:	CE 0344	Curve tolerance:	ISO9906:2012 3B2	Pump housing:	EN-GJL-200		EN-GJL-200	Impeller:	EN-GJS-500-7		EN-GJS-500-7	Motor:	EN-GJL-200	Maximum ambient temperature:	40 °C	Flange standard:	DIN	Pump inlet:	65	Pump outlet:	65	Pressure rating:	PN10	Maximum installation depth:	10 m	Frame range:	A	Power input - P1:	1.6 kW	Rated power - P2:	1.1 kW	Mains frequency:	50 Hz	Rated voltage:	1 x 230 V	Voltage tolerance:	+6/-10 %	Max starts per. hour:	30	Rated current:	7.4 A
Moisture sensor:	without moisture sensors																																																													
Water-in-oil sensor:	without water-in-oil sensor																																																													
AUTOADAPT:	YES																																																													
Maximum liquid temperature:	40 °C																																																													
Density:	998.2 kg/m³																																																													
Type of impeller:	SINGLE CHANNEL																																																													
Maximum particle size:	50 mm																																																													
Primary shaft seal:	SIC/SIC																																																													
Secondary shaft seal:	LIPSEAL																																																													
Approvals on nameplate:	CE 0344																																																													
Curve tolerance:	ISO9906:2012 3B2																																																													
Pump housing:	EN-GJL-200																																																													
	EN-GJL-200																																																													
Impeller:	EN-GJS-500-7																																																													
	EN-GJS-500-7																																																													
Motor:	EN-GJL-200																																																													
Maximum ambient temperature:	40 °C																																																													
Flange standard:	DIN																																																													
Pump inlet:	65																																																													
Pump outlet:	65																																																													
Pressure rating:	PN10																																																													
Maximum installation depth:	10 m																																																													
Frame range:	A																																																													
Power input - P1:	1.6 kW																																																													
Rated power - P2:	1.1 kW																																																													
Mains frequency:	50 Hz																																																													
Rated voltage:	1 x 230 V																																																													
Voltage tolerance:	+6/-10 %																																																													
Max starts per. hour:	30																																																													
Rated current:	7.4 A																																																													

Position	Qty.	Description
		Rated current at 3/4 load: 5.8 A Rated current at 1/2 load: 4.5 A Starting current: 38 A Rated current at no load: 2.6 A Cos phi - power factor: 0,97 Cos phi - p.f. at 3/4 load: 0,96 Cos phi - p.f. at 1/2 load: 0,89 Rated speed: 2830 rpm Motor efficiency at full load: 67 % Motor efficiency at 3/4 load: 66 % Motor efficiency at 1/2 load: 60 % Capacitor size - run: 20 µF Number of poles: 2 Start. method: direct-on-line Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Explosion proof: yes Length of cable: 10 m Cable type: LYNIFLEX Others: Net weight: 59.5 kg

96878456 SL1.50.65.11.E.EX.2.1.502 50 Hz




Description	Value
General information:	
Product name:	SL1.50.65.11.E.EX.2.1.502
Product No:	96878456
EAN number:	5700312550341
Technical:	
Max flow:	17.9 l/s
Head max:	15.9 m
Type of impeller:	SINGLE CHANNEL
Maximum particle size:	50 mm
Primary shaft seal:	SIC/SIC
Secondary shaft seal:	LIPSEAL
Approvals on nameplate:	CE 0344
Curve tolerance:	ISO9906:2012 3B2
Cooling jacket:	without cooling jacket
Materials:	
Pump housing:	EN-GJL-200
	EN-GJL-200
Impeller:	EN-GJS-500-7
	EN-GJS-500-7
Motor:	EN-GJL-200
Installation:	
Maximum ambient temperature:	40 °C
Flange standard:	DIN
Pump inlet:	65
Pump outlet:	65
Pressure rating:	PN10
Maximum installation depth:	10 m
Inst dry/wet:	SUBMERGED
Installation:	Vertical
Frame range:	A
Liquid:	
Maximum liquid temperature:	40 °C
Density:	998.2 kg/m³
Electrical data:	
Power input - P1:	1.6 kW
Rated power - P2:	1.1 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 230 V
Voltage tolerance:	+6/-10 %
Max starts per. hour:	30
Rated current:	7.4 A
Rated current at 3/4 load:	5.8 A
Rated current at 1/2 load:	4.5 A
Starting current:	38 A
Rated current at no load:	2.6 A
Cos phi - power factor:	0,97
Cos phi - p.f. at 3/4 load:	0,96
Cos phi - p.f. at 1/2 load:	0,89
Rated speed:	2830 rpm
Motor efficiency at full load:	67 %
Motor efficiency at 3/4 load:	66 %
Motor efficiency at 1/2 load:	60 %
Capacitor size - run:	20 µF
Number of poles:	2
Start. method:	direct-on-line
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Explosion proof:	yes
Motor protec:	THERMAL SWITCH
Length of cable:	10 m
Cable type:	LYNIFLEX
Controls:	
Additional I/O:	N
Moisture sensor:	without moisture sensors




Description	Value
Water-in-oil sensor:	without water-in-oil sensor
AUTOADAPT:	YES
Others:	
Net weight:	59.5 kg

96878456 SL1.50.65.11.E.EX.2.1.502 50 Hz




Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

96878456 SL1.50.65.11.E.EX.2.1.502 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

96878456 SL1.50.65.11.E.EX.2.1.502 50 Hz



Note! All units are in [mm] unless others are stated.

*Disclaimer: The information about the Grundfos pump in this document may be outdated.
Data may be subject to alterations without further notice.
Please contact us to verify the data above is still accurate/up-to-date.*

All information is copyright Grundfos.



info@lenntech.com

www.lenntech.com

tel. +31-15-261.09.00

fax. +31-15-261.62.89