

DWK.E.10.150.300.5.1D.R

Grundfos Pump 96922749



Thank you for your interest in our products

Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/DWK000/96922749/DWK-E-10-150-300-5-1D-R.html>

info@lenntech.com


tel. +31-15-261.09.00

fax. +31-15-261.62.89




Position	Qty.	Description
	1	DWK.E.10.150.300.5.1D.R  Note! Product picture may differ from actual product Product No.: 96922749 Submersible Contractor Pump Grundfos DWK pump is a submersible pump for dewatering and drainage applications. The pump is suitable for pumping ·water with dirt from drainage pits ·water with sand from construction sites, excavation sites and tunnels The pump design makes it suitable for both temporary and permanent installation. The pump is cast iron, with vertical discharge port and integrated submersible 3-phase totally enclosed motor in insulation class F (155°C). The pump has a rise pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and a high chrome stainless steel enclosed impeller to ensure high efficiency and maintained performance. The pump is equipped with a double mechanical seal and an additional lip seal that prevents the shaft and the mechanical seal from abrasives. The pump is equipped with a temperature bi-metal sensor for motor protection in case of overheating and electrode seal sensor to detect water penetration in to the motor housing. The pump is fitted with suction strainer and 10 m cable. The cable sealing consist of a rubber bushing, epoxy and rubber cover that eliminates the risk of water penetration in to the motor. The pump is equipped with a hose coupling discharge. Controls: Seal sensor:Y Liquid: Liquid temperature range:0 .. 40 °C Density:998.2 kg/m³ Technical: Actual impeller diameter:243 mm Type of impeller:E Maximum particle size:10 mm Primary shaft seal:SIC-SIC Secondary shaft seal:CERAMIC-CARBON Max. hydraulic efficiency:75 %

Position	Qty.	Description
		Curve tolerance: ISO9906:2012 3B Materials: Pump housing: Cast iron EN1561 EN-GJL-200 Impeller: high-chrome stainless steel DIN W.-Nr. HI-CR Motor: Cast iron EN1561 EN-GJL-200 Installation: Maximum ambient temperature: 40 °C Pump outlet: DN 150 Maximum installation depth: 25 m Electrical data: Rated power - P2: 30 kW Mains frequency: 50 Hz Rated voltage: 3 x 380-415 V Voltage tolerance: +5/-5 % Max starts per. hour: 18 Rated current: 59 A Rated current at 3/4 load: 46 A Rated current at 1/2 load: 34 A Cos phi - power factor: 0,86 Cos phi - p.f. at 3/4 load: 0,828 Cos phi - p.f. at 1/2 load: 0,751 Rated speed: 2850 rpm Motor efficiency at full load: 89.7 % Motor efficiency at 3/4 load: 89.1 % Motor efficiency at 1/2 load: 87.2 % Number of poles: 2 Start. method: star/delta Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Explosion proof: no Length of cable: 10 m Cable type: TP90/TP90 Others: Net weight: 442 kg


96922749 DWK.E.10.150.300.5.1D.R 50 Hz



Description	Value
General information:	
Product name:	DWK.E.10.150.300.5.1D.R
Product No:	96922749
EAN number:	5700313725373
Technical:	
Max flow:	48.6 l/s
Head min:	5 m
Head max:	71 m
Actual impeller diameter:	243 mm
Type of impeller:	E
Maximum particle size:	10 mm
Primary shaft seal:	SIC-SIC
Secondary shaft seal:	CERAMIC-CARBON
Max. hydraulic efficiency:	75 %
Curve tolerance:	ISO9906:2012 3B
Materials:	
Pump housing:	Cast iron EN1561 EN-GJL-200
Impeller:	high-chrome stainless steel DIN W.-Nr. HI-CR
Motor:	Cast iron EN1561 EN-GJL-200
Installation:	
Maximum ambient temperature:	40 °C
Pump outlet:	DN 150
Maximum installation depth:	25 m
Liquid:	
Liquid temperature range:	0 .. 40 °C
Density:	998.2 kg/m ³
Min. pH-value:	4
Electrical data:	
Rated power - P2:	30 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-415 V
Voltage tolerance:	+5/-5 %
Max starts per. hour:	18
Rated current:	59 A
Rated current at 3/4 load:	46 A
Rated current at 1/2 load:	34 A
Cos phi - power factor:	0,86
Cos phi - p.f. at 3/4 load:	0,828
Cos phi - p.f. at 1/2 load:	0,751
Rated speed:	2850 rpm
Motor efficiency at full load:	89.7 %
Motor efficiency at 3/4 load:	89.1 %
Motor efficiency at 1/2 load:	87.2 %
Number of poles:	2
Start. method:	star/delta
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Explosion proof:	no
Length of cable:	10 m
Cable type:	TP90/TP90
Cable size:	7X10.0MM2+6X1.5MM2
Controls:	
Seal sensor:	Y
Sensor type:	BI-METAL
Others:	
Net weight:	442 kg




96922749 DWK.E.10.150.300.5.1D.R 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

96922749 DWK.E.10.150.300.5.1D.R 50 Hz



Note! All units are in [mm] unless others are stated.

*Disclaimer: The information about the Grundfos pump in this document may be outdated.
Data may be subject to alterations without further notice.
Please contact us to verify the data above is still accurate/up-to-date.*

All information is copyright Grundfos.



info@lenntech.com

www.lenntech.com

tel. +31-15-261.09.00

fax. +31-15-261.62.89