

DWK.O.13.150.150.5.1D

Grundfos Pump 96926060



Thank you for your interest in our products

Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/DWK000/96926060/DWK-O-13-150-150-5-1D.html>

info@lenntech.com


tel. +31-15-261.09.00

fax. +31-15-261.62.89




Position	Qty.	Description																																
	1	 Product No.: 96926060 Submersible Contractor Pump Grundfos DWK pump is a submersible pump for dewatering and drainage applications. The pump is suitable for pumping ·large quantities of underground and surface water ·drainage water at high head ·water with dirt from drainage pits The compact design makes the pump suitable for both temporary and permanent installation. The pump is cast iron, with vertical discharge port and integrated submersible 3-phase totally enclosed motor in insulation class F (155°C). The pump has a rise pipe, a double mechanical seal and semi-open impeller type The pump is equipped with a temperature Bi-metal sensor for motor protection in case of overheating and electrode seal sensor to detect water penetration in to the motor housing. The pump is fitted with suction strainer, lifting handle and 10 m cable. Controls: <table><tr><td>Seal sensor:</td><td>N</td></tr></table> Liquid: <table><tr><td>Liquid temperature range:</td><td>0 .. 40 °C</td></tr><tr><td>Density:</td><td>998.2 kg/m³</td></tr></table> Technical: <table><tr><td>Actual impeller diameter:</td><td>186 mm</td></tr><tr><td>Type of impeller:</td><td>O</td></tr><tr><td>Maximum particle size:</td><td>13 mm</td></tr><tr><td>Primary shaft seal:</td><td>SIC-SIC</td></tr><tr><td>Secondary shaft seal:</td><td>CERAMIC-CARBON</td></tr><tr><td>Max. hydraulic efficiency:</td><td>59 %</td></tr><tr><td>Curve tolerance:</td><td>ISO9906:2012 3B</td></tr></table> Materials: <table><tr><td>Pump housing:</td><td>Cast iron EN1561 EN-GJL-200</td></tr><tr><td>Impeller:</td><td>Ductile cast iron EN1563 EN-GJS-450-10</td></tr><tr><td>Motor:</td><td>Cast iron EN1561 EN-GJL-200</td></tr></table> Installation: <table><tr><td>Maximum ambient temperature:</td><td>40 °C</td></tr><tr><td>Pump outlet:</td><td>DN 150</td></tr><tr><td>Maximum installation depth:</td><td>25 m</td></tr></table> Electrical data:	Seal sensor:	N	Liquid temperature range:	0 .. 40 °C	Density:	998.2 kg/m³	Actual impeller diameter:	186 mm	Type of impeller:	O	Maximum particle size:	13 mm	Primary shaft seal:	SIC-SIC	Secondary shaft seal:	CERAMIC-CARBON	Max. hydraulic efficiency:	59 %	Curve tolerance:	ISO9906:2012 3B	Pump housing:	Cast iron EN1561 EN-GJL-200	Impeller:	Ductile cast iron EN1563 EN-GJS-450-10	Motor:	Cast iron EN1561 EN-GJL-200	Maximum ambient temperature:	40 °C	Pump outlet:	DN 150	Maximum installation depth:	25 m
Seal sensor:	N																																	
Liquid temperature range:	0 .. 40 °C																																	
Density:	998.2 kg/m³																																	
Actual impeller diameter:	186 mm																																	
Type of impeller:	O																																	
Maximum particle size:	13 mm																																	
Primary shaft seal:	SIC-SIC																																	
Secondary shaft seal:	CERAMIC-CARBON																																	
Max. hydraulic efficiency:	59 %																																	
Curve tolerance:	ISO9906:2012 3B																																	
Pump housing:	Cast iron EN1561 EN-GJL-200																																	
Impeller:	Ductile cast iron EN1563 EN-GJS-450-10																																	
Motor:	Cast iron EN1561 EN-GJL-200																																	
Maximum ambient temperature:	40 °C																																	
Pump outlet:	DN 150																																	
Maximum installation depth:	25 m																																	

Position	Qty.	Description
		Rated power - P2: 15 kW Mains frequency: 50 Hz Rated voltage: 3 x 380-415 V Voltage tolerance: +5/-5 % Max starts per. hour: 30 Rated current: 27.8 A Rated current at 3/4 load: 21.1 A Rated current at 1/2 load: 14.5 A Maximum current consumption: 27.8 A Cos phi - power factor: 0.92 Cos phi - p.f. at 3/4 load: 0.91 Cos phi - p.f. at 1/2 load: 0.88 Rated speed: 2850 rpm Motor efficiency at full load: 89.8 % Motor efficiency at 3/4 load: 90.3 % Motor efficiency at 1/2 load: 89.5 % Number of poles: 2 Start. method: star/delta Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Explosion proof: no Length of cable: 10 m Cable type: TP90/TP90 Others: Net weight: 195 kg


96926060 DWK.O.13.150.150.5.1D 50 Hz



Description	Value
General information:	
Product name:	DWK.O.13.150.150.5.1D
Product No:	96926060
EAN number:	5700313815081
Technical:	
Max flow:	33.1 l/s
Head min:	24.3 m
Head max:	37.3 m
Actual impeller diameter:	186 mm
Type of impeller:	O
Maximum particle size:	13 mm
Primary shaft seal:	SIC-SIC
Secondary shaft seal:	CERAMIC-CARBON
Max. hydraulic efficiency:	59 %
Curve tolerance:	ISO9906:2012 3B
Materials:	
Pump housing:	Cast iron EN1561 EN-GJL-200
Impeller:	Ductile cast iron EN1563 EN-GJS-450-10
Motor:	Cast iron EN1561 EN-GJL-200
Installation:	
Maximum ambient temperature:	40 °C
Pump outlet:	DN 150
Maximum installation depth:	25 m
Liquid:	
Liquid temperature range:	0 .. 40 °C
Density:	998.2 kg/m ³
Min. pH-value:	4
Electrical data:	
Rated power - P2:	15 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-415 V
Voltage tolerance:	+5/-5 %
Max starts per. hour:	30
Rated current:	27.8 A
Rated current at 3/4 load:	21.1 A
Rated current at 1/2 load:	14.5 A
Maximum current consumption:	27.8 A
Cos phi - power factor:	0.92
Cos phi - p.f. at 3/4 load:	0.91
Cos phi - p.f. at 1/2 load:	0.88
Rated speed:	2850 rpm
Motor efficiency at full load:	89.8 %
Motor efficiency at 3/4 load:	90.3 %
Motor efficiency at 1/2 load:	89.5 %
Number of poles:	2
Start. method:	star/delta
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Explosion proof:	no
Length of cable:	10 m
Cable type:	TP90/TP90
Cable size:	7X4.0MM2+4X1MM2
Controls:	
Seal sensor:	N
Sensor type:	Y
Others:	
Net weight:	195 kg




96926060 DWK.O.13.150.150.5.1D 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

96926060 DWK.O.13.150.150.5.1D 50 Hz



Note! All units are in [mm] unless others are stated.

*Disclaimer: The information about the Grundfos pump in this document may be outdated.
Data may be subject to alterations without further notice.
Please contact us to verify the data above is still accurate/up-to-date.*

All information is copyright Grundfos.



info@lenntech.com

www.lenntech.com

tel. +31-15-261.09.00

fax. +31-15-261.62.89