

SEV.80.100.110.2.51E.R

Grundfos pump 97679526



Thank you for your interest in our products. Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/SEV00/97679526/SEV-80-100-110-2-51E-R.html>

info@lenntech.com

tel. +31 152 610 900


fax. +31 152 616 289

Position	Qty.	Description
	1	SEV.80.100.110.2.51E.R  Note! Product picture may differ from actual product Product No.: On request Non-self-priming, single-stage, centrifugal pump designed for handling wastewater, process water and unscreened raw sewage. The pump is designed for intermittent and continuous operation. The liquidless and maintenance free cooling system ensures that the pump can be used for submerged or dry installation. The efficient SuperVortex impeller provides passage of long fibres and solids up to 80 mm and is suitable for wastewater with a dry matter content of up to 5 %. A unique stainless-steel clamp assembling system enables quick and easy disassembly of the pump from the motor unit for service and inspection. No special tools are required. Pipework connection is via a DIN flange. Further product details Typical application is transfer of liquid, such as: - large quantities of drainage and surface water - domestic wastewater with discharge from toilets - wastewater from commercial buildings without discharge from toilets - sludge-containing industrial wastewater. The pump is ideal for pumping of the above liquids from for instance: - municipal network pumping stations - public buildings - blocks of flats - factories/industry. The pump is suitable for both temporary and permanent installation either as free-standing on ring stand, on base stand, on brackets or on an auto-coupling system. Pump The pump is fitted with an easy-to-clean stainless-steel motor sleeve (EN 1.4401) that is extremely robust and impact-resistant. The entire pump is made of stainless steel (EN 1.4408). The SuperVortex impeller is a symmetrical multivane winglet impeller. The design ensures a flow entirely outside the impeller providing limited contact between the impeller and the pumped liquid. This ensures that long fibres, rags and more passes freely through the pump without getting caught and without causing clogging or jamming.  The shaft seal consists of two mechanical seals that ensure a reliable sealing between the pumped liquid and motor. The shaft seals are incorporated in a single-unit cartridge shaft seal system that is easy to replace in the field without use of special tools. The combination of the primary and secondary seals in a cartridge shaft seal system results in a shorter assembly length compared to conventional shaft seals. - Primary seal: Silicon carbide/silicon carbide (SiC/SiC) - Secondary seal: Carbon/Ceramics





Position	Qty.	Description																																																		
		The shaft seal is bidirectional, meaning it operates correctly in case of backflow through the pump.  The pump is approved according to EN12050-1. Motor The motor is a watertight, totally encapsulated motor supplied with a 10 m power cable. The stainless steel plug is fastened with a union nut. This nut and the O-rings provide sealing against ingress of the liquid. The plug is polyurethane-embedded, ensuring a watertight and durable seal around the leads of the cable. This prevents the ingress of water into the motor through the cable in case of cable breakage or adverse handling in connection with installation or service. A compact motor construction with a short shaft reduces vibrations, resulting in an increased efficiency and lifetime of the shaft seal and ball bearings. The motor features built-in thermal protection to protect the motor against overheating and ensure the reliability. A solid-block stator housing with built-in cooling conduits, efficiently transfers excess heat to the pumped liquid via a solid cast intermediate cooling flange, that is in direct contact with the pumped liquid. This allows for continuous operation even in a dry installation. An extremely robust impact-resistant stainless-steel jacket with an easy-to-clean smooth surface is fitted on the top of the solid-block stator housing. The pump is designed for speed-controlled operation to keep the energy consumption at a minimum. To avoid the risk of sedimentation in the pipes, we recommend that you operate the speed-controlled pump within a speed range of 30 % to 100 % and at a flow rate above 1 m/s. Controls: <table><tr><td>Moisture sensor:</td><td>without moisture sensors</td></tr><tr><td>Water-in-oil sensor:</td><td>without water-in-oil sensor</td></tr><tr><td>Temp. sensor:</td><td>N</td></tr></table> Liquid: <table><tr><td>Liquid temperature range:</td><td>0 .. 40 °C</td></tr><tr><td>Density:</td><td>998.2 kg/m³</td></tr></table> Technical: <table><tr><td>Type of impeller:</td><td>SUPER VORTEX</td></tr><tr><td>Maximum particle size:</td><td>80 mm</td></tr><tr><td>Primary shaft seal:</td><td>SIC/SIC</td></tr><tr><td>Secondary shaft seal:</td><td>CARBON/CERAMICS</td></tr><tr><td>Max. hydraulic efficiency:</td><td>43 %</td></tr><tr><td>Approvals on nameplate:</td><td>EN12050-1</td></tr><tr><td>Curve tolerance:</td><td>ISO9906:2012 3B</td></tr></table> Materials: <table><tr><td>Pump housing:</td><td>EN 1.4408</td></tr><tr><td>Impeller:</td><td>Stainless steel</td></tr></table> Installation: <table><tr><td>Maximum ambient temperature:</td><td>40 °C</td></tr><tr><td>Maximum operating pressure:</td><td>6 bar</td></tr><tr><td>Flange standard:</td><td>DIN</td></tr><tr><td>Pump outlet:</td><td>DN 100</td></tr><tr><td>Pressure rating:</td><td>PN 10</td></tr><tr><td>Maximum installation depth:</td><td>20 m</td></tr></table> Electrical data: <table><tr><td>Power input - P1:</td><td>12.6 kW</td></tr><tr><td>Rated power - P2:</td><td>11 kW</td></tr><tr><td>Mains frequency:</td><td>50 Hz</td></tr><tr><td>Rated voltage:</td><td>3 x 220-240 V</td></tr><tr><td>Voltage tolerance:</td><td>+6/-10 %</td></tr></table>	Moisture sensor:	without moisture sensors	Water-in-oil sensor:	without water-in-oil sensor	Temp. sensor:	N	Liquid temperature range:	0 .. 40 °C	Density:	998.2 kg/m³	Type of impeller:	SUPER VORTEX	Maximum particle size:	80 mm	Primary shaft seal:	SIC/SIC	Secondary shaft seal:	CARBON/CERAMICS	Max. hydraulic efficiency:	43 %	Approvals on nameplate:	EN12050-1	Curve tolerance:	ISO9906:2012 3B	Pump housing:	EN 1.4408	Impeller:	Stainless steel	Maximum ambient temperature:	40 °C	Maximum operating pressure:	6 bar	Flange standard:	DIN	Pump outlet:	DN 100	Pressure rating:	PN 10	Maximum installation depth:	20 m	Power input - P1:	12.6 kW	Rated power - P2:	11 kW	Mains frequency:	50 Hz	Rated voltage:	3 x 220-240 V	Voltage tolerance:	+6/-10 %
Moisture sensor:	without moisture sensors																																																			
Water-in-oil sensor:	without water-in-oil sensor																																																			
Temp. sensor:	N																																																			
Liquid temperature range:	0 .. 40 °C																																																			
Density:	998.2 kg/m³																																																			
Type of impeller:	SUPER VORTEX																																																			
Maximum particle size:	80 mm																																																			
Primary shaft seal:	SIC/SIC																																																			
Secondary shaft seal:	CARBON/CERAMICS																																																			
Max. hydraulic efficiency:	43 %																																																			
Approvals on nameplate:	EN12050-1																																																			
Curve tolerance:	ISO9906:2012 3B																																																			
Pump housing:	EN 1.4408																																																			
Impeller:	Stainless steel																																																			
Maximum ambient temperature:	40 °C																																																			
Maximum operating pressure:	6 bar																																																			
Flange standard:	DIN																																																			
Pump outlet:	DN 100																																																			
Pressure rating:	PN 10																																																			
Maximum installation depth:	20 m																																																			
Power input - P1:	12.6 kW																																																			
Rated power - P2:	11 kW																																																			
Mains frequency:	50 Hz																																																			
Rated voltage:	3 x 220-240 V																																																			
Voltage tolerance:	+6/-10 %																																																			

Position	Qty.	Description
		Max starts per. hour: 20 Rated current: 39.2-37.0 A Rated current at 3/4 load: 28 A Rated current at 1/2 load: 21.2 A Starting current: 280 A Rated current at no load: 12.4 A Cos phi - power factor: 0.88 Cos phi - p.f. at no load: 0.15 Cos phi - p.f. at 3/4 load: 0.84 Cos phi - p.f. at 1/2 load: 0.75 Rated speed: 2935 rpm Locked-rotor torque: 85 Nm Breakdown torque: 118 Nm Moment of inertia: 0.0368 kg m ² Motor efficiency at full load: 87.7 % Motor efficiency at 3/4 load: 88.1 % Motor efficiency at 1/2 load: 86.4 % Number of poles: 2 Start. method: star/delta Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Explosion proof: no Length of cable: 10 m Cable type: LYNIFLEX Type of cable plug: NO PLUG Others: Net weight: 196 kg

On request SEV.80.100.110.2.51E.R 50 Hz





Description	Value
General information:	
Product name:	SEV.80.100.110.2.51E.R
Product No:	On request
EAN number:	On request
Technical:	
Max flow:	36.1 l/s
Head max:	41.6 m
Type of impeller:	SUPER VORTEX
Maximum particle size:	80 mm
Primary shaft seal:	SIC/SIC
Secondary shaft seal:	CARBON/CERAMICS
Max. hydraulic efficiency:	43 %
Approvals on nameplate:	EN12050-1
Curve tolerance:	ISO9906:2012 3B
Cooling jacket:	with cooling jacket
Materials:	
Pump housing:	EN 1.4408
Impeller:	Stainless steel
Installation:	
Maximum ambient temperature:	40 °C
Maximum operating pressure:	6 bar
Flange standard:	DIN
Pump outlet:	DN 100
Pressure rating:	PN 10
Maximum installation depth:	20 m
Inst dry/wet:	DRY/SUBMERGED
Installation:	horizontal or vertical
Liquid:	
Liquid temperature range:	0 .. 40 °C
Density:	998.2 kg/m ³
Electrical data:	
Power input - P1:	12.6 kW
Rated power - P2:	11 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 220-240 V
Voltage tolerance:	+6/-10 %
Max starts per. hour:	20
Rated current:	39.2-37.0 A
Rated current at 3/4 load:	28 A
Rated current at 1/2 load:	21.2 A
Starting current:	280 A
Rated current at no load:	12.4 A
Cos phi - power factor:	0.88
Cos phi - p.f. at no load:	0.15
Cos phi - p.f. at 3/4 load:	0.84
Cos phi - p.f. at 1/2 load:	0.75
Rated speed:	2935 rpm
Locked-rotor torque:	85 Nm
Breakdown torque:	118 Nm
Moment of inertia:	0.0368 kg m ²
Motor efficiency at full load:	87.7 %
Motor efficiency at 3/4 load:	88.1 %
Motor efficiency at 1/2 load:	86.4 %
Number of poles:	2
Start. method:	star/delta
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Explosion proof:	no
Motor protec:	THERMAL SWITCH
Thermal protec:	internal
Length of cable:	10 m
Cable type:	LYNIFLEX
Type of cable plug:	NO PLUG
Controls:	




Description	Value
Control box:	not included
Moisture sensor:	without moisture sensors
Water-in-oil sensor:	without water-in-oil sensor
Temp. sensor:	N
Others:	
Net weight:	196 kg

On request SEV.80.100.110.2.51E.R 50 Hz




Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

On request SEV.80.100.110.2.51E.R 50 Hz





Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

On request SEV.80.100.110.2.51E.R 50 Hz




Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

On request SEV.80.100.110.2.51E.R 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

On request SEV.80.100.110.2.51E.R 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Exploded view



Sectional drawing (TM058200 for TPE2,TPE3)



TM058200

Exploded view (TM057026 for MGE model H/I)



Parts list SEV.80.100.110.2.51E.R, Product No. On request
Valid from 3.5.2004 (0419)

Pos	Description	Annotation	Données de classification	Référence	Quantité	Unité
	Clamp				2	pcs
-	Kit, O-rings				1	pcs
37	O-ring				1	
37a	O-ring				2	
37b	O-ring				1	
106	O-ring				2	
107	O-ring				1	
108	O-ring				1	
109	O-ring				1	
153b	O-ring				1	
159	O-ring				1	
183a	Washer		Internal diameter: 33		1	
			Outer diameter: 38			
			Thickness: 2			
194	Washer		Internal diameter: 19		2	
			Outer diameter: 12.2			
			Thickness: 4.4			
198	O-ring				1	
	Earth connector				1	pcs
	Thermotransfer foil				0	M
	Thermotransfer foil				0	M
6a	Pin				1	pcs
6a	Pin				1	pcs
7a	Rivet				4	pcs
9a	Parallel key		Dimension: 8X7X28		1	pcs
37	O-ring		Diameter: 330		1	pcs
			Material type: NBR70			
			Thickness: 4			
37a	O-ring		Diameter: 346		2	pcs
			Material type: NBR70			
			Thickness: 4			
37b	O-ring				1	pcs
48	Stator				1	pcs
49	Impeller				1	pcs
50	Pump housing				1	pcs
55	Stator housing				1	pcs
58	Cover for oil chamber				1	pcs
59	Bearing cover				1	pcs
60	Bearing retainer				1	pcs
61	Bearing retainer				1	pcs
66	Washer		Internal diameter: 12.5		1	pcs
			Outer diameter: 31			
			Thickness: 5			
76	Nameplate				1	pcs
+ 92	Strap cpl.				1	pcs
+ 105	Shaft seal				1	pcs
107	O-ring				1	pcs
108	O-ring				1	pcs
109	O-ring		Diameter: 100		1	pcs
			Material type: NBR			
			Thickness: 3			
150	Motor sleeve				1	pcs
151	Motor cover				1	pcs
153	Ball bearing		Designation: 6306.2Z.C4.SYN		1	pcs
153b	O-ring				1	pcs
153b	Circlip				1	pcs
154	Ball bearing				1	pcs
155	Intermediate flange				1	pcs
157	Waved washer				1	pcs

Pos	Description	Annotation	Données de classification	Référence	Quantité	Unité
158	Waved washer				1	pcs
159	O-ring				1	pcs
172	Shaft w/rotor				1	pcs
174a	Lock washer				1	pcs
176	Plug				1	pcs
177	Plug protector				1	pcs
177	Hex socket head cap screw				1	pcs
- 181	Cable cpl.				1	pcs
198	O-ring				1	
183	Hex socket head cap screw		Length (mm): 50 Thread: M30		1	pcs
183a	Washer		Internal diameter: 33 Outer diameter: 38 Thickness: 2		1	pcs
184	Hex socket head cap screw		Designation: DIN 912 Length (mm): 40 Thread: M10		6	pcs
184a	Washer		Internal diameter: 10.5 Outer diameter: 18 Thickness: 1.6		6	pcs
186	Hex socket head cap screw				2	pcs
187	Hex socket head cap screw				4	pcs
188	Hex socket head cap screw				4	pcs
188a	Hex socket head cap screw		Length (mm): 35 Thread: M12		1	pcs
190	Lifting bracket				1	pcs
190a	Rubber bush				2	pcs
192	Cooling paste				6	G
193	Hex socket head cap screw		Designation: A2-70 Length (mm): 20 Thread: M12		2	pcs
193a	Oil				0	L
194	Washer		Internal diameter: 19 Outer diameter: 12.2 Thickness: 4.4		2	pcs
1031	Connector pin				6	pcs

Disclaimer: The information about the Grundfos pump in this document may be outdated.

Data may be subject to alterations without further notice.

Please contact us to verify the data above is still accurate/up-to-date.

All information is copyright Grundfos.



info@lenntech.com

<https://www.lenntech.com>

tel. +31 152 610 900

fax. +31 152 616 289