

SBA3-45 A 230V 50Hz 15m Schuko, GAS IT Grundfos pump 97896290



Thank you for your interest in our products. Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/SBFAM/97896290/SBA-3-45-A.html>

info@lenntech.com


tel. +31 152 610 900

fax. +31 152 616 289



Position	Qty.	Description
	1	SBA 3-45 A  Note! Product picture may differ from actual product Product No.: On request Grundfos SBA 3-45 A is an all-in-one submersible booster designed for pumping clean water for domestic use. The SBA is built on the proven SB platform and comes with an integrated control unit. This eliminates the need for an external pump controller in the house. It is silent when submerged and therefore a noiseless alternative to surface-mounted pumps. The pump is built from high quality composite and stainless steel materials that are resistant to corrosion. The SBA 3-45 A is equipped with a 15 m supply cable, and the maximum installation depth is 10 m below the water level, with a liquid temperature ranging from 0 °C to 40 °C. The pump starts automatically when the pipe pressure falls below 2.2 bar. The SBA 3-45 A is ideal for operation in a well or ground tanks, as it easily prevents solid particles from entering the pump. The maximum particle size is 1 mm. The pump features a float switch, which promises the user a convenient experience with automatic start/stop operation of the pump and provides dry running protection. The single-phase model is effectively protected against any accidental overload by built-in thermal protection. The pump has built-in thermal protection, which immediately stops the pump if it overheats. Having cooled down, the pump automatically restarts when it reaches a normal temperature. Liquid: Pumped liquid: Water Liquid temperature range: 0 .. 40 °C Liquid temperature during operation: 20 °C Density: 998.2 kg/m³ Technical:

Position	Qty.	Description
		Rated flow: 2.83 m³/h Rated head: 30.1 m Max. Particle: 1 mm Curve tolerance: ISO9906:2012 3B Return valve: YES Rated driver speed: 2800 rpm Materials: Pump housing: Composite Impeller: Composite Installation: Range of ambient temperature: -10 .. 50 °C Type of inlet connection: STRAINER Pump outlet: G 1" Maximum installation depth: 10 m Electrical data: Motor protec: YES Insulation: F Power input P1: 1.05 kW Mains frequency: 50 Hz Rated voltage: 220-240 V I start: 12 A Cos phi: 0.94 Capacitor size - run: 13 µF/450 V Enclosure class (IEC 34-5): IP68 Length of cable: 15 m Cable type: H07RN-F 3G1 Type of cable plug: SCHUKO P2: 0.62 kW Rated current: 4.8 A Others: Net weight: 9.69 kg Gross weight: 10.4 kg Shipping volume: 0.022 m³ Danish VVS No.: 391367045 Swedish RSK No.: 5850421 Finnish: LVI NO 4822546 Norwegian NRF no.: 9041859 Approvals: CE,VDE,WEEE


On request SBA 3-45 A 50 Hz



Description	Value
General information:	
Product name:	SBA 3-45 A
Product No:	On request
EAN number:	On request
Technical:	
Rated flow:	2.83 m ³ /h
Rated head:	30.1 m
Impellers:	4
Max. Particle:	1 mm
Curve tolerance:	ISO9906:2012 3B
Return valve:	YES
Rated driver speed:	2800 rpm
Materials:	
Pump housing:	Composite
Impeller:	Composite
Installation:	
Range of ambient temperature:	-10 .. 50 °C
Type of inlet connection:	STRAINER
Pump outlet:	G 1"
Maximum installation depth:	10 m
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	0 .. 40 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m ³
pH-value range:	4-9
Electrical data:	
Motor protec:	YES
Insulation:	F
Power input P1:	1.05 kW
Mains frequency:	50 Hz
Rated voltage:	220-240 V
I start:	12 A
Cos phi:	0.94
Capacitor size - run:	13 µF/450 V
Enclosure class (IEC 34-5):	IP68
Length of cable:	15 m
Cable type:	H07RN-F 3G1
Type of cable plug:	SCHUKO
P2:	0.62 kW
Rated current:	4.8 A
Controls:	
Flow switch:	yes
Others:	
Net weight:	9.69 kg
Gross weight:	10.4 kg
Shipping volume:	0.022 m ³
Danish VVS No.:	391367045
Swedish RSK No.:	5850421
Finnish:	LVI NO 4822546
Norwegian NRF no.:	9041859
Approvals:	CE,VDE,WEEE




On request SBA 3-45 A 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Exploded view



Sectional drawing (TM058200 for TPE2,TPE3)



TM058200

Exploded view (TM057026 for MGE model H/I)



Disclaimer: The information about the Grundfos pump in this document may be outdated.

Data may be subject to alterations without further notice.

Please contact us to verify the data above is still accurate/up-to-date.

All information is copyright Grundfos.



info@lenntech.com

<https://www.lenntech.com>

tel. +31 152 610 900

fax. +31 152 616 289