

DDC 9-7 AR-PP/E/C with access.

Grundfos pump 97974067



Thank you for your interest in our products. Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/DDCFAM/97974067/DDC-9-7-WITH-ACCESS.html>

info@lenntech.com


tel. +31 152 610 900

fax. +31 152 616 289



Position	Qty.	Description
	1	DDC 9-7 WITH ACCESS.  Note! Product picture may differ from actual product Product No.: On request DDC 9-7 AR-PP/E/C WITH ACCESS. The SMART Digital DDC is a compact positive displacement, diaphragm dosing pump with variable-speed drive (stepper motor) and intelligent control electronics with minimum energy consumption. The SMART Digital Dosing series operates at full stroke length to ensure optimum accuracy, priming and suction, even for high-viscosity or degassing liquids. The duration of each discharge stroke varies according to the capacity set, resulting in optimum smooth and continuous discharge flow. The click-stop mounting plate allows installation in three different positions without using any additional accessories. The control cube can be turned easily into front, left or right position. The click wheel and the multi-coloured backlit graphical, plain-text LC display make commissioning and operation intuitive. The control elements are protected by a transparent cover. The dosing head is composed of: - Long lifetime and universal, chemically resistant full-PTFE diaphragm. - Double ball valves for highest dosing accuracy. - Deaeration valve for easy start-up. Operation modes: - Manual dosing in ml/h, l/h or gph. - Pulse control in ml/pulse (incl. memory function). - Analog control 0/4-20 mA. Other features: - Two SlowMode steps (anti-cavitation), 50 % (maximum flow: 4.5 l/h) and 25 % (maximum flow: 2.25 l/h), e.g. for high-viscosity or degassing liquids. - Service information display to show when service and which wear-part order number is required. - Two-step key lock function to protect the pump against unauthorised access. - Additional display function to provide further information, e.g. the actual mA input signal. - Counter for total dosed volume (resettable), operating hours and others. - Save and load customised settings as well as reload of factory settings. Signal inputs/outputs: - Input for pulse, analog 0/4-20mA, external stop. - Input for low-level and empty-tank signal. - Two potential-free output relays for max. 30 V AC/DC (configurable, e.g. alarm, stroke signal, pump dosing, etc.) Installation set includes: - Foot valve with strainer and weight (with two level switch). - Injection unit. - 6 m PE discharge hose. - 2 m PVC suction hose. - 2 m PVC deaeration hose (4/6 mm). - 5 m Control cable for all in and output signals. - 5 m Control cable for potential-free output relays. Controls: Control variant: AR Level control: YES Analog input: 0/4-20 MA

Position	Qty.	Description
		Pulse control: YES Ext. Stop input: YES Output relays: 2 Liquid: Pumped liquid: Water Liquid temperature range: -10 .. 45 °C Liquid temperature during operation: 20 °C Density: 998.2 kg/m³ Technical: Type key: DDC 9-7 AR-PP/E/C WITH ACCESS. Max. Flow: 9 l/h Max. flow in slow mode 50%: 4.5 l/h Max. flow in slow mode 25%: 2.25 l/h Min flow: 9.0 ml/h Turn-down ratio: 1:1000 Approvals on nameplate: CE,CSA-US Valve type: Standard Maximum viscosity at 100 %: 50 mPas Maximum viscosity in slow mode 50 %: 1300 mPas Maximum viscosity in slow mode 25 %: 2000 mPas Accuracy of repeatability: 1 % Materials: Dosing head: PP (Polypropylene) Valve ball: Ceramic Gasket: EPDM Installation: Range of ambient temperature: 0 .. 45 °C Maximum operating pressure: 7 bar Installation set: YES Installation type: No installation set Pump inlet: 4/6, 6/9, 6/12, 9/12 mm Pump outlet: 4/6, 6/9, 6/12, 9/12 mm Max. Suction lift during operation: 6 m Max. Suction lift during priming: 2 m Electrical data: Maximum power input - P1: 22 W Mains frequency: 50 Hz Rated voltage: 1 x 100-240 V Enclosure class (IEC 34-5): IP65 / NEMA 4X Length of cable: 1.5 m Type of cable plug: EU Inrush current: 25A at 230V for 2ms Others: Net weight: 2 kg Gross weight: 3 kg Color: RED



On request DDC 9-7 WITH ACCESS. 50 Hz



Description	Value
General information:	
Product name:	DDC 9-7 WITH ACCESS.
Product No:	On request
EAN number:	On request
Technical:	
Type key:	DDC 9-7 AR-PP/E/C WITH ACCESS.
Max. Flow:	9 l/h
Max. flow in slow mode 50%:	4.5 l/h
Max. flow in slow mode 25%:	2.25 l/h
Min flow:	9.0 ml/h
Turn-down ratio:	1:1000
Approvals on nameplate:	CE,CSA-US
Valve type:	Standard
Maximum viscosity at 100 %:	50 mPas
Maximum viscosity in slow mode 50 %:	1300 mPas
Maximum viscosity in slow mode 25 %:	2000 mPas
Accuracy of repeatability:	1 %
Materials:	
Dosing head:	PP (Polypropylene)
Valve ball:	Ceramic
Gasket:	EPDM
Installation:	
Range of ambient temperature:	0 .. 45 °C
Maximum operating pressure:	7 bar
Installation set:	YES
Installation type:	No installation set
Pump inlet:	4/6, 6/9, 6/12, 9/12 mm
Pump outlet:	4/6, 6/9, 6/12, 9/12 mm
Max. Suction lift during operation:	6 m
Max. Suction lift during priming:	2 m
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-10 .. 45 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m ³
Electrical data:	
Maximum power input - P1:	22 W
Mains frequency:	50 Hz
Rated voltage:	1 x 100-240 V
Enclosure class (IEC 34-5):	IP65 / NEMA 4X
Length of cable:	1.5 m
Type of cable plug:	EU
Inrush current:	25A at 230V for 2ms
Controls:	
Control variant:	AR
Control panel:	FRONT-MOUNTED
Level control:	YES
Analog input:	0/4-20 MA
Pulse control:	YES
Ext. Stop input:	YES
Output relays:	2
Others:	
Net weight:	2 kg
Gross weight:	3 kg
Color:	RED



On request DDC 9-7 WITH ACCESS. 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Exploded view



Sectional drawing (TM058200 for TPE2,TPE3)



TM058200

Exploded view (TM057026 for MGE model H/I)



Disclaimer: The information about the Grundfos pump in this document may be outdated.

Data may be subject to alterations without further notice.

Please contact us to verify the data above is still accurate/up-to-date.

All information is copyright Grundfos.



info@lenntech.com

<https://www.lenntech.com>

tel. +31 152 610 900

fax. +31 152 616 289