

UPS2 PH-40/60

Grundfos pump 98334567



Thank you for your interest in our products. Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/UPS200/98334567/UPS2-PH-40-60.html>



info@lenntech.com

tel. +31 152 610 900





fax. +31 152 616 289

Position	Qty.	Description
	1	UPS2 PH-40/60  Note! Product picture may differ from actual product Product No.: On request High-efficiency circulator pump with permanent-magnet motor (ECM technology) fit for the ErP directive No 641/2009 due to continuously variable speed control for circulation of clean heating water according to VDI 2035. Features and benefits: UPS2 PH-40/60 High-efficiency circulator pump with permanent-magnet motor (ECM technology) complying with the ErP directive No 641/2009 thanks to continuously variable speed control. Suitable for circulation of clean heating water according to VDI 2035. Features and benefits: • Complying with requirements of the ErP directive as from 2015. • 1 pump replaces 3 variants. • It is available as pump head without pump housing. Fits on all 4-m, 5-m and 6-m pump housings of the Series 100. • For tight installations, i.e. in boiler applications. • High energy savings thanks to an energy efficiency index (EEI) lower than 0.23. • Complies with the German regulation on energy saving in buildings and building systems – Energieeinsparverordnung – EnEV §14(3). • One button for simple selection among three proportional-pressure curves or three fixed speeds. • No corrosion issues thanks to the electrocoated pump housing. • Reduced installation costs as no external motor protection is required. Liquid: Pumped liquid: Water Liquid temperature range: 2 .. 95 °C Liquid temperature during operation: 60 °C Density: 983.2 kg/m³ Technical: TF class: 95 Approvals on nameplate: CE,VDE,WEEE Materials: Impeller: Composite, PES/PP Installation: Maximum operating pressure: 10 bar Pressure rating: PN 10 Electrical data: Power input - P1: 48 W Mains frequency: 50 Hz Rated voltage: 1 x 230 V Maximum current consumption: 0.06 .. 0.42 A Enclosure class (IEC 34-5): IP44 Insulation class (IEC 85): F



On request UPS2 PH-40/60 50 Hz



Description	Value
General information:	
Product name:	UPS2 PH-40/60
Product No:	On request
EAN number:	On request
Technical:	
Head max:	60 dm
TF class:	95
Approvals on nameplate:	CE,VDE,WEEE
Materials:	
Impeller:	Composite, PES/PP
Installation:	
Maximum operating pressure:	10 bar
Pressure rating:	PN 10
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	2 .. 95 °C
Liquid temperature during operation:	60 °C
Density:	983.2 kg/m ³
Electrical data:	
Power input - P1:	48 W
Mains frequency:	50 Hz
Rated voltage:	1 x 230 V
Maximum current consumption:	0.06 .. 0.42 A
Enclosure class (IEC 34-5):	IP44
Insulation class (IEC 85):	F
Motor protec:	NONE
Thermal protec:	ELEC
Others:	
Energy (EEI):	0.23
Designed for:	UPS2/UPS 15, 25-40/50/60
Net weight:	1.5 kg
Gross weight:	1.7 kg
Shipping volume:	0.004 m ³




On request UPS2 PH-40/60 50 Hz




Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Exploded view




Sectional drawing (TM058200 for TPE2,TPE3)



TM058200

Exploded view (TM057026 for MGE model H/I)



Disclaimer: The information about the Grundfos pump in this document may be outdated.

Data may be subject to alterations without further notice.

Please contact us to verify the data above is still accurate/up-to-date.

All information is copyright Grundfos.



info@lenntech.com

<https://www.lenntech.com>

tel. +31 152 610 900

fax. +31 152 616 289