

CRE20-01 AN-A-A-E-HQQE 3x380-500 60 HZ

Grundfos Pump 98390768



Thank you for your interest in our products

Please contact us for more information, or visit our website

<https://www.lennotech.com/grundfos/CRE20/98390768/CRE-20-1-AN-A-A-E-HQQE.html>

info@lennotech.com


tel. +31-15-261.09.00

fax. +31-15-261.62.89

Position	Qty.	Description				
	1	 Product No.: 98390768 Vertical, non-self-priming, multistage, in-line, centrifugal pump for installation in pipe systems and mounting on a foundation. The pump has the following characteristics: - Impellers and intermediate chambers are made of - The shaft seal has assembly length according to EN 12756. - Power transmission is via cast iron split coupling. The pump is fitted with an IEC-flanged three-phase MGE motor with frequency converter and PI-controller integrated in the motor terminal box. No additional motor protection is required as both motor and electronics are protected by integrated overload and temperature protection. The pump is equipped with a pressure transmitter registering pump discharge pressure and enabling controlled pump operation based on constant pressure. A control panel enables setting of required setpoint as well as setting of pump to MIN or MAX operation or to STOP. The control panel has indicator lights for "Operation" and "Fault". Communication with the pump is possible by means of Grundfos R100 Remote Control enabling further settings as well as reading out of a number of parameters such as "Actual value", "Speed", "Power input" and total "Power consumption". The terminal box holds terminals for the connection of: - Pump start/stop (potential-free contact), - external remote setpoint setting via analog signal, 0 - 5 V, 0 - 10 V, 0(4) - 20 mA, - 5 V voltage supply for setpoint potentiometer, I_{max} = 5 mA, - pressure sensor factory-fitted. - input for forced control to MIN or MAX (potential-free contact), - potential-free fault signal relay with changeover contact, reporting Fault, Operation or Ready, - RS485 GENIbus. Controls: <table><tr><td>Frequency converter:</td><td>Built-in</td></tr><tr><td>Pressure sensor:</td><td>Y</td></tr></table> Liquid:	Frequency converter:	Built-in	Pressure sensor:	Y
Frequency converter:	Built-in					
Pressure sensor:	Y					


Position	Qty.	Description
		Pumped liquid: Water Liquid temperature range: -20 .. 120 °C Liquid temperature during operation: 20 °C Density: 998.2 kg/m³ Technical: Speed for pump data: 3501 rpm Rated flow: 25.3 m³/h Rated head: 14.3 m Pump orientation: Vertical Shaft seal arrangement: Single Code for shaft seal: HQQE Approvals on nameplate: CE, EAC Curve tolerance: ISO9906:2012 3B Materials: Base: Cast iron EN 1561 EN-GJL-200 ASTM A48-25B Impeller: Stainless steel EN 1.4301 AISI 304 Bearing: SIC Installation: Maximum ambient temperature: 50 °C Maximum operating pressure: 10 bar Max pressure at stated temp: 10 bar / 120 °C 10 bar / -20 °C Type of connection: Oval / Rp Size of inlet connection: 2 inch Size of outlet connection: 2 inch Pressure rating for pipe connection: PN 10 Flange size for motor: FT115 Electrical data: Motor standard: IEC Motor type: 90LD IE Efficiency class: IE5 Rated power - P2: 2.2 kW Power (P2) required by pump: 2.2 kW Mains frequency: 50 Hz Rated voltage: 3 x 380-500 V Rated current: 4,15-3,40 A Cos phi - power factor: 0,93-0,87 Rated speed: 360-4000 rpm Efficiency: 90,1% Motor efficiency at full load: 90.1 % Enclosure class (IEC 34-5): IP55 Insulation class (IEC 85): F Others: Minimum efficiency index, MEI ≥: 0.7 Net weight: 47 kg Gross weight: 51 kg Shipping volume: 0.143 m³

98390768 CRE 20-1 50 Hz




Description	Value
Frequency converter:	Built-in
Pressure sensor:	Y
Others:	
Minimum efficiency index, MEI ≥:	0.7
Net weight:	47 kg
Gross weight:	51 kg
Shipping volume:	0.143 m ³

98390768 CRE 20-1 50 Hz




98390768 CRE 20-1 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

98390768 CRE 20-1 50 Hz



Note! All units are in [mm] unless others are stated.

*Disclaimer: The information about the Grundfos pump in this document may be outdated.
Data may be subject to alterations without further notice.
Please contact us to verify the data above is still accurate/up-to-date.*

All information is copyright Grundfos.



info@lenntech.com

www.lenntech.com

tel. +31-15-261.09.00

fax. +31-15-261.62.89