

## CME5-2 A-R-I-E-AQQE U-A-D-N

Grundfos pump 98395001



Thank you for your interest in our products. Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/CMEBASIS/98395001/CME5-2-A-R-I-E-AQQE.html>

[info@lenntech.com](mailto:info@lenntech.com)

tel. +31 152 610 900


fax. +31 152 616 289

| Position | Qty. | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|          | 1    | <p><b>CME5-2 A-R-I-E-AQQE</b></p>  <p>Product No.: On request</p> <p>Compact, reliable, horizontal, multistage, end-suction centrifugal pump with axial suction port and radial discharge port. Pump materials in contact with the liquid are in stainless steel. The mechanical shaft seal is a special designed, unbalanced O-ring seal. Pipework connection is via internal Whitworth pipe threads, Rp (ISO 7/1).</p> <p>The pump is fitted with a 1-phase, fan-cooled, permanent-magnet, synchronous motor. The motor efficiency is classified as IE5 in accordance with IEC 60034-30-2.</p> <p>The motor includes a frequency converter and PI controller in the motor terminal box. This enables continuously variable control of the motor speed, which again enables adaptation of the performance to a given requirement.</p> <p>An operating panel on the motor terminal box enables setting of required setpoint as well as setting of pump to "Min." or "Max." operation or to "Stop". The Grundfos Eye indicator on the operating panel provides visual indication of pump status:</p> <ul style="list-style-type: none"> <li>• "Power on": Motor is running (rotating green indicator lights) or not running (permanently green indicator lights)</li> <li>• "Warning": Motor is still running (rotating yellow indicator lights) or has stopped (permanently yellow indicator lights)</li> <li>• "Alarm": Motor has stopped (flashing red indicator lights).</li> </ul> <p>Communication with the pump is possible by means of Grundfos GO Remote (accessory). The remote control enables further settings as well as reading out of a number of parameters such as "Actual value", "Speed", "Power input" and total "Power consumption".</p> <p>The terminal box holds terminals for these connections:</p> <ul style="list-style-type: none"> <li>• one dedicated digital input</li> <li>• two analog inputs, 0(4)-20 mA, 0-5 V, 0-10 V, 0.5 - 3.5 V</li> <li>• 5 V voltage supply to potentiometer and sensor</li> <li>• one configurable digital input or open-collector output</li> <li>• Grundfos Digital Sensor input and output</li> <li>• 24 V voltage supply for sensors</li> <li>• two signal-relay outputs (potential-free contacts)</li> <li>• GENIbus connection</li> <li>• interface for Grundfos CIM fieldbus module.</li> </ul> <p><b>Further product details</b></p> <p>Pump and motor are integrated in a compact and user-friendly design. The pump is fitted to a low base plate, making it ideal for installation in systems where compactness is important.</p> <p>The state-of-the-art design and materials of the shaft seal ensure high wear resistance, improved sticking and dry-running capabilities and long operating life.</p> <p>Servicing the pump requires no special service tools. Service parts are in stock for quick delivery and are available as kits, single parts or bulk. Service videos are available on <a href="http://www.youtube.com">www.youtube.com</a>.</p> <p>Frequency converter operation offers these functions:</p> <ul style="list-style-type: none"> <li>- controlled operation, i.e. consumption fluctuates</li> <li>- constant pressure</li> <li>- communication with the pump.</li> </ul> <p>Adaption of performance through frequency-controlled speed offers obvious benefits such as:</p> <ul style="list-style-type: none"> <li>- energy savings</li> <li>- increased comfort</li> </ul> |




| Position | Qty. | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|----------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|          |      | <ul style="list-style-type: none"> <li>- control and monitoring of the application and pump performance.</li> </ul> <p>An operating panel on the motor terminal box enables setting of required setpoint as well as setting of pump to "Min." or "Max." operation or to "Stop". The Grundfos Eye indicator on the operating panel provides visual indication of pump status:</p> <ul style="list-style-type: none"> <li>• "Power on": Motor is running (rotating green indicator lights) or not running (permanently green indicator lights)</li> <li>• "Warning": Motor is still running (rotating yellow indicator lights) or has stopped (permanently yellow indicator lights)</li> <li>• "Alarm": Motor has stopped (flashing red indicator lights).</li> </ul> <p>Communication with the pump is possible by means of Grundfos GO Remote (accessory). The remote control enables further settings as well as reading out of a number of parameters such as "Actual value", "Speed", "Power input" and total "Power consumption".</p> <p><b>Pump</b></p> <p>A combination of a stop ring and a Nord-lock® washer secures a tight and reliable fixation of the impeller spacing pipes to the splined pump shaft. It is possible to remove and fit the hydraulic parts from the pump side. The inlet and outlet port are integrated in the pump sleeve. The inlet part, chambers and discharge part are hold together by four staybolts and a retaining flange.</p> <p>The pump is fitted with an unbalanced O-ring seal with a rigid torque-transmission system. It has a fixed seal driver ensuring a reliable rotation of all parts. The dynamic secondary seal is an O-ring.</p> <p>Primary seal:</p> <ul style="list-style-type: none"> <li>• Rotating seal ring material: silicon carbide (SiC)</li> <li>• Stationary seat material: silicon carbide (SiC)</li> </ul> <p>This material pairing is used where higher corrosion resistance is required. The high hardness of this material pairing offers good resistance against abrasive particles.</p> <p>Secondary seal material: EPDM (ethylene-propylene rubber)</p> <p>EPDM has excellent resistance to hot water. EPDM is not suitable for mineral oils.</p>  <p>The pump shaft is connected to the motor shaft through a left thread and tight fit. The shaft cannot be dismantled.</p> <p><b>Motor</b></p> <p>The motor is a totally enclosed, fan-cooled motor with principal dimensions to EN 50347. Electrical tolerances comply with EN 60034.</p> <p>The motor efficiency is classified as IE5 in accordance with IEC 60034-30-2.</p> <p>The motor requires no external motor protection. The motor control unit incorporates protection against slow- and quick-rising temperatures, e.g. constant overload and stalled conditions.</p> <p>The terminal box holds terminals for these connections:</p> <ul style="list-style-type: none"> <li>• one dedicated digital input</li> <li>• two analog inputs, 0(4)-20 mA, 0-5 V, 0-10 V, 0.5 - 3.5 V</li> <li>• 5 V voltage supply to potentiometer and sensor</li> <li>• one configurable digital input or open-collector output</li> <li>• Grundfos Digital Sensor input and output</li> <li>• 24 V voltage supply for sensors</li> <li>• two signal-relay outputs (potential-free contacts)</li> <li>• GENIbus connection</li> <li>• interface for Grundfos CIM fieldbus module.</li> </ul> <p><b>Technical data</b></p> <p><b>Liquid:</b></p> <p>Pumped liquid: Water</p> <p>Liquid temperature range: -20 .. 120 °C</p> |

| Position | Qty. | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|          |      | <p>Liquid temperature during operation: 20 °C<br/> Density: 998.2 kg/m³</p> <p><b>Technical:</b><br/> Rated flow: 5.6 m³/h<br/> Rated head: 21.4 m<br/> Primary shaft seal: AQQE<br/> Approvals on nameplate: CE,TR,CURUS,EAC<br/> Curve tolerance: ISO9906:2012 3B</p> <p><b>Materials:</b><br/> Pump housing: Stainless steel<br/> DIN W.-Nr. 1.4301<br/> AISI 304<br/> Impeller: Stainless steel<br/> DIN W.-Nr. 1.4301<br/> AISI 304<br/> Rubber: EPDM</p> <p><b>Installation:</b><br/> Maximum ambient temperature: 40 °C<br/> Maximum operating pressure: 16 bar<br/> Max pressure at stated temp: 10 bar / 120 °C<br/> 16 bar / 90 °C<br/> Flange standard: WHITWORTH THREAD RP<br/> Pump inlet: Rp 1 1/4<br/> Pump outlet: Rp 1</p> <p><b>Electrical data:</b><br/> Motor type: 80B<br/> IE Efficiency class: IE5<br/> Rated power - P2: 1.1 kW<br/> Mains frequency: 50 Hz<br/> Rated voltage: 1 x 200-240 V<br/> Rated current: 6.70-5.60 A<br/> Rated speed: 360-4000 rpm<br/> Enclosure class (IEC 34-5): IP55<br/> Insulation class (IEC 85): F</p> <p><b>Others:</b><br/> Minimum efficiency index, MEI ≥: 0.7<br/> Net weight: 14.2 kg<br/> Gross weight: 17.7 kg<br/> Danish VVS No.: 385232020</p> |


# On request CME5-2 A-R-I-E-AQQE 50 Hz




| Description                          | Value               |
|--------------------------------------|---------------------|
| <b>General information:</b>          |                     |
| Product name:                        | CME5-2 A-R-I-E-AQQE |
| Product No:                          | On request          |
| EAN number:                          | On request          |
| <b>Technical:</b>                    |                     |
| Rated flow:                          | 5.6 m³/h            |
| Rated head:                          | 21.4 m              |
| Impellers:                           | 2                   |
| Primary shaft seal:                  | AQQE                |
| Approvals on nameplate:              | CE,TR,CURUS,EAC     |
| Curve tolerance:                     | ISO9906:2012 3B     |
| Pump version:                        | A                   |
| Model:                               | A                   |
| <b>Materials:</b>                    |                     |
| Pump housing:                        | Stainless steel     |
|                                      | DIN W.-Nr. 1.4301   |
|                                      | AISI 304            |
| Impeller:                            | Stainless steel     |
|                                      | DIN W.-Nr. 1.4301   |
|                                      | AISI 304            |
| Material code:                       | I                   |
| Rubber:                              | EPDM                |
| Code for rubber:                     | E                   |
| <b>Installation:</b>                 |                     |
| Maximum ambient temperature:         | 40 °C               |
| Maximum operating pressure:          | 16 bar              |
| Max pressure at stated temp:         | 10 bar / 120 °C     |
|                                      | 16 bar / 90 °C      |
| Flange standard:                     | WHITWORTH THREAD RP |
| Pump inlet:                          | Rp 1 1/4            |
| Pump outlet:                         | Rp 1                |
| Connect code:                        | R                   |
| <b>Liquid:</b>                       |                     |
| Pumped liquid:                       | Water               |
| Liquid temperature range:            | -20 .. 120 °C       |
| Liquid temperature during operation: | 20 °C               |
| Density:                             | 998.2 kg/m³         |
| <b>Electrical data:</b>              |                     |
| Motor type:                          | 80B                 |
| IE Efficiency class:                 | IE5                 |
| Rated power - P2:                    | 1.1 kW              |
| Mains frequency:                     | 50 Hz               |
| Rated voltage:                       | 1 x 200-240 V       |
| Rated current:                       | 6.70-5.60 A         |
| Rated speed:                         | 360-4000 rpm        |
| Enclosure class (IEC 34-5):          | IP55                |
| Insulation class (IEC 85):           | F                   |
| <b>Others:</b>                       |                     |
| Minimum efficiency index, MEI ≥:     | 0.7                 |
| Net weight:                          | 14.2 kg             |
| Gross weight:                        | 17.7 kg             |
| Config. file no:                     | 98499010            |
| Danish VVS No.:                      | 385232020           |



# On request CME5-2 A-R-I-E-AQQE 50 Hz



# On request CME5-2 A-R-I-E-AQQE 50 Hz



Note! All units are in [mm] unless others are stated.  
Disclaimer: This simplified dimensional drawing does not show all details.

# Exploded view



Sectional drawing (TM058200 for TPE2,TPE3)



TM058200

# Exploded view ( TM057026 for MGE model H/I )



**Parts list CME5-2, Product No. On request**  
**Valid from 2.1.2013 (1301)**

| Pos   | Description                    | Annotation | Données de classification                                 | Référence | Quantité | Unité |
|-------|--------------------------------|------------|-----------------------------------------------------------|-----------|----------|-------|
| +     | MGE80B                         |            |                                                           |           | 1        | pcs   |
|       | Cross recess countersunk screw |            |                                                           |           | 4        | pcs   |
| - 4.d | Chamber cpl.                   |            |                                                           |           | 1        | pcs   |
|       | Chamber                        |            |                                                           |           | 1        |       |
|       | Retainer for seal ring         |            |                                                           |           | 1        |       |
|       | Guide vane                     |            |                                                           |           | 6        |       |
|       | Plate                          |            |                                                           |           | 1        |       |
|       | Vane                           |            |                                                           |           | 1        |       |
| 45    | Neck ring                      |            |                                                           |           | 1        |       |
| 65    | Neck ring retainer             |            |                                                           |           | 1        |       |
| - 4e  | Chamber cpl.                   |            |                                                           |           | 1        | pcs   |
|       | Retainer                       |            |                                                           |           | 1        |       |
|       | Intermediate chamber           |            |                                                           |           | 1        |       |
|       | Vane                           |            |                                                           |           | 1        |       |
| 45    | Neck ring                      |            |                                                           |           | 1        |       |
| 65    | Retainer                       |            |                                                           |           | 1        |       |
| 5a    | Chamber, empty                 |            |                                                           |           | 1        | pcs   |
| 6.a   | Flange                         |            |                                                           |           | 1        | pcs   |
| 16    | Collar sleeve cpl.             |            |                                                           |           | 1        | pcs   |
| - 25  | Drain plug cpl.                |            |                                                           |           | 2        | pcs   |
| 11    | O-ring                         |            | Diameter: 18,5<br>Material type: EPDM<br>Thickness: 2     |           | 1        |       |
| 25    | Plug                           |            |                                                           |           | 1        |       |
| 26    | Hex socket head cap screw      |            | Length (mm): 80<br>Thread: M8                             |           | 4        | pcs   |
| 31    | O-ring                         |            | Diameter: 114<br>Material type: EPDM<br>Thickness: 3,9    |           | 1        | pcs   |
| - 32  | Cover plate                    |            |                                                           |           | 1        | pcs   |
|       | Cover plate                    |            |                                                           |           | 1        |       |
|       | Plate                          |            |                                                           |           | 1        |       |
| 36    | Lock nut                       |            | Thread: M8                                                |           | 1        | pcs   |
| 49    | Impeller cpl.                  |            |                                                           |           | 2        | pcs   |
| 51    | Pump shaft                     |            | Diameter: D12                                             |           | 1        | pcs   |
| 64    | Spacing pipe                   |            |                                                           |           | 1        | pcs   |
| 64.c  | Clamp                          |            |                                                           |           | 1        | pcs   |
| 66    | Wedge lock washer              |            |                                                           |           | 1        | pcs   |
| 76    | Nameplate                      |            |                                                           |           | 2        | pcs   |
| - 105 | Shaft seal                     |            |                                                           |           | 1        | pcs   |
| 102   | O-ring                         |            | Diameter: 17,86<br>Material type: EPDM<br>Thickness: 2,62 |           | 1        |       |
| 103   | Seal ring, stationary          |            |                                                           |           | 1        |       |
| 104   | Seal ring, rotating            |            |                                                           |           | 1        |       |
| 107   | O-ring                         |            |                                                           |           | 1        |       |
| 108   | Compression spring             |            |                                                           |           | 1        |       |
| 111   | Retainer                       |            |                                                           |           | 1        |       |
| 112   | Driver for shaft seal          |            |                                                           |           | 1        |       |
| 111.a | Stop ring                      |            |                                                           |           | 1        | pcs   |
| 151   | Fan cover                      |            |                                                           |           | 1        | pcs   |
| 152   | Pan head thread forming screw  |            |                                                           |           | 4        | pcs   |
| 156   | Fan                            |            |                                                           |           | 1        | pcs   |

*Disclaimer: The information about the Grundfos pump in this document may be outdated.*

*Data may be subject to alterations without further notice.*

*Please contact us to verify the data above is still accurate/up-to-date.*

*All information is copyright Grundfos.*



[info@lenntech.com](mailto:info@lenntech.com)

<https://www.lenntech.com>

tel. +31 152 610 900

fax. +31 152 616 289