

## TPE2 50-60-N-A-F-A-BQQE

Grundfos Pump 98416574



**Thank you for your interest in our products**


Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/TPE00/98416574/TPE2-50-60-N-A-F-A-BQQE.html>

[info@lenntech.com](mailto:info@lenntech.com)

tel. +31-15-261.09.00

fax. +31-15-261.62.89

| Position | Qty. | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|          | 1    | <p><b>TPE2 50-60-N A-F-A-BQQE</b></p>  <p>Product No.: <a href="#">98416574</a></p> <p>Single-stage, close-coupled, volute pump with in-line suction and discharge ports of identical diameter. The pump is of the top-pull-out design, i.e. the power head (motor, pump head and impeller) can be removed for maintenance or service while the pump housing remains in the pipework.</p> <p>The shaft seal is according to EN 12756. Pipework connection is via PN 16 DIN flanges (EN 1092-2 and ISO 7005-2).</p> <p>The pump is fitted with a fan-cooled, permanent-magnet synchronous motor. The motor includes a frequency converter and PI controller in the motor terminal box. This enables continuously variable control of the motor speed, which again enables adaptation of the performance to a given requirement.</p> <p><b>Further product details</b></p> <p>A control panel on the motor terminal box enables setting of required setpoint as well as setting of pump to "Min." or "Max." operation or to "Stop". The Grundfos Eye indicator on the control panel provides visual indication of pump status:</p> <ul style="list-style-type: none"> <li>- "Power on": Motor is running (rotating green indicator lights) or not running (permanently green indicator lights)</li> <li>- "Warning": Motor is still running (rotating yellow indicator lights) or has stopped (permanently yellow indicator lights)</li> <li>- "Alarm": Motor has stopped (flashing red indicator lights).</li> </ul> <p>Communication with the pump is possible by means of the Grundfos GO Remote (accessory). The remote control enables further settings as well as reading out of a number of parameters such as "Actual value", "Speed", "Power input" and total "Power consumption".</p> <p>The product's minimum efficiency index (MEI) is greater or equal to 0.70. This is by the Commission Regulation (EU) considered as an indicative benchmark for best-performing water pump available on the market as from 1 January 2013.</p> <p><b>Pump</b></p> <p>Pump housing and pump head are electrocoated to improve the corrosion resistance. Electrocoating includes:</p> <ol style="list-style-type: none"> <li>1) Alkaline-based cleaning.</li> <li>2) Pretreatment with zinc phosphate coating.</li> <li>3) Cathodic electrocoating (epoxy).</li> <li>4) Curing of paint film at 200-250 °C.</li> </ol>  <ol style="list-style-type: none"> <li>1: Pump housing</li> <li>2: Impeller</li> <li>3: Neck ring</li> <li>4: Pump head/motor stool</li> <li>5: Stub shaft</li> </ol> |

TWINPUMP=D}The twin-head pump is designed with two parallel power-heads. A flap valve in the common discharge port is opened by the flow of the pumped liquid and prevents backflow of liquid into the idle pump head.

The pump housing is provided with a replaceable stainless steel/PTFE neck ring to reduce the amount of liquid running from the discharge side of the impeller to the suction side. The impeller is secured to the shaft with a nut.

The pump is fitted with an unbalanced rubber bellows seal with torque transmission across the spring and around the bellows. Due to the bellows, the seal does not wear the shaft, and the axial movement is not prevented by deposits on the shaft.

Primary seal:

- Rotating seal ring material: Silicon carbide (SiC)
- Stationary seat material: Silicon carbide (SiC)

This material pairing is used where higher corrosion resistance is required. The high hardness of this material pairing offers good resistance against abrasive particles.

Secondary seal material: EPDM (ethylene-propylene rubber)

EPDM has excellent resistance to hot water. EPDM is not suitable for mineral oils.

The motor stool forms connection between the pump housing and the motor, and is equipped with a manual air vent screw for venting of the pump housing and the shaft seal chamber. The sealing between motor stool and pump housing is an O-ring.

The central part of the motor stool is provided with guards for protection against the shaft and coupling. The pump stub shaft is fastened directly on the motor shaft with key and set screws.

## Motor

The motor is a totally enclosed, fan-cooled motor with principal dimensions to IEC and DIN standards. Electrical tolerances comply with IEC 60034.

The motor efficiency is classified as IE5 in accordance with IEC 60034-30-2.

The motor requires no external motor protection. The motor control unit incorporates protection against slow- and quick-rising temperatures, e.g. constant overload and stalled conditions.

The terminal box holds terminals for these connections:

- one dedicated digital input
- two analog inputs, 0(4)-20 mA, 0-5 V, 0-10 V, 0.5 - 3.5 V
- 5 V voltage supply to potentiometer and sensor
- one configurable digital input or open-collector output
- Grundfos Digital Sensor input and output
- 24 V voltage supply for sensors
- two signal relay outputs (potential-free contacts)
- GENIbus connection
- interface for Grundfos CIM fieldbus module.

## Technical data

### Liquid:

Pumped liquid: Water  
Liquid temperature range: -25 .. 120 °C  
Liquid temperature during operation: 20 °C  
Density: 998.2 kg/m<sup>3</sup>

### Technical:


Speed for pump data: 2500 rpm  
Rated flow: 16.3 m<sup>3</sup>/h  
Rated head: 3.9 m  
Actual impeller diameter: 74 mm  
Primary shaft seal: BQQE  
Curve tolerance: ISO9906:2012 3B

### Materials:



Pump housing: Cast iron  
EN-JL1040  
ASTM A48-40 B  
Impeller: Composite PES/PP 30% GF

| Position | Qty. | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|          |      | <p><b>Installation:</b></p> <p>Range of ambient temperature: -20 .. 50 °C</p> <p>Maximum operating pressure: 16 bar</p> <p>Flange standard: DIN</p> <p>Pipe connection: DN 50</p> <p>Pressure rating: PN 16</p> <p>Port-to-port length: 280 mm</p> <p>Flange size for motor: 56C</p> <p><b>Electrical data:</b></p> <p>Motor type: 71A</p> <p>IE Efficiency class: IE5</p> <p>Rated power - P2: 0.37 kW</p> <p>Mains frequency: 50 Hz</p> <p>Rated voltage: 1 x 200-240 V</p> <p>Rated current: 2,40-2,10 A</p> <p>Cos phi - power factor: 0,96</p> <p>Rated speed: 360-4000 rpm</p> <p>Efficiency: 84,0%</p> <p>Enclosure class (IEC 34-5): IP55</p> <p>Insulation class (IEC 85): F</p> <p><b>Others:</b></p> <p>Minimum efficiency index, MEI ≥: 0.7</p> <p>ErP status: EuP Standalone/Prod.</p> <p>Net weight: 24.7 kg</p> <p>Gross weight: 31.9 kg</p> <p>Shipping volume: 0.1 m³</p> |


# 98416574 TPE2 50-60-N 50 Hz



| Description                          | Value                                   |
|--------------------------------------|-----------------------------------------|
| <b>General information:</b>          |                                         |
| Product name:                        | TPE2 50-60-N A-F-A-BQQE                 |
| Product No:                          | 98416574                                |
| EAN number:                          | 5711494653201                           |
| <b>Technical:</b>                    |                                         |
| Speed for pump data:                 | 2500 rpm                                |
| Rated flow:                          | 16.3 m³/h                               |
| Rated head:                          | 3.9 m                                   |
| Head max:                            | 60 dm                                   |
| Actual impeller diameter:            | 74 mm                                   |
| Primary shaft seal:                  | BQQE                                    |
| Curve tolerance:                     | ISO9906:2012 3B                         |
| Pump version:                        | A                                       |
| Model:                               | A                                       |
| <b>Materials:</b>                    |                                         |
| Pump housing:                        | Cast iron<br>EN-JL1040<br>ASTM A48-40 B |
| Impeller:                            | Composite PES/PP 30% GF                 |
| Material code:                       | A                                       |
| <b>Installation:</b>                 |                                         |
| Range of ambient temperature:        | -20 .. 50 °C                            |
| Maximum operating pressure:          | 16 bar                                  |
| Flange standard:                     | DIN                                     |
| Connect code:                        | F                                       |
| Pipe connection:                     | DN 50                                   |
| Pressure rating:                     | PN 16                                   |
| Port-to-port length:                 | 280 mm                                  |
| Flange size for motor:               | 56C                                     |
| <b>Liquid:</b>                       |                                         |
| Pumped liquid:                       | Water                                   |
| Liquid temperature range:            | -25 .. 120 °C                           |
| Liquid temperature during operation: | 20 °C                                   |
| Density:                             | 998.2 kg/m³                             |
| <b>Electrical data:</b>              |                                         |
| Motor type:                          | 71A                                     |
| IE Efficiency class:                 | IE5                                     |
| Rated power - P2:                    | 0.37 kW                                 |
| Mains frequency:                     | 50 Hz                                   |
| Rated voltage:                       | 1 x 200-240 V                           |
| Rated current:                       | 2,40-2,10 A                             |
| Cos phi - power factor:              | 0,96                                    |
| Rated speed:                         | 360-4000 rpm                            |
| Efficiency:                          | 84,0%                                   |
| Enclosure class (IEC 34-5):          | IP55                                    |
| Insulation class (IEC 85):           | F                                       |
| Motor protec:                        | YES                                     |
| Motor No:                            | 99137991                                |
| <b>Controls:</b>                     |                                         |
| Control panel:                       | HMI200 - Standard                       |
| Function Module:                     | FM300 - Advanced                        |
| <b>Others:</b>                       |                                         |
| Minimum efficiency index, MEI ≥:     | 0.7                                     |
| ErP status:                          | EuP Standalone/Prod.                    |
| Net weight:                          | 24.7 kg                                 |
| Gross weight:                        | 31.9 kg                                 |
| Shipping volume:                     | 0.1 m³                                  |
| Config. file no:                     | 98819174                                |



# 98416574 TPE2 50-60-N 50 Hz




# 98416574 TPE2 50-60-N 50 Hz



Note! All units are in [mm] unless others are stated.  
Disclaimer: This simplified dimensional drawing does not show all details.

# 98416574 TPE2 50-60-N 50 Hz



Note! All units are in [mm] unless others are stated.

*Disclaimer: The information about the Grundfos pump in this document may be outdated.  
Data may be subject to alterations without further notice.  
Please contact us to verify the data above is still accurate/up-to-date.*

*All information is copyright Grundfos.*



[info@lenntech.com](mailto:info@lenntech.com)

[www.lenntech.com](http://www.lenntech.com)

tel. +31-15-261.09.00

fax. +31-15-261.62.89