

TPE2 100-150-N-A-F-A-BQQE

Grundfos pump 98416968




Thank you for your interest in our products. Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/TPE00/98416968/TPE2-100-150-N-A-F-A-BQQE.html>

info@lenntech.com

tel. +31 152 610 900


fax. +31 152 616 289

Position	Qty.	Description
	1	TPE2 100-150-N A-F-A-BQQE  Product No.: On request Single-stage, close-coupled, volute pump with in-line suction and discharge ports of identical diameter. The pump is of the top-pull-out design, i.e. the power head (motor, pump head and impeller) can be removed for maintenance or service while the pump housing remains in the pipework. The shaft seal is according to EN 12756. Pipework connection is via PN 16 DIN flanges (EN 1092-2 and ISO 7005-2). The pump is fitted with a fan-cooled, permanent-magnet synchronous motor. The motor efficiency is classified as IE5 in accordance with IEC 60034-30-2. The motor includes a frequency converter and PI controller in the motor terminal box. This enables continuously variable control of the motor speed, which again enables adaptation of the performance to a given requirement. Further product details An operating panel on the motor terminal box enables setting of required setpoint as well as setting of pump to "Min." or "Max." operation or to "Stop". The Grundfos Eye indicator on the operating panel provides visual indication of pump status: • "Power on": Motor is running (rotating green indicator lights) or not running (permanently green indicator lights) • "Warning": Motor is still running (rotating yellow indicator lights) or has stopped (permanently yellow indicator lights) • "Alarm": Motor has stopped (flashing red indicator lights). Communication with the pump is possible by means of Grundfos GO Remote (accessory). The remote control enables further settings as well as reading out of a number of parameters such as "Actual value", "Speed", "Power input" and total "Power consumption". The product's minimum efficiency index (MEI) is greater or equal to 0.70. This is by the Commission Regulation (EU) considered as an indicative benchmark for best-performing water pump available on the market as from 1 January 2013. Pump Pump housing and pump head are electrocoated to improve the corrosion resistance. Electrocoating includes: 1) Alkaline-based cleaning. 2) Pretreatment with zinc phosphate coating. 3) Cathodic electrocoating (epoxy). 4) Curing of paint film at 200-250 °C.  1: Pump housing 2: Impeller 3: Neck ring 4: Pump head/motor stool 5: Stub shaft




Position	Qty.	Description
		TWINPUMP=D}The twin-head pump is designed with two parallel power-heads. A flap valve in the common discharge port is opened by the flow of the pumped liquid and prevents backflow of liquid into the idle pump head. The pump housing is provided with a replaceable stainless steel/PTFE neck ring to reduce the amount of liquid running from the discharge side of the impeller to the suction side. The impeller is secured to the shaft with a nut. The pump is fitted with an unbalanced rubber bellows seal with torque transmission across the spring and around the bellows. Due to the bellows, the seal does not wear the shaft, and the axial movement is not prevented by deposits on the shaft. Primary seal: - Rotating seal ring material: silicon carbide (SiC) - Stationary seat material: silicon carbide (SiC) This material pairing is used where higher corrosion resistance is required. The high hardness of this material pairing offers good resistance against abrasive particles. Secondary seal material: EPDM (ethylene-propylene rubber) EPDM has excellent resistance to hot water. EPDM is not suitable for mineral oils. The motor stool forms connection between the pump housing and the motor, and is equipped with a manual air vent screw for venting of the pump housing and the shaft seal chamber. The sealing between motor stool and pump housing is an O-ring. The central part of the motor stool is provided with guards for protection against the shaft and coupling. The pump shaft is fastened directly on the motor shaft with key and set screws. Motor The motor is a totally enclosed, fan-cooled motor with principal dimensions to IEC and DIN standards. Electrical tolerances comply with IEC 60034. The motor efficiency is classified as IE5 in accordance with IEC 60034-30-2. The motor requires no external motor protection. The motor control unit incorporates protection against slow- and quick-rising temperatures, e.g. constant overload and stalled conditions. The terminal box holds terminals for these connections: - one dedicated digital input - two analog inputs, 0(4)-20 mA, 0-5 V, 0-10 V, 0.5 - 3.5 V 5 V voltage supply to potentiometer and sensor - one configurable digital input or open-collector output - Grundfos Digital Sensor input and output 24 V voltage supply for sensors - two signal-relay outputs (potential-free contacts) - GENIbus connection - interface for Grundfos CIM fieldbus module. Technical data Controls: Frequency converter: Built-in Liquid: Pumped liquid: Water Liquid temperature range: -25 .. 120 °C Liquid temperature during operation: 20 °C Density: 998.2 kg/m³ Technical: Rated flow: 44.4 m³/h Rated head: 9.8 m Actual impeller diameter: 90 mm Primary shaft seal: BQQE Curve tolerance: ISO9906:2012 3B Materials: Pump housing: Cast iron EN-JL1040

Position	Qty.	Description
		ASTM A48-40 B Impeller: Composite PES/PP 30% GF Installation: Range of ambient temperature: -20 .. 50 °C Maximum operating pressure: 16 bar Flange standard: DIN Pipe connection: DN 100 Pressure rating: PN 16 (@): 450 mm Flange size for motor: 56C Electrical data: Motor type: 90SC IE Efficiency class: IE5 Rated power - P2: 1.5 kW Mains frequency: 50 Hz Rated voltage: 3 x 380-500 V Rated current: 2.90-2.40 A Cos phi - power factor: 0.92-0.85 Rated speed: 360-4000 rpm Efficiency: 88.9% Motor efficiency at full load: 88.9 % Enclosure class (IEC 34-5): IP55 Insulation class (IEC 85): F Others: Minimum efficiency index, MEI ≥: 0.7 ErP status: EuP Standalone/Prod. Net weight: 41.1 kg Gross weight: 49.9 kg Shipping volume: 0.16 m³


On request TPE2 100-150-N A-F-A-BQQE 50 Hz




Description	Value
General information:	
Product name:	TPE2 100-150-N
Product No:	A-F-A-BQQE
EAN number:	On request
Technical:	
Rated flow:	44.4 m³/h
Rated head:	9.8 m
Head max:	150 dm
Actual impeller diameter:	90 mm
Primary shaft seal:	BQQE
Curve tolerance:	ISO9906:2012 3B
Pump version:	A
Model:	A
Materials:	
Pump housing:	Cast iron
	EN-JL1040
	ASTM A48-40 B
Impeller:	Composite PES/PP 30% GF
Material code:	A
Installation:	
Range of ambient temperature:	-20 .. 50 °C
Maximum operating pressure:	16 bar
Flange standard:	DIN
Pipe connection:	DN 100
Pressure rating:	PN 16
(@)	450 mm
Flange size for motor:	56C
Connect code:	F
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-25 .. 120 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	90SC
IE Efficiency class:	IE5
Rated power - P2:	1.5 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-500 V
Rated current:	2.90-2.40 A
Cos phi - power factor:	0.92-0.85
Rated speed:	360-4000 rpm
Efficiency:	88.9%
Motor efficiency at full load:	88.9 %
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Motor protec:	YES
Motor No:	99138020
Controls:	
Control panel:	HMI200 - Standard
Function Module:	FM300 - Advanced
Frequency converter:	Built-in
Others:	
Minimum efficiency index, MEI ≥:	0.7
ErP status:	EuP Standalone/Prod.
Net weight:	41.1 kg
Gross weight:	49.9 kg
Shipping volume:	0.16 m³
Config. file no:	98819281



On request TPE2 100-150-N A-F-A-BQQE 50 Hz



On request TPE2 100-150-N A-F-A-BQQE 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Exploded view



Sectional drawing (TM058200 for TPE2,TPE3)



TM058200

Exploded view (TM057026 for MGE model H/I)



Parts list TPE2 100-150-N, Product No. On request
Valid from 25.12.2012 (1252)

Pos	Description	Annotation	Données de classification	Référence	Quantité	Unité
-	Motor				1	pcs
	Terminal				3	
	Pan head thread forming screw				4	
150	Stator housing				1	
150	Stator				1	
151	Fan cover				1	
152	Pan head thread forming screw				6	
152	Pan head thread forming screw				1	
152	Pan head thread forming screw				1	
152	Pan head thread forming screw				4	
153	Ball bearing				1	
154	Ball bearing		Designation: 6204.2Z.C3.SYN		1	
156	Fan				1	
156b	Flange				1	
156d	Gasket		Internal diameter: 114,80		1	
			Outer diameter: 121,20			
			Thickness: 0,25			
157	O-ring		Diameter: 47		1	
			Material type: NBR			
			Thickness: 3			
158	Waved washer				1	
159a	Seal ring				1	
159c	Seal ring				1	
166	Torx Screw				2	
172	Shaft w/rotor				1	
172a	Parallel key				1	
173a	Base				1	
185	Cross recess Pan head screw				4	
186	Drain plug				1	
187	Retaining ring				1	
188	Retaining ring				1	
203	Terminal plug				1	
251a	Control box				1	
251b	Control box				1	
251d	Pan head thread forming screw				4	
266	Connector plug 3-pole				1	
266	Connector plug 3-pole				1	
266	Connector plug 8-pole				1	
266	Connector plug 8-pole				1	
266	Connector plug 10-pole				1	
268	Pan head screw				1	
273	Funct. Module cpl.				1	
275a	Pin				1	
277	Isolation cover				1	
277a	Cross recess Pan head screw				1	
277a	Cross recess Pan head screw				4	
277a	Cross recess Pan head screw				1	
286	Spacer				1	
286	Spacer				1	
287	Cover				1	
288	Wire clamp				3	
288b	Washer				6	
289	Wire clamp				1	
290	Control panel, cpl.				1	
300	Plug cpl.				4	
301	Jumper				1	
-	Guard				2	pcs
7	Guard				1	
7a	Pan head screw				2	

Pos	Description	Annotation	Données de classification	Référence	Quantité	Unité
66	Lock washer				2	
-	Motor stool cpl.				1	pcs
17	Air vent screw				1	
28	Hex head cap screw		Length (mm): 25		4	
			Thread: UNC 3/8"			
77	Motor stool				1	
-	Pump housing cpl.				1	pcs
6	Pump housing				1	
45	Neck ring cpl.				1	
-	Shaft cpl.				1	pcs
9	Socket set screw				3	
11b	Key				1	
51	Shaft				1	
66a	Wedge lock washer				1	
67	Lock nut		Thread: M8		1	
- 49	Impeller cpl.				1	pcs
	Impeller cpl.				1	
100	Spacer ring				1	pcs
105	Shaft seal				1	pcs

Disclaimer: The information about the Grundfos pump in this document may be outdated.

Data may be subject to alterations without further notice.

Please contact us to verify the data above is still accurate/up-to-date.

All information is copyright Grundfos.



info@lenntech.com

<https://www.lenntech.com>

tel. +31 152 610 900

fax. +31 152 616 289