

NK100-250/274 EUPA2F2AE-SBAQE

Grundfos Pump 98745966



Thank you for your interest in our products


Please contact us for more information, or visit our website

<https://www.lenntech.com/grundfos/NKBASIS/98745966/NK-100-250-274-EUP-A2-F-A-E-BAQE.html>

info@lenntech.com

tel. +31-15-261.09.00

fax. +31-15-261.62.89

Position	Qty.	Description
	1	NK 100-250/274 EUP A2-F-A-E-BAQE  Product No.: 98745966 Non-self-priming, single-stage, centrifugal volute pump designed according to ISO 5199 with dimensions and rated performance according to EN 733. Flanges are PN 16 with dimensions according to EN 1092-2. The pump has an axial suction port, a radial discharge port and horizontal shaft. It is of the back pull-out design enabling removal of the coupling, bearing bracket and impeller without disturbing the motor, pump housing or pipework. The unbalanced rubber bellows seal is according to DIN EN 12756. The pump is fitted with a foot-mounted, fan-cooled asynchronous motor. Pump and motor are mounted on a common base frame. Further product details The product's minimum efficiency index (MEI) is greater or equal to 0.70. This is by the Commission Regulation (EU) considered as an indicative benchmark for best-performing water pump available on the market as from 1 January 2013. Pump and motor are mounted on a common steel base frame in accordance with ISO 3661. The back pull-out design together with a spacer coupling makes it possible to make service on the pump without dismantling the pump housing and motor from the base frame. This saves realignment of pump and motor after service. 1) Remove coupling. 2) Remove the bolts in the bearing bracket support foot. 3) Remove the bearing bracket from the pump housing.  Cast-iron parts have an epoxy-based coating made in a cathodic electro-deposition (CED) process. CED is a high-quality dip-painting process where an electrical field around the products ensures deposition of paint particles as a thin, well-controlled layer on the surface. An integral part of the process is a pretreatment. The entire process consists of these elements: 1) Alkaline-based cleaning. 2) Zinc phosphating. 3) Cathodic electro-deposition. 4) Curing to a dry film thickness 18-22 my m. The colour code for the finished product is NCS 9000/RAL 9005. Pump The pump housing has both a priming and a drain hole closed by plugs. The impeller is a closed impeller with double-curved blades with smooth surfaces. The impeller is statically balanced according to ISO 1940-1 class G6.3 and hydraulically balanced to compensate for axial thrust. Wear rings used in pump housing and for impeller are made of bronze/brass or cast iron. The pump is fitted with an unbalanced rubber bellows seal with torque transmission across the spring and around the bellows. Due to the bellows, the seal does not wear the shaft, and the axial movement is not prevented by deposits on the shaft. Primary seal: - Rotating seal ring material: Carbon graphite, metal-impregnated - Stationary seat material: Silicon carbide (SiC)

This material pairing has a very good corrosion resistance and is especially suitable for water up to +120 °C. However, seal life will be reduced at temperatures above +90 °C. The material pairing is not recommended for liquids containing particles as this will result in heavy wear on the SiC face.

Secondary seal material: EPDM (ethylene-propylene rubber)

EPDM has excellent resistance to hot water. EPDM is not suitable for mineral oils.

The shaft is made of stainless steel and has a diameter of 32 mm where the coupling is mounted.

The pump uses a spacer coupling between the pump and motor shaft.



Motor

The motor is a totally enclosed, fan-cooled motor with principal dimensions to IEC and DIN standards and mounting designation B3 (IM 1001). Electrical tolerances comply with IEC 60034.

The motor efficiency is classified as IE3 in accordance with IEC 60034-30.

The motor has thermistors (PTC sensors) in the windings in accordance with DIN 44081/DIN 44082. The protection reacts to both slow- and quick-rising temperatures, e.g. constant overload and stalled conditions.

Thermal switches must be connected to an external control circuit in a way which ensures that the automatic reset cannot cause accidents. The motors must be connected to a motor-protective circuit breaker according to local regulations.

A variable speed drive makes adjustment of pump performance to any duty point possible. If the motor is to be connected to a variable speed drive, the pump should be ordered with an electrically insulated motor bearing.

Technical data

Liquid:

Pumped liquid:	Water
Liquid temperature range:	0 .. 120 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m ³

Technical:

Speed for pump data:	2980 rpm
Rated flow:	345 m ³ /h
Rated head:	92 m
Actual impeller diameter:	274 EUP mm
Impeller nom:	250 mm
Primary shaft seal:	BAQE
Secondary shaft seal:	NONE
Curve tolerance:	ISO9906:2012 3B

Materials:


Pump housing:	Cast iron EN-GJL-250 ASTM A48-40 B
Impeller:	Cast iron EN-GJL-200 ASTM A48-30 B
Rubber:	EPDM
Wear ring mat.:	High alloy brass(CuZn34Mn3Al2

Installation:



Maximum ambient temperature:	55 °C
Maximum operating pressure:	16 bar
Flange standard:	EN 1092-2
Pump inlet:	DN 125

Position	Qty.	Description
		Pump outlet: DN 100 Pressure rating: PN 16 Coupling type: Spacer Base frame: C - Channel Electrical data: Motor type: SIEMENS IE Efficiency class: IE3 Rated power - P2: 132 kW Mains frequency: 50 Hz Rated voltage: 3 x 380-420D/660-725Y V Rated current: 230-210/134-122 A Starting current: 720-720 % Cos phi - power factor: 0,91 Rated speed: 2980 rpm Efficiency: IE3 95,4% Motor efficiency at full load: 95.4-95.4 % Motor efficiency at 3/4 load: 95.6-95.6 % Motor efficiency at 1/2 load: 95.2-95.2 % Number of poles: 2 Enclosure class (IEC 34-5): 55 Dust/Jetting Insulation class (IEC 85): F Lubricant type: Grease Others: Minimum efficiency index, MEI ≥: 0.70 ErP status: EuP Standalone/Prod. Net weight: 1230 kg Gross weight: 1330 kg Shipping volume: 3.76 m³

98745966 NK 100-250/274 EUP 50 Hz





Description	Value
General information:	
Product name:	NK 100-250/274 EUP
Product No:	A2-F-A-E-BAQE
EAN number:	98745966
EAN number:	5712600847682
Technical:	
Speed for pump data:	2980 rpm
Rated flow:	345 m³/h
Rated head:	92 m
Actual impeller diameter:	274 EUP mm
Impeller nom:	250 mm
Primary shaft seal:	BAQE
Secondary shaft seal:	NONE
Shaft diameter:	32 mm
Curve tolerance:	ISO9906:2012 3B
Pump version:	A2
Materials:	
Pump housing:	Cast iron
	EN-GJL-250
	ASTM A48-40 B
Impeller:	Cast iron
	EN-GJL-200
	ASTM A48-30 B
Material code:	A
Rubber:	EPDM
Code for rubber:	E
Wear ring mat.:	High alloy brass(CuZn34Mn3Al2
Installation:	
Maximum ambient temperature:	55 °C
Maximum operating pressure:	16 bar
Flange standard:	EN 1092-2
Connect code:	F
Pump inlet:	DN 125
Pump outlet:	DN 100
Pressure rating:	PN 16
Coupling type:	Spacer
Wear ring(s):	neckring(s)
Base frame:	C - Channel
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	0 .. 120 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	SIEMENS
IE Efficiency class:	IE3
Rated power - P2:	132 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-420D/660-725Y V
Rated current:	230-210/134-122 A
Starting current:	720-720 %
Cos phi - power factor:	0,91
Rated speed:	2980 rpm
Efficiency:	IE3 95,4%
Motor efficiency at full load:	95.4-95.4 %
Motor efficiency at 3/4 load:	95.6-95.6 %
Motor efficiency at 1/2 load:	95.2-95.2 %
Number of poles:	2
Enclosure class (IEC 34-5):	55 Dust/Jetting
Insulation class (IEC 85):	F
Motor protec:	PTC
Motor No:	98943383
Lubricant type:	Grease



Description	Value
Others:	
Minimum efficiency index, MEI ≥:	0.70
ErP status:	EuP Standalone/Prod.
Net weight:	1230 kg
Gross weight:	1330 kg
Shipping volume:	3.76 m ³

98745966 NK 100-250/274 EUP 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

98745966 NK 100-250/274 EUP 50 Hz



IEC TP211 THERMALLY PROTECTED WHEN THE THERMISTORS ARE
CONNECTED TO AMPLIFIER RELAY FOR CONTROL OF MAIN SUPPLY
THERMISTORS PTC ACCORDING TO DIN 44082

Note! All units are in [mm] unless others are stated.

*Disclaimer: The information about the Grundfos pump in this document may be outdated.
Data may be subject to alterations without further notice.
Please contact us to verify the data above is still accurate/up-to-date.*

All information is copyright Grundfos.



info@lenntech.com

www.lenntech.com

tel. +31-15-261.09.00

fax. +31-15-261.62.89