

## CRE15-03 A-A-A-E-HQQE 3x380-500 60 HZ

Grundfos pump 99071512



Thank you for your interest in our products. Please contact us for more information, or visit our website




<https://www.lenntech.com/grundfos/CRE15/99071512/CRE-15-3-A-A-A-E-HQQE.html>


[info@lenntech.com](mailto:info@lenntech.com)

tel. +31 152 610 900

fax. +31 152 616 289

| Position | Qty. | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|          | 1    | <p><b>CRE 15-3 A-A-A-E-HQQE</b></p>  <p>Product No.: On request</p> <p>Vertical, multistage centrifugal pump with inlet and outlet ports on same the level (inline). The pump head and base are in cast iron – all other wetted parts are in stainless steel. A cartridge shaft seal ensures high reliability, safe handling, and easy access and service. Power transmission is via a rigid split coupling. Pipe connection is via oval flanges with internal Rp threads.</p> <p>The pump is fitted with a 3-phase, fan-cooled, permanent-magnet, synchronous motor. The motor efficiency is classified as IE5 in accordance with IEC 60034-30-2.</p> <p>The motor includes a frequency converter and PI controller in the motor terminal box. This enables continuously variable control of the motor speed, which again enables adaptation of the performance to a given requirement. An operating panel on the motor terminal box enables setting of required setpoint as well as setting of pump to "Min." or "Max." operation or to "Stop". The Grundfos Eye indicator on the operating panel provides visual indication of pump status:</p> <ul style="list-style-type: none"> <li>• "Power on": Motor is running (rotating green indicator lights) or not running (permanently green indicator lights)</li> <li>• "Warning": Motor is still running (rotating yellow indicator lights) or has stopped (permanently yellow indicator lights)</li> <li>• "Alarm": Motor has stopped (flashing red indicator lights).</li> </ul> <p>Communication with the pump is possible by means of Grundfos GO Remote (accessory). The remote control enables further settings as well as reading out of a number of parameters such as "Actual value", "Speed", "Power input" and total "Power consumption".</p> <p>The terminal box has a number of inputs and outputs enabling the motor to be used in advanced applications where many inputs and outputs are required:</p> <ul style="list-style-type: none"> <li>• two dedicated digital inputs</li> <li>• three analog inputs, 0(4)-20 mA, 0-5 V, 0-10 V, 0.5 - 3.5 V</li> <li>• 5 V voltage supply to potentiometer and sensor</li> <li>• one analog output, 0-10 V, 0(4)-20 mA</li> <li>• two configurable digital inputs or open-collector outputs</li> <li>• two Pt100/Pt1000 inputs</li> <li>• LiqTec, dry-running protection sensor input</li> <li>• Grundfos Digital Sensor input and output</li> <li>• 24 V voltage supply for sensors</li> <li>• two signal-relay outputs (potential-free contacts)</li> <li>• GENIbus connection</li> <li>• interface for Grundfos CIM fieldbus module.</li> </ul> <p><b>Further product details</b></p> <p>An external sensor can be connected if controlled pump operation based on for example flow, differential pressure or temperature is required.</p> <p>An operating panel on the motor terminal box enables setting of required setpoint as well as setting of pump to "Min." or "Max." operation or to "Stop". The Grundfos Eye indicator on the operating panel provides visual indication of pump status:</p> <ul style="list-style-type: none"> <li>• "Power on": Motor is running (rotating green indicator lights) or not running (permanently green indicator lights)</li> <li>• "Warning": Motor is still running (rotating yellow indicator lights) or has stopped (permanently yellow indicator lights)</li> <li>• "Alarm": Motor has stopped (flashing red indicator lights).</li> </ul> <p>Communication with the pump is possible by means of Grundfos GO Remote (accessory). The remote control enables further settings as well as reading out of a number of parameters such as "Actual value", "Speed", "Power input" and total "Power consumption".</p> |

| Position | Qty. | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|          |      | <p>Steel, cast iron and aluminium components have an epoxy-based coating made in a cathodic electro-deposition (CED) process. CED is a high-quality dip-painting process where an electrical field around the products ensures deposition of paint particles as a thin, well-controlled layer on the surface. An integral part of the process is a pretreatment. The entire process consists of these elements:</p> <ol style="list-style-type: none"> <li>1) Alkaline-based cleaning.</li> <li>2) Zinc phosphating.</li> <li>3) Cathodic electro-deposition.</li> <li>4) Curing to a dry film thickness 18-22 my m.</li> </ol> <p>The colour code for the finished product is NCS 9000/RAL 9005.</p> <p><b>Pump</b></p> <p>A standard split coupling connects the pump and motor shaft. It is enclosed in the pump head/motor stool by means of two coupling guards.</p>  <p>The pump head, pump head cover and flange for motor mounting is made in one piece. The pump head has a combined 1/2" priming plug and vent screw.</p>  <p>The pump is fitted with a balanced O-ring seal unit with a rigid torque-transmission system. This seal type is assembled in a cartridge unit which makes replacement safe and easy. Due to the balancing, this seal type is suitable for high-pressure applications. The cartridge construction also protects the pump shaft from possible wear from a dynamic O-ring between pump shaft and shaft seal.</p> <p>Primary seal:</p> <ul style="list-style-type: none"> <li>• Rotating seal ring material: silicon carbide (SiC)</li> <li>• Stationary seat material: silicon carbide (SiC)</li> </ul> <p>This material pairing is used where higher corrosion resistance is required. The high hardness of this material pairing offers good resistance against abrasive particles.</p> <p>Secondary seal material: EPDM (ethylene-propylene rubber)</p> <p>EPDM has excellent resistance to hot water. EPDM is not suitable for mineral oils.</p>  <p>The shaft seal is screwed into the pump head.</p> <p>The chambers and impellers are made of stainless-steel sheet. The chambers are provided with a PTFE neck ring offering improved sealing and high efficiency. The impellers have smooth surfaces, and the shape of the blades ensure a high efficiency.</p> <p>The base is made of cast iron. The oval flanges are bolted to the base. The outlet side of the base has a drain plug. The pump is secured to the foundation by four bolts through the base plate.</p> |



## Motor

The motor is a totally enclosed, fan-cooled motor with principal dimensions to IEC and DIN standards. The motor is flange-mounted with tapped-hole flange (FT).

Motor-mounting designation in accordance with IEC 60034-7: IM B 14 (Code I) / IM 3601 (Code II).

Electrical tolerances comply with IEC 60034.

The motor efficiency is classified as IE5 in accordance with IEC 60034-30-2.

The motor requires no external motor protection. The motor control unit incorporates protection against slow- and quick-rising temperatures, e.g. constant overload and stalled conditions.

The terminal box has a number of inputs and outputs enabling the motor to be used in advanced applications where many inputs and outputs are required:

- two dedicated digital inputs
- three analog inputs, 0(4)-20 mA, 0-5 V, 0-10 V, 0.5 - 3.5 V
- 5 V voltage supply to potentiometer and sensor
- one analog output, 0-10 V, 0(4)-20 mA
- two configurable digital inputs or open-collector outputs
- two Pt100/Pt1000 inputs
- LiqTec, dry-running protection sensor input
- Grundfos Digital Sensor input and output
- 24 V voltage supply for sensors
- two signal-relay outputs (potential-free contacts)
- GENIbus connection
- interface for Grundfos CIM fieldbus module.

## Technical data

### Controls:

|                      |          |
|----------------------|----------|
| Frequency converter: | Built-in |
| Pressure sensor:     | N        |

### Liquid:

|                                      |                         |
|--------------------------------------|-------------------------|
| Pumped liquid:                       | Water                   |
| Liquid temperature range:            | -20 .. 120 °C           |
| Liquid temperature during operation: | 20 °C                   |
| Density:                             | 998.2 kg/m <sup>3</sup> |

### Technical:

|                         |                        |
|-------------------------|------------------------|
| Rated flow:             | 20.5 m <sup>3</sup> /h |
| Rated head:             | 47.9 m                 |
| Pump orientation:       | Vertical               |
| Shaft seal arrangement: | Single                 |
| Code for shaft seal:    | HQQE                   |
| Approvals on nameplate: | CE, EAC, ACS           |
| Curve tolerance:        | ISO9906:2012 3B        |

### Materials:


|           |                                                 |
|-----------|-------------------------------------------------|
| Base:     | Cast iron<br>EN 1561 EN-GJL-200<br>ASTM A48-25B |
| Impeller: | Stainless steel<br>EN 1.4301                    |
| Bearing:  | AISI 304<br>SIC                                 |

### Installation:




|                              |        |
|------------------------------|--------|
| Maximum ambient temperature: | 50 °C  |
| Maximum operating pressure:  | 10 bar |

| Position | Qty. | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|----------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|          |      | <p>Max pressure at stated temp: 10 bar / 120 °C<br/>10 bar / -20 °C</p> <p>Type of connection: Oval / Rp</p> <p>Size of inlet connection: 2 inch</p> <p>Size of outlet connection: 2 inch</p> <p>Pressure rating for pipe connection: PN 10</p> <p>Flange size for motor: FT130</p> <p><b>Electrical data:</b></p> <p>Motor standard: IEC</p> <p>Motor type: 112MC</p> <p>IE Efficiency class: IE5</p> <p>Rated power - P2: 4 kW</p> <p>Power (P2) required by pump: 4 kW</p> <p>Mains frequency: 50 Hz</p> <p>Rated voltage: 3 x 380-500 V</p> <p>Rated current: 7.60-6.20 A</p> <p>Cos phi - power factor: 0.92-0.87</p> <p>Rated speed: 360-4000 rpm</p> <p>Efficiency: 92.2%</p> <p>Motor efficiency at full load: 92.2 %</p> <p>Enclosure class (IEC 34-5): IP55</p> <p>Insulation class (IEC 85): F</p> <p><b>Others:</b></p> <p>Minimum efficiency index, MEI ≥: 0.70</p> <p>Net weight: 61 kg</p> <p>Gross weight: 83 kg</p> <p>Shipping volume: 0.234 m³</p> |

# On request CRE 15-3 A-A-A-E-HQQE 50 Hz




| Description                           | Value                 |
|---------------------------------------|-----------------------|
| <b>General information:</b>           |                       |
| Product name:                         | CRE 15-3 A-A-A-E-HQQE |
| Product No:                           | On request            |
| EAN number:                           | On request            |
| <b>Technical:</b>                     |                       |
| Rated flow:                           | 20.5 m³/h             |
| Rated head:                           | 47.9 m                |
| Stages:                               | 3                     |
| Impellers:                            | 3                     |
| Number of reduced-diameter impellers: | 0                     |
| Low NPSH:                             | N                     |
| Pump orientation:                     | Vertical              |
| Shaft seal arrangement:               | Single                |
| Code for shaft seal:                  | HQQE                  |
| Approvals on nameplate:               | CE, EAC, ACS          |
| Curve tolerance:                      | ISO9906:2012 3B       |
| Pump version:                         | A                     |
| Model:                                | A                     |
| <b>Materials:</b>                     |                       |
| Base:                                 | Cast iron             |
|                                       | EN 1561 EN-GJL-200    |
|                                       | ASTM A48-25B          |
| Impeller:                             | Stainless steel       |
|                                       | EN 1.4301             |
|                                       | AISI 304              |
| Material code:                        | A                     |
| Code for rubber:                      | E                     |
| Bearing:                              | SIC                   |
| <b>Installation:</b>                  |                       |
| Maximum ambient temperature:          | 50 °C                 |
| Maximum operating pressure:           | 10 bar                |
| Max pressure at stated temp:          | 10 bar / 120 °C       |
|                                       | 10 bar / -20 °C       |
| Type of connection:                   | Oval / Rp             |
| Size of inlet connection:             | 2 inch                |
| Size of outlet connection:            | 2 inch                |
| Pressure rating for pipe connection:  | PN 10                 |
| Flange size for motor:                | FT130                 |
| Connect code:                         | A                     |
| <b>Liquid:</b>                        |                       |
| Pumped liquid:                        | Water                 |
| Liquid temperature range:             | -20 .. 120 °C         |
| Liquid temperature during operation:  | 20 °C                 |
| Density:                              | 998.2 kg/m³           |
| <b>Electrical data:</b>               |                       |
| Motor standard:                       | IEC                   |
| Motor type:                           | 112MC                 |
| IE Efficiency class:                  | IE5                   |
| Rated power - P2:                     | 4 kW                  |
| Power (P2) required by pump:          | 4 kW                  |
| Mains frequency:                      | 50 Hz                 |
| Rated voltage:                        | 3 x 380-500 V         |
| Rated current:                        | 7.60-6.20 A           |
| Cos phi - power factor:               | 0.92-0.87             |
| Rated speed:                          | 360-4000 rpm          |
| Efficiency:                           | 92.2%                 |
| Motor efficiency at full load:        | 92.2 %                |
| Enclosure class (IEC 34-5):           | IP55                  |
| Insulation class (IEC 85):            | F                     |
| Motor protec:                         | YES                   |
| Motor No:                             | 98971050              |
| <b>Controls:</b>                      |                       |
| Control panel:                        | Standard              |




| Description                      | Value                |
|----------------------------------|----------------------|
| Function Module:                 | FM300 - Advanced     |
| Frequency converter:             | Built-in             |
| Pressure sensor:                 | N                    |
| <b>Others:</b>                   |                      |
| Minimum efficiency index, MEI ≥: | 0.70                 |
| Net weight:                      | 61 kg                |
| Gross weight:                    | 83 kg                |
| Shipping volume:                 | 0.234 m <sup>3</sup> |



# On request CRE 15-3 A-A-A-E-HQQE 50 Hz




# On request CRE 15-3 A-A-A-E-HQQE 50 Hz




Note! All units are in [mm] unless others are stated.  
 Disclaimer: This simplified dimensional drawing does not show all details.

# Exploded view




Sectional drawing (TM058200 for TPE2,TPE3)



TM058200

# Exploded view ( TM057026 for MGE model H/I )



**Parts list CRE 15-3, Product No. On request**  
**Valid from 1.1.2004 (0401)**

| Pos  | Description                  | Annotation | Données de classification                                                             | Référence | Quantité | Unité |
|------|------------------------------|------------|---------------------------------------------------------------------------------------|-----------|----------|-------|
| +    | Motor                        |            |                                                                                       |           | 1        | pcs   |
| -    | Base cpl.                    |            |                                                                                       |           | 1        | pcs   |
| 6    | Base                         |            |                                                                                       |           | 1        |       |
| 12   | Flange                       |            |                                                                                       |           | 2        |       |
| 25   | Drain plug                   |            |                                                                                       |           | 1        |       |
| 35   | Hex head screw               |            |                                                                                       |           | 4        |       |
| -    | Rubber module                |            |                                                                                       |           | 1        | pcs   |
| 20   | Spring                       |            |                                                                                       |           | 4        |       |
| 37   | O-ring                       |            |                                                                                       |           | 2        |       |
| 38a  | O-ring                       |            | Diameter: 5,3<br>Material type: EPDM<br>Thickness: 2,4                                |           | 1        |       |
| 100  | O-ring                       |            | Diameter: 16,3<br>Material type: EPDM<br>Thickness: 2,4                               |           | 3        |       |
| - 2  | Pump head cpl.               |            |                                                                                       |           | 1        | pcs   |
| 2    | Pump head                    |            |                                                                                       |           | 1        |       |
| 7    | Coupling guard               |            |                                                                                       |           | 2        |       |
| 7.a  | Combi Slot Torx screw        |            |                                                                                       |           | 4        |       |
| - 18 | Air vent screw               |            |                                                                                       |           | 1        |       |
|      | Plug                         |            |                                                                                       |           | 1        |       |
|      | Spindle                      |            |                                                                                       |           | 1        |       |
| 23   | Plug                         |            |                                                                                       |           | 1        |       |
| 28   | Hex head screw               |            | Length (mm): 25<br>Thread: M8                                                         |           | 4        |       |
| 76   | Nameplate                    |            |                                                                                       |           | 1        |       |
| 76a  | Rivet                        |            |                                                                                       |           | 1        |       |
| - 8  | Coupling cpl.                |            |                                                                                       |           | 1        | pcs   |
| 9    | Hex socket head cap screw    |            | Designation: DIN 912<br>Length (mm): 25<br>Thread: M8                                 |           | 4        |       |
| 10   | Shaft pin                    |            | Diameter: 5<br>Length (mm): 26                                                        |           | 1        |       |
| 10a  | Coupling half                |            |                                                                                       |           | 2        |       |
| 26   | Staybolt                     |            |                                                                                       |           | 4        | pcs   |
| 36   | Hex nut                      |            | Thread: M16                                                                           |           | 4        | pcs   |
| 55   | Outer sleeve                 |            |                                                                                       |           | 1        | pcs   |
| 66a  | Washer                       |            | Designation: DIN 125 A<br>Internal diameter: 17<br>Outer diameter: 30<br>Thickness: 3 |           | 4        | pcs   |
| - 80 | Chamber stack                |            |                                                                                       |           | 1        | pcs   |
| - 4  | Intermediate chamber cpl.    |            |                                                                                       |           | 1        |       |
| 45   | Neck ring cpl.               |            |                                                                                       |           | 1        |       |
| 65   | Retainer for upper seal ring |            |                                                                                       |           | 1        |       |
| - 4  | Intermediate chamber cpl.    |            |                                                                                       |           | 1        |       |
|      | Guide vane                   |            |                                                                                       |           | 10       |       |
|      | Front plate                  |            |                                                                                       |           | 1        |       |
| 3    | Top intermediate chamber     |            |                                                                                       |           | 1        |       |
| - 4a | Intermediate chamber cpl.    |            |                                                                                       |           | 1        |       |
|      | Bearing plate                |            |                                                                                       |           | 1        |       |
|      | Bearing bush                 |            |                                                                                       |           | 1        |       |
| 3a   | Intermediate chamber         |            |                                                                                       |           | 1        |       |
| 45   | Neck ring cpl.               |            |                                                                                       |           | 1        |       |
| 65   | Retainer for upper seal ring |            |                                                                                       |           | 1        |       |
| 26.b | Hex head screw               |            |                                                                                       |           | 2        |       |
| 26.c | Washer                       |            | Designation: DIN 125A<br>Thickness: 1,6                                               |           | 2        |       |
| 26a  | Strap cpl.                   |            |                                                                                       |           | 2        |       |

| Pos   | Description                  | Annotation | Données de classification | Référence | Quantité | Unité |
|-------|------------------------------|------------|---------------------------|-----------|----------|-------|
| 36    | Lock nut                     |            | Thread: M8                |           | 1        |       |
| - 44a | Inlet part cpl.              |            |                           |           | 1        |       |
| 45    | Neck ring cpl.               |            |                           |           | 1        |       |
| 65    | Retainer for upper seal ring |            |                           |           | 1        |       |
| 47a   | Bearing ring                 |            |                           |           | 1        |       |
| + 49  | Impeller cpl.                |            |                           |           | 3        |       |
| - 51  | Shaft, spline, cpl.          |            |                           |           | 1        |       |
|       | Bar                          |            |                           |           | 0        |       |
| 62    | Stop ring                    |            |                           |           | 1        |       |
| 64b   | Spacing bush                 |            |                           |           | 1        |       |
| 64c   | Spacing pipe                 |            | Length (mm): 12.7         |           | 1        |       |
| 66    | Wedge lock washer            |            |                           |           | 1        |       |
| 69    | Spacing pipe                 |            | Length (mm): 43.6         |           | 1        |       |
| 69    | Spacing pipe                 |            | Internal diameter: 17,5   |           | 1        |       |
|       |                              |            | Length (mm): 17           |           |          |       |
| 69    | Spacing bush                 |            |                           |           | 1        |       |
| 105   | Shaft seal                   |            | Material type: HQQE       |           | 1        | pcs   |

*Disclaimer: The information about the Grundfos pump in this document may be outdated.*

*Data may be subject to alterations without further notice.*

*Please contact us to verify the data above is still accurate/up-to-date.*

*All information is copyright Grundfos.*



[info@lenntech.com](mailto:info@lenntech.com)

<https://www.lenntech.com>

tel. +31 152 610 900

fax. +31 152 616 289