

NKE100-200/178A2F2AE-SBQQE

Grundfos pump 99105875




Thank you for your interest in our products. Please contact us for more information, or visit our website


<https://www.lenntech.com/grundfos/NKEBASIS/99105875/NKE-100-200-178-A2-F-A-E-BQQE.html>

info@lenntech.com

tel. +31 152 610 900


fax. +31 152 616 289

Position	Qty.	Description
	1	NKE 100-200/178 A2-F-A-E-BQQE  Product No.: On request The pump has an axial suction port, a radial discharge port and horizontal shaft. It is of the back pull-out design enabling removal of the coupling, bearing bracket and impeller without disturbing the motor, pump housing or pipework. The unbalanced rubber bellows seal is according to DIN EN 12756. The pump is fitted with a foot-mounted, fan-cooled, permanent-magnet synchronous motor. Pump and motor are mounted on a common base frame. The motor includes a frequency converter and PI controller in the motor terminal box. This enables continuously variable control of the motor speed, which again enables adaptation of the performance to a given requirement. Further product details An external sensor can be connected if controlled pump operation is required for flow, differential pressure or temperature control. An operating panel on the motor terminal box enables setting of required setpoint as well as setting of pump to "Min." or "Max." operation or to "Stop". The Grundfos Eye indicator on the operating panel provides visual indication of pump status: • "Power on": Motor is running (rotating green indicator lights) or not running (permanently green indicator lights) • "Warning": Motor is still running (rotating yellow indicator lights) or has stopped (permanently yellow indicator lights) • "Alarm": Motor has stopped (flashing red indicator lights). Communication with the pump is possible by means of Grundfos GO Remote (accessory). The remote control enables further settings as well as reading out of a number of parameters such as "Actual value", "Speed", "Power input" and total "Power consumption". Pump and motor are mounted on a common steel base frame in accordance with ISO 3661. The back pull-out design together with a spacer coupling makes it possible to make service on the pump without dismantling the pump housing and motor from the base frame. This saves realignment of pump and motor after service. 1) Remove coupling. 2) Remove the bolts in the bearing bracket support foot. 3) Remove the bearing bracket from the pump housing.  Cast-iron parts have an epoxy-based coating made in a cathodic electro-deposition (CED) process. CED is a high-quality dip-painting process where an electrical field around the products ensures deposition of paint particles as a thin, well-controlled layer on the surface. An integral part of the process is a pretreatment. The entire process consists of these elements: 1) Alkaline-based cleaning. 2) Zinc phosphating. 3) Cathodic electro-deposition. 4) Curing to a dry film thickness 18-22 my m. The colour code for the finished product is NCS 9000/RAL 9005. Pump The pump housing has both a priming and a drain hole closed by plugs.





Position	Qty.	Description
		The impeller is a closed impeller with double-curved blades with smooth surfaces. The impeller is statically balanced according to ISO 1940-1 class G6.3 and hydraulically balanced to compensate for axial thrust. Wear rings used in pump housing and for impeller are made of bronze/brass or cast iron. The pump is fitted with an unbalanced rubber bellows seal with torque transmission across the spring and around the bellows. Due to the bellows, the seal does not wear the shaft, and the axial movement is not prevented by deposits on the shaft. Primary seal: - Rotating seal ring material: silicon carbide (SiC) - Stationary seat material: silicon carbide (SiC) This material pairing is used where higher corrosion resistance is required. The high hardness of this material pairing offers good resistance against abrasive particles. Secondary seal material: EPDM (ethylene-propylene rubber) EPDM has excellent resistance to hot water. EPDM is not suitable for mineral oils. The shaft is made of stainless steel and has a diameter of 32 mm where the coupling is mounted. The pump uses a spacer coupling between the pump and motor shaft.  Motor The motor is a totally enclosed, fan-cooled motor with principal dimensions to IEC and DIN standards and mounting designation B3 (IM 1001). Electrical tolerances comply with IEC 60034. The motor efficiency is classified as IE5 in accordance with IEC 60034-30-2. The motor requires no external motor protection. The motor control unit incorporates protection against slow- and quick-rising temperatures, e.g. constant overload and stalled conditions. The terminal box holds terminals for these connections: - one dedicated digital input - two analog inputs, 0(4)-20 mA, 0-5 V, 0-10 V, 0.5 - 3.5 V 5 V voltage supply to potentiometer and sensor - one configurable digital input or open-collector output - Grundfos Digital Sensor input and output 24 V voltage supply for sensors - two signal-relay outputs (potential-free contacts) - GENIbus connection - interface for Grundfos CIM fieldbus module. Technical data Liquid: Pumped liquid: Water Liquid temperature range: -25 .. 120 °C Liquid temperature during operation: 20 °C Density: 998.2 kg/m³ Technical: Rated flow: 135 m³/h Rated head: 7.9 m Actual impeller diameter: 178 mm Impeller nom: 200 mm Primary shaft seal: BQQE Secondary shaft seal: NONE Curve tolerance: ISO9906:2012 3B Materials: Pump housing: Cast iron EN-GJL-250

Position	Qty.	Description
		ASTM A48-40 B Impeller: Cast iron EN-GJL-200 ASTM A48-30 B Rubber: EPDM Wear ring mat.: High alloy brass(CuZn34Mn3Al2 Installation: Maximum ambient temperature: 50 °C Maximum operating pressure: 16 bar Pump inlet: DN 125 Pump outlet: DN 100 Pressure rating: PN 16 Coupling type: Spacer Base frame: EN / ISO Electrical data: Motor type: 112ME IE Efficiency class: IE5 Rated power - P2: 4 kW Mains frequency: 50 Hz Rated voltage: 3 x 380-500 V Rated current: 7.70-6.00 A Cos phi - power factor: 0.92-0.87 Rated speed: 180-2200 rpm Efficiency: 90.3% Motor efficiency at full load: 90.3 % Number of poles: 4 Enclosure class (IEC 34-5): IP55 Insulation class (IEC 85): F Lubricant type: Grease Others: Minimum efficiency index, MEI ≥: 0.61 ErP status: EuP Standalone/Prod. Net weight: 208 kg Gross weight: 223 kg Shipping volume: 0.554 m³

On request NKE 100-200/178 A2-F-A-E-BQQE 50 Hz




Description	Value
General information:	
Product name:	NKE 100-200/178
Product No:	A2-F-A-E-BQQE
EAN number:	On request
Technical:	
Rated flow:	135 m³/h
Rated head:	7.9 m
Actual impeller diameter:	178 mm
Impeller nom:	200 mm
Primary shaft seal:	BQQE
Secondary shaft seal:	NONE
Shaft diameter:	32 mm
Curve tolerance:	ISO9906:2012 3B
Pump version:	A2
Materials:	
Pump housing:	Cast iron
	EN-GJL-250
	ASTM A48-40 B
Impeller:	Cast iron
	EN-GJL-200
	ASTM A48-30 B
Material code:	A
Rubber:	EPDM
Code for rubber:	E
Wear ring mat.:	High alloy brass(CuZn34Mn3Al2
Installation:	
Maximum ambient temperature:	50 °C
Maximum operating pressure:	16 bar
Pump inlet:	DN 125
Pump outlet:	DN 100
Pressure rating:	PN 16
Coupling type:	Spacer
Wear ring(s):	neckring(s)
Base frame:	EN / ISO
Connect code:	F
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-25 .. 120 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	112ME
IE Efficiency class:	IE5
Rated power - P2:	4 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-500 V
Rated current:	7.70-6.00 A
Cos phi - power factor:	0.92-0.87
Rated speed:	180-2200 rpm
Efficiency:	90.3%
Motor efficiency at full load:	90.3 %
Number of poles:	4
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Motor protec:	YES
Motor No:	99305882
Lubricant type:	Grease
Controls:	
Control panel:	HMI300 - Advanced
Function Module:	FM300 - Advanced
Others:	
Minimum efficiency index, MEI ≥:	0.61





Description	Value
ErP status:	EuP Standalone/Prod.
Net weight:	208 kg
Gross weight:	223 kg
Shipping volume:	0.554 m ³
Config. file no:	99100731

On request NKE 100-200/178 A2-F-A-E-BQQE 50 Hz



On request NKE 100-200/178 A2-F-A-E-BQQE 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Exploded view




Sectional drawing (TM058200 for TPE2,TPE3)



TM058200

Exploded view (TM057026 for MGE model H/I)



Parts list NKE 100-200/178, Product No. On request
Valid from 1.3.2010 (1009)

Pos	Description	Annotation	Données de classification	Référence	Quantité	Unité
+	Motor				1	pcs
-	Coupling cpl.				1	pcs
89.b	Socket set screw		Length (mm): 8		2	
			Thread: M6			
89.d	Hex socket head cap screw		Length (mm): 16		12	
			Thread: M6			
89.p	Coupling female				1	
89o	Coupling part spacer side				6	
89o	Coupling part spacer side				1	
89r	Spacer sleeve				1	
89s	Spacer ring				1	
-	Nut				1	pcs
66	Washer		Designation: DIN 125 A2		1	
			Internal diameter: 19			
			Outer diameter: 34			
			Thickness: 3			
66a	Spring lock washer				1	
67	Nut		Thread: M18		1	
-	Cover cpl.				1	pcs
77	Cover				1	
-	Pump housing cpl.				1	pcs
6	Pump housing				1	
36	Nut		Thread: M10		8	
-	7	Coupling guard cpl.			1	pcs
-	7	Coupling guard cpl.			1	
7c	Spacer f/coupling guard				1	
7e	Hex socket head cap screw				3	
94	Lock nut		Thread: M6		2	
7b	Retainer for coupling guard				1	
7k	Hex socket head cap screw		Length (mm): 10		4	
			Thread: M6			
-	7.d	Foot for coupling guard			1	pcs
7d	Foot for coupling guard				1	
7h	Hex socket head cap screw				2	
7l	Support f/coupling guard foot				1	
66	Washer				2	
49	Impeller				1	pcs
72.a	O-ring		Diameter: 221,84		1	pcs
			Material type: EPDM			
			Thickness: 3,53			
-	86	Bearing bracket			1	pcs
28a	Hex head screw		Length (mm): 25		1	
			Thread: M12			
53.b	Spacer ring				1	
54	Ball bearing				2	
54a	O-ring		Diameter: 89,5		2	
			Material type: EPDM			
			Thickness: 3			
77a	Pan head screw				4	
86	Bearing bracket				1	
153a	Retaining ring				2	
156a	Bearing cover				2	
159a	V-ring				2	
-	90	Base plate			1	pcs
	Washer				16	
	Washer				4	
	Base plate				1	
	Support rail				2	
	Support block				2	

Pos	Description	Annotation	Données de classification	Référence	Quantité	Unité
7h	Hex head screw		Length (mm): 16		2	
			Thread: M8			
28a	Hex head screw		Length (mm): 45		4	
			Thread: M16			
28a	Hex head screw		Length (mm): 25		2	
			Thread: M12			
36	Nut		Thread: M10		8	
66	Washer				2	
66	Washer				2	
211	Hex head screw				4	
105	Shaft seal				1	pcs
105b	Spacer				1	pcs

Disclaimer: The information about the Grundfos pump in this document may be outdated.

Data may be subject to alterations without further notice.

Please contact us to verify the data above is still accurate/up-to-date.

All information is copyright Grundfos.



info@lenntech.com

<https://www.lenntech.com>

tel. +31 152 610 900

fax. +31 152 616 289